

TENDER NOTICE

INVITATION FOR BIDS

Sealed Tenders are invited from GST & Income Tax registered Manufacturer/Firms or their Authorized Distributors/Dealers/Suppliers for Supply of **Various Items**, on item rate Basis for Various Departments of the Islamia University of Bahawalpur on FOR basis as per detail given below:-

Sr-No.	Category (Specifications in Tender Documents)	Estimated Cost	2% Bid Security
A	IT Items for Alumni & Senior Tutor	Rs.790,000/-	Rs.15,800/-
В	Misc Items for Security Branch	Rs.1,590,000/-	Rs.31,800/-
С	Binding Material for Main Library	Rs.480,000/-	Rs.9,600/-

- 1. Interested bidders may get the Tender Documents containing detailed specifications, terms and conditions from the Purchase Section, Treasurer's Office Abbasia Campus, the Islamia University of Bahawalpur during office hours 8:00 A.M. to 4:00 P.M. on submission of written application on letter head and a copy of CNIC OR can be down loaded from the IUB Website www.iub.edu.pk or PPRA website www.ppra.punjab.gov.pk on payment of (nonrefundable fee) Rs.1000/- through HBL Bank challan in A/C 14730000010403 or pay order in the name of the Treasurer Islamia University of Bahawalpur.
- 2. **2% bid security** (**re-fundable**) of the total estimated cost as mentioned above in shape of Bank Guarantee shall be attached with the bid, otherwise bid will not be entertained.
- 3. <u>Single Stage Two Envelope</u> bidding procedure will be adopted as per PPRA Rules 38- 2(a). The Envelope shall be marked as "TECHNICAL PROPOSAL" AND "FINANCIAL PROPOSAL" in legible letters. Financial Proposal of bids found technically non-responsive shall be returned un-opened.
- 4. Procurement shall be governed under the Punjab Procurement Rules 2014.
- 5. The rates should be quoted inclusive all taxes. Copy of paid bank challan Professional tax also be Provided.
- 6. The procuring agency may reject all bids or proposals at any time prior to the acceptance of a bid or proposal. The procuring agency shall upon request communicate to any bidder, the grounds for rejection of all bids or proposals, but shall not be required to justify those grounds.
- 7. Tender must reach in the Treasurer's Office on or before **20-05-2021**by **11:00 A.M.** which will be opened on the same day at **11:30 AM** in the presence of bidders or their representatives.
- 8. All bids submitted after the given time, incomplete and alternate bidding shall not be accepted.
- 9. All prevailing taxes will be applicable as per Govt. Rules & Regulations, i.e. (income tax, Sales tax, etc).
- 10. The offered rates shall be valid upto 90-days from the date of opening of the tender.
- 11. In case of closed/forced holidays, tender opening time/date will be considered as the next working day.



Treasurer The Islamia University of Bahawalpur Abbasia Campus, Bahawalpur. Phone: 062-9250245, 9250328 Fax No: 062-9250255

PROCUREMENT OF IT ITEMS FOR ALUMNI & SENIOR TUTOR TENDER-A FORM

I+	ame Snace		OTV	Rate per items
8.	Professional Tax No:			
6.	General Sale Tax No:	7. Income Tax No		
5.	Tender Fee Challan No. & amount	CDR No. & Amount_		
3.	Phone No:	_ 4. Fax No:		
2.	Mailing Address:			
1.	Name of Firm:			

	8. Professional Tax No:		
Sr.	Items Specs	QTY	Rate per items
	·		with all taxes
1	Specifications:	2	
_	item name: Camera		
	Lens compatibility: E-mount lenses		
	No of pixels effective: Approx. 24.2 megapixels		
	No of pixel total: Approx. 25.0 megapixels		
	Sensor Type: APS-C type (23.5 x 15.6 mm), Exmor® CMOS sensor		
	Anti Dust system: Charge protection coating on optical filter and image sensor shift mechanism		
	Recording format: JPEG (DCF Ver. 2.0, Exif Ver.2.31, MPF Baseline compliant), RAW (ARW 2.3 format)		
	Picture effect: 8 types: Posterization (Color), Posterization (B/W), Pop Color, Retro Photo, Partial Color		
	(R/G/B/Y), High Contrast Monochrome, Toy Camera (Normal/Cool/Warm/Green/Magenta), Soft High-		
	key, Rich-tone Monochrome		
	Creative Style: Standard, Vivid, Neutral, Clear, Deep, Light, Portrait, Landscape, Sunset, Night Scene,		
	Autumn leaves, Black & White, Sepia, Style Box (1-6), (Contrast (-3 to +3 steps), Saturation (-3 to +3 steps), Sharphood (-3 to +3 steps))		
	steps), Sharpness (-3 to +3 steps)) Picture Profile: Yes (Off/PP1-PP10) Parameters: Black level, Gamma (Movie, Still, Cine1-4, ITU709,		
	ITU709 [800%], S-Log2, S-Log3, HLG, HLG1-3), Black Gamma, Knee, Color Mode, Saturation, Color Phase,		
	Color Depth, Detail, Copy, Reset		
	Color Space: sRGB standard (with sYCC gamut) and Adobe RGB standard compatible with TRILUMINOS		
	Color		
	Recording format: XAVC S, AVCHD format Ver. 2.0 compliant		
	Video Compression: XAVC S: MPEG-4 AVC/H.264, AVCHD: MPEG-4 AVC/H.264		
	Image pixels: XAVC S 4K: 3840 x 2160 (30p, 100 M), 3840 x 2160 (24p, 100 M), 3840 x 2160 (30p, 60 M),		
	3840 x 2160 (24p, 60 M), XAVC S HD: 1920 x 1080 (120p, 100M), 1920 x 1080 (120p, 60M), 1920 x 1080		
	(60p, 50M), 1920 x 1080 (30p, 50M), 1920 x 1080 (24p, 50M), 1920 x 1080 (60p, 25M), 1920 x 1080		
	(30p, 16M), AVCHD: 1920 x 1080 (60i, 24M, FX), 1920 x 1080 (60i, 17M, FH) HDMI output: 3840 x 2160 (30p), 3840 x 2160 (25p), 3840 x 2160 (24p), 1920 x 1080 (60p), 1920 x 1080		
	(60i), 1920 x 1080 (50p), 1920 x 1080 (50i), 1920 x 1080 (24p), YCbCr 4:2:2 8 bit / RGB 8 bit		
	Shutter AWB lock: Yes (Shut. Halfway Down/ Cont. Shooting/ Off)		
	Focus Type: Fast Hybrid AF (phase-detection AF/contrast-detection AF)		
	Focus sensor: Exmor® CMOS sensor		
	Focus point: 425 points (phase-detection AF) / 425 points (contrast-detection AF)		
	Focus sensitivity: EV-2 to EV 20 (ISO 100 equivalent with F2.0 lens attached)		
	Focus area: Wide (425 points (phase-detection AF), 425 points (contrast-detection AF)) / Zone / Center /		
	Flexible Spot (S/M/L) / Expanded Flexible Spot / Tracking (Wide / Zone / Center / Flexible Spot (S/M/L) /		
	Expanded Flexible Spot) AF Illuminator: Yes (with built-in LED type)		
	View finder: 1.0 cm (0.39 type) electronic viewfinder (color)		
	No of dots: 2,359,296 dots		
	LCD: 2.95 in (3.0-type) wide type TFT touch		
	Shutter type: Electronically controlled, vertical-traverse, focal-plane type		
	Image Stabilization: Image Sensor-Shift mechanism with 5-axis compensation (compensation depends		
	on lens specifications)		
	NFC: yes		
	WLAN: yes		
	Bluetooth: yes HD output: yes		
	Mic Terminal yes		
	headphone terminal yes		
	Lens compensation: Peripheral Shading, Chromatic Aberration, Distortion		
	battery model: One rechargeable battery pack NP-FZ100		
	Approx. 720 shots (Viewfinder) / Approx. 810 shots (LCD monitor) (CIPA standard)		
	Dimensions: Approx. 4 3/4" x 2 3/4" x 2 3/4", Approx. 4 3/4" x 2 3/4 "x 2 3/8" (from grip to monitor),		
	Approx. 120.0 mm x 66.9 mm x 69.3 mm, Approx. 120.0 mm x 66.9 mm x 59.0 mm (grip to monitor)		

2 Septification: Heart type: handheld stabilizer Heart type: handheld				
Team type: Pandheld stabilizer Frankheld	2	Specification:	2	
Handland Statillar for multiple devices Operation Voltage Mair 12.8 × Sandard 11.1 v Mair 18.8 v	-			
Docardion Voltage Main. 12.6 v Standard 1.1 km 1.8 a V		item type: nandneid stabilizer		
Sandard: 11.4 v Mar. 3 & v Oceation Transporture Nat. 49°C Standard: 25°C Min: -10°C Selter Authorite Max. 71 Door on Scotter Standard Standard: 25°C Min: -10°C Selter Authorite Max. 71 Door on Scotter Standard Standard: 23°C Min: 1.00°C Selter Authorite Max. 71 Door on Scotter Standard: 100°C From Sta		Handheld stabilizer for multiple devices		
Sandard: 11.4 v Mar. 3 & v Oceation Transporture Nat. 49°C Standard: 25°C Min: -10°C Selter Authorite Max. 71 Door on Scotter Standard Standard: 25°C Min: -10°C Selter Authorite Max. 71 Door on Scotter Standard Standard: 23°C Min: 1.00°C Selter Authorite Max. 71 Door on Scotter Standard: 100°C From Sta		Operation Voltage Max : 12.6 v		
Output Yorking Standard : 5 v Operation Femorature Max : 7 h Charger Time Tostanded : 2 h Charger Time Standard : 2 h Tollowing Deviation in Michion State : Max : 2 0.01 * Min : 2 0.01 * Till Mechanical Range : Standard : 310 * Chol Mechanical Range : Standard : 310 * Port and transparent parage Standard : 320 * Para and transparent parage Standard : 320 * Void Paywood : Max : 720 g Min : 210 g Tollowing Deviation in Michion State : Max : 2 0.01 * Till Mechanical Ranger : Standard : 320 g Tollowing Deviation in Michion State : Max : 2 0.01 * Till Mechanical Ranger : Standard : 320 g Tollowing Deviation in Michion State : Max : 2 0.01 * Wolf Paywood : Max : 720 g Min : 210 g Tollowing Deviation in Min : 100 g Tollowing Deviation in Till : 100 g Toll				
Operation Temperature Max. 19 if Standard : 25 °C Min : -10 °C Basinery Resident Max. 19 if Charging Time Standard : 21 Octors 40 Octors				
Battery Runtime Mais: 7 h. Changing Time Standards: 2 h. 2000 nA 500 nA		•		
Charging Time Standard : 2 h 2000 AM SOLID A Stabilizer Following Deviation in Moston State : Max : ±0.04* Min : ±0.05* Following Deviation in Moston State : Max : ±0.04* Min : ±0.01* Bold Indecisance Home : Standard : \$20.4* Para sati movement angle range Standard : \$30.0* Unlimited rotation Valid Pysicon : Max : 270 g Min : 130 g Comm M2 3. Specification: Item type: tripool Paramatin (India dampening Read Integrated Para A Thi Lata Integrated Paramatin Integrated				
200 m/s 300 m/		Battery Runtime Max : 7 h		
Following Deviation in Marketin State: 1 Mar.: 1.0.3 ** Min.: 1.0.05 ** Following Deviation in State State Mar.: 2.0.0 ** Min.: 1.0.05 ** Following Deviation in State State Mar.: 2.0.0 ** Mar.: 1.0.0 ** Min.: 1.0.0 *		Charging Time Standard : 2 h		
Policioning Pevilation in Static State Max : 2.06 * Min : 2.001 * Titl Mechanical Prage : Standard : 330 * Min Mechanical Prage : Standard : 320 * Unimitate rotation Standard : 3		2000 mA 500 mA Stabilizer		
Policioning Pevilation in Static State Max : 2.06 * Min : 2.001 * Titl Mechanical Prage : Standard : 330 * Min Mechanical Prage : Standard : 320 * Unimitate rotation Standard : 3		Following Deviation in Motion State: Max: ± 0.3 ° Min: ± 0.05 °		
Till Mechanical Range : Sandard : 320 * Roll Rechanical Range : Sandard : 324 * Pan and movement angle ranger Sandard : 340 * Unlimited roution : 22 pkm : 130 g Cone 10.* 3. Specification: Hent type: tripod Panoramic fluid dampening head Integrated Pan - 78 to Lock Signature in Till Lock Signatur				
Boll Mechanical Ranges - Standard : 3247 Pan asis movement apple range Standard : 380 * Unlimited rotation Valid Pylacid : Max : 720 g Min : 300 g Crimer Mi 3. Specification: Hem type: tripod Parromanic Rand dampening head Integrated Pan & Tâl Lucis Richard Standard : 300 min : 300 g Parromanic Rand dampening head Integrated Pan & Tâl Lucis Richard Standard : 300 min : 300 g Parromanic Rand dampening head Integrated Pan & Tâl Lucis Richard : 100 to 100 g / 2105 max loading Trowl Case and Shandard Starp Included Specifications: VF 1500 Wide Tripod Section : 300 to 100 g / 2105 max loading Trowl Case and Shandard Starp Included Specifications: VF 1500 Wide Tripod Section : 300 to 100 g / 2105 max loading Trowl Case and Shandard Starp Included Specifications: VF 1500 Wide Tripod Max Regist : 560 m / 23 dinch Todde leaght : 560 m / 23 dinch Model VF 1715 Moterial Riskid Size (18**H; 300 to 130 P8**D 100 mm / 3 1*3.1*3.0 mch Rand Gamber Cofform / 23 dinch Rand Gamber Cofform / 23 dinch Trowl Cofform / 25 dinch Rand Gamber Cofform / 25 din				
Pan asid movement angle range: Standard : 380 ° Unlimited rotation Valid Payload : Max : 720 g Min : 130 g Core Min : 130 g C				
Unimited rotation Valid Pypiosi : Max : 70g Min : 130 g Crane M2 Specification: Hem type: tripod Pacroansic fluid dispersing breat Integrated Pan & Titt Locks Fill-Lock ig System extends up to 85° max height Aluminum lac construction Supports up to 10kg / 22lb const loading Travel Case and Shoulder Strap included System of the Construction Supports up to 10kg / 22lb const loading Travel Case and Shoulder Strap included System of the Construction Supports up to 10kg / 22lb construction Max Height 10kg / 22lb construction Max Height 10kg / 22lb construction Max Load: 10kg / 28lbs In The Roa: VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card 4. Specification: Hen type: lens for camera Lens type: 30mm F1.1 a DC DN Mount-For El Mount Max Max Aperture F1.4 Minimum Aperture F1.1 Mini				
Valid Payload : Max : 720 g Min : 130 g		Pan axis movement angle range: Standard: 360°		
Specification: Item type: tripod Panoramic fluid dampening head Panoramic fluid dampening fluid flui		Unlimited rotation		
Specification: Item type: tripod Panoramic fluid dampening head Panoramic fluid dampening fluid flui		Valid Payload: Max: 720 g Min: 130 g		
Herm Lype: Lindod				
Herm Lype: Lindod	2	Specification	2	
Pancramic fluid dampening head integrated Pan & Tit Lock	<u>3.</u>	<u>specification:</u>		
Pancramic fluid dampening head integrated Pan & Tit Lock		Item type: tripod		
Integrated Pan & Tit Locks Fill-Juck (sp. system setends up to 55' max height Aluminum leg construction Supports up to 10g/ 22 bits max loading Travel Case and Shoulder Strap included Supports up to 10g/ 22 bits max loading Travel Case and Shoulder Strap included Supports up to 10g/ 22 bits max loading Travel Case and Shoulder Strap included Supports up to 10g/ 27 bits Su				
File Jock Ieg System extends up to 65" max height Aluminum lag construction Supports up to 106/2 / 27list max loading Travel Case and Shoulder Stap Included Specifications: V1-1500 Widen Trand Start Case Specifications: V1-1500 Widen Trand Start Case Specifications Start Case Specifications Start Case Specifications Start Case Specifications Spec		. •		
Auminum Re; construction Supports up to 188/ 228b max loading Travel Case and Shoulder Strap included Specification: VT-1500 Video Tripod Leg material suminum alloy, Section: S-ections Min. Height Score 72.5 sinch, Min. Height Score 72.5 sinch, Min. Leght Score 72.5 sinch, Pan totate angle: 180-degree. Bass score VICA39: Max. Leght 48y / 88 bs. In The Box VIT-1500 Thrond, VT-1510 Fluid Head, Travel 2p Bag, Shoulder Strap, User Manual & Warranty Card Specification: Ikem type: lens for camera Lens type: 30mm E1.1 d.C DN Mount: For Mount Manufacturer: Sigma 5.1 appherical and 1 double-sided aspherical Minimum Aperture F1.5 Disphragm Blades 9 Number of groups 7 Special elements 9 Number of groups 7 Specification: Ikem type: Lens for camera MOUNT E-mount for for f				
Supports up to 10kg / 27lbs max loading Travel Case and Shoulder Strap Included Specifications: VT-1500 Video Tripod Legs material: aluminum alloy. Section: 3 actions. Max. Height: 166cm / 73.6mch. Min. Height: 160cm / 73.6mch. Min. Height: 160cm / 73.6mch. Min. Load: 10kg / 20lbs. VT-1510 Mind Drag Pon ITH Head Model: VT-1510. Marterial: Plastic. Size (1°8*H about 180°8 07lbmm / 5.1°3.1°3.9 inch. Base diameter: 6flum / 7.36inch. Parn orbate angle: 360-degree. Base screw: UNCL/8". Cameria screw: UNCL/8". Cameria screw: UNCL/8". Max. load: 16kg / 8.8llos. In The Dox: VT-1500 Tippod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warramy Card 4 Specification: Hern type: lens for camera Lens type: 3 somm F1.4 DC In Minimum Aperture F1.4 Minimum Aperture F1.4 Minimum Aperture F1.4 Minimum Aperture F1.5 Diaphragm Blades: 9 Number of group: 5 Specification: Hern type: Lens for camera MOUNT F emount ColonAT 35 mm full frame F0.4 LENSTH (180 Specification: Hern type: Lens for camera MOUNT F emount ColonAT 35 mm full frame F0.4 LENSTH (180 Specification: Hern type: Lens for camera MOUNT F emount ColonAT 35 mm full frame F0.4 LENSTH (180 Specification: Hern type: Lens for camera MOUNT F emount ColonAT 35 mm full frame F0.4 LENSTH (180 Specification: Hern type: Lens for camera MOUNT F emount ColonAT 35 mm full frame F0.4 LENSTH (180 Specification: Hern type: Lens for camera MOUNT F emount ColonAT 35 mm full frame F0.4 LENSTH (180 Specification: Hern type: Lens for camera MOUNT F emount ColonAT 35 mm full frame F0.4 LENSTH (180 Specification: Hern type: Lens for camera MOUNT F emount ColonAT 35 mm full frame F0.4 LENSTH (180 Specification: Hern type: Lens for camera MOUNT F emount ColonAT 35 mm full frame F0.4 LENSTH (180 Specification: Hern type: Lens for camera MOUNT F emount ColonAT 35 mm full frame F0.4 LENSTH (180 Specification: Hern type: Lens for ca				
Travel Case and Shoulder Strap Included Specifications: VT-1500 Video Tripod Legs material aluminum alloy. Sections 3 sections. Max. Height 166cm / 55inch. Max. Height 166cm / 55inch. Max. Losd: 100k / 225m. Max. Height 166cm / 25inch. Max. Losd: 100k / 225m. Max. Height 166cm / 25inch. Max. Losd: 100k / 225m. Losd: 100k / 225m. Losd: 100k				
Specifications: VT-1500 Video Tripod Leg material: aluminum alloy. Section: 3-sections. Max. Height: 156cm / 23-sinch. Min. Load: 106 / 22bs. Min. Min. Load: 116 / 22bs. Min. Min. Load: 116 / 22bs. Min. Min. Load: 116 / 22bs. Min. Load				
VT-1300 Video Trippod Legs material aluminum alloy, Section: 3-sections. Max. Height: 66cm / 56inch. Min. Height: 66cm / 22 Sinch. Max. Load: 10ig / 22 lbs. VT-1310 Material: Flastic. Size (1-87*) shoots 13 00*9 (27 lbs.) VT-1310 Material: Flastic. Size (1-87*) shoots 13 00*9 (27 lbs.) VT-1310 Material: Flastic. Bias screw. UNC3/8*. Camera screw. UNC3/8*. Camera screw. UNC3/8*. Camera screw. UNC3/8*. Max. load: 46 g/s 8.lbs. In The Boo: VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card 4 Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: Fore Mount Manufacture: Signs Minimum Aperture: E16 Dipolnyan Blades Number of elements: 9 Number of elements:		·		
Legs material aluminum alloy. Section 3-sections. Max. Height: 166cm / 25.6inch. Min. Height: 166cm / 25.6inch. Folided length: 66cm / 25.8inch. Folided length: 66cm / 25.8inch. Folided length: 66cm / 25.8inch. Max. Load: 100g / 22lbs. VT-1510 Fluid Drag Pan Till Head Model: VT-1510 Material Plastic. Size (L*B*H): about 130*80*100mm / 5.1*3.1*3.9 inch. Base disurers: 60mm / 2580 degree. Base screw. WCS/8* Max. load: 48g / 88lbs. In The Box VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warramty Card 4 Specification: Rem type: 30mm FLA DC ON Mount: For E Mount Manufacturer: Sigma Max. Aperture F1.4 Minimum Aperture F1.0 Diaphragm Blades 9 Number of elements 10.6x Minimum Florous 0.30 m (11.81*) Minimum Florous 0.		·		
Section 3-sections				
Max. Height: 166cm / 25.5 inch. folded length: 66cm / 25.5 inch. folded length:		Legs material: aluminum alloy.		
Min. Height: 60cm (2.3 finch. Folded leight: 60cm (2.3 finch. Max. Load: 10kg (2.7 lbs. VT-1510 Mild Orag Pan Tilt Head Model: VT-1510 Material: Plastic. Size (1.8 H); about 130 %97 010cm (5.1*3.1*3.9 inch. Base diameter: 60mm (2.3 finch. Pan rotate angle: 360 degree. Base screw: UNCJ8*: Camera screw: UNCJ4*: Max. load: 4kg (8.8 lbs. In The Box: VT-1500 Tipod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card 4 Specification: Hem twpe: lens for camera Less type: 30cm (1.1 a UT) Max. Aperture F1.4 Minimum Aperture F36 Diaphragm Blades: 9 Number of groups: 7 Special elements/coatings: 1 aspherical and 1 double-sided aspherical Minimum Aperture F36 Diaphragm Blades: 9 Number of groups: 7 Special elements/coatings: 1 aspherical and 1 double-sided aspherical Minimum Magnification: 0.14x Motor Type: Stepper motor Full Time Manual No Weight: 265 g (0.58 lb) Dimensions (Dxt): 65 x 73mm (2.6 x 2.9 in.) Filter Thread: 52mm (2.6 x 2		Section: 3-sections.		
Min. Height: 60cm (2.3 finch. Folded leight: 60cm (2.3 finch. Max. Load: 10kg (2.7 lbs. VT-1510 Mild Orag Pan Tilt Head Model: VT-1510 Material: Plastic. Size (1.8 H); about 130 %97 010cm (5.1*3.1*3.9 inch. Base diameter: 60mm (2.3 finch. Pan rotate angle: 360 degree. Base screw: UNCJ8*: Camera screw: UNCJ4*: Max. load: 4kg (8.8 lbs. In The Box: VT-1500 Tipod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card 4 Specification: Hem twpe: lens for camera Less type: 30cm (1.1 a UT) Max. Aperture F1.4 Minimum Aperture F36 Diaphragm Blades: 9 Number of groups: 7 Special elements/coatings: 1 aspherical and 1 double-sided aspherical Minimum Aperture F36 Diaphragm Blades: 9 Number of groups: 7 Special elements/coatings: 1 aspherical and 1 double-sided aspherical Minimum Magnification: 0.14x Motor Type: Stepper motor Full Time Manual No Weight: 265 g (0.58 lb) Dimensions (Dxt): 65 x 73mm (2.6 x 2.9 in.) Filter Thread: 52mm (2.6 x 2		Max. Height: 166cm /65inch.		
Max. Load: 10lg (272lbs. VT-1510 Material: Plastic. Sire (1.49 Fil.) about 130°90 100mm /5.1°3.1°3.9 inch. Base diameter: 60mm /2.36inch. Parr lottat angle: 360-degree. Base screw: UNCJ38". Camera screw: UNCJ38". Camera screw: UNCJ4", Max. load: 4kg /8.8lbs. In The Bos: VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card 4 Specification: Item type: lens for camera Lens type: 30mm F1.4 OC DN Mount: For E Mount Manufacturer: Sigma Max. Aperture F1.4 Minimum Aperture F1.4 Minimum Aperture F1.6 Diaphragm Bades 9 Number of elements 9 Number of element		Min. Height: 60cm /23.6inch.		
Max. Load: 10lg (272lbs. VT-1510 Material: Plastic. Sire (1.49 Fil.) about 130°90 100mm /5.1°3.1°3.9 inch. Base diameter: 60mm /2.36inch. Parr lottat angle: 360-degree. Base screw: UNCJ38". Camera screw: UNCJ38". Camera screw: UNCJ4", Max. load: 4kg /8.8lbs. In The Bos: VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card 4 Specification: Item type: lens for camera Lens type: 30mm F1.4 OC DN Mount: For E Mount Manufacturer: Sigma Max. Aperture F1.4 Minimum Aperture F1.4 Minimum Aperture F1.6 Diaphragm Bades 9 Number of elements 9 Number of element		Folded length: 66cm /25.9inch.		
V-1-1510 Puterlair Bastic. Size (L*B*H); about 130*80*100mm/5.1*3.1*3.9 inch. Base diameter: 60mm / 2.3 dinch. Pan rotate angle: 360-degree. Base screw: WICKJ8** Camera screw: WICKJ8** Max. load: 44g /8.8 lbs. In The Box: VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card 4 Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For F. Mount Manufacturer sigma Max Aperture F1.4 Minimum Aperture F1.6 Diaphragm Biades 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 30.30 m (11.81*) Maximum Magnification 0.140 North Type 30mm F1.4 DC DN Momentions (DK1) 65 x 73mm (2.6 x 2.9 in.) Filter Throad 52mm 5 Specification: Item type: Lens for camera MOUNT Emount FOOMAT 35 mm full frame FOCAL LENGTH (MM) 8 S S MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELENS 1.8 MM) 20* ANGLE OF VIEW (AS-S) 1972 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.68 ft (0.8 m) MAXIMUM APERTURE (F) 1.8 MINIMUM MASHIFICATION (STEAD/SHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, BUSINESS 1.1/4" (78 x 82 mm) VEIGHT 13.1 to (371 g) What's in The Box Hood (model): ALC-5475				
Model: VT-1510. Material: Plastic.				
Size (L*B*H): about 130*80*100mm /5.1*3.1*3.9 inch. Base diameter: 60mm /2.3 clinch. Pael nortate angle: 360-degree. Base screw: UNCX/8". Camera screw: UNCX/8". Max. load: 48g, /8.8lbs. In The Box: VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card 4 Specification: Item type: lens for camera Less type: 30mm F1.4 DC DN Mount: For E Mount Mauntacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of groups 7 Special dements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81*) Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g(0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm 5 Specification: Item type: Lens for camera MOUNT E-miount FOOMAT 35 mm full frame FOCAL LENGTH (MM) 8 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / LENGTH (MM) 8 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / LENGTH (F1.18 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCLUAR APERTURE (F) 1.8 MINIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 THE LECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMMSIONS (DIAMETERX LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WeiGHT 13.1 to (371 g) What's in the Box Hood (model): ALC; 94150 Lens front cap: ALC; 6765				
Base dameter. 50mm /2.3 Sinch. Parriotate angle: 360-degree. Base screw: UNCJ/8". Camera screw: UNCJ/8". Camera screw: UNCJ/8". Camera screw: UNCJ/8". Max. load: 48g /8.8 lbs. In The Box: VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card 4				
Pan rotate angle: 360-degree. Base serve: UNC3/8". Camera screw: UNC1/4". Max Load: 48g /8 Bibs. In the Box: VT-1500 fripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & WarranyCard 4 Specification: Item type: lens for camera Less type: 30mm F14 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F1.6 Diaphragm Blades 9 Number of groups 7 Special Jeements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 mt (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.98 lb) Dimensions (DAL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread Szmm 5 Specification: Item type: Lens for camera MOUNT E-mount FOOMAT 35 mm full frame FOCAL LENGTH (MM) 8 3 SI MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (ASS-C) 19"2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (MM) 67 INASS TSABILIZATION (STEADYSHOT) - (body-integrated) TIELE DIAMETER (TAST LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) Weight T1.3.1 to (271 g) What's in the Box Hood (model): ALC-5H150				
Base screw: UNCJ/8". Camera screw: UNCJ/8". Max. load: 48g /8, 8lbs. In The Box: VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card 4 Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount-For Mount Manufacturer: Sigma Max Aperture F1.6 Diaphragm Blades: 9 Number of elements: 9 Number of groups: 7 Special elements/coating: 1 aspherical and 1 double-sided aspherical Minimum Aperture F1.6 Diaphragm Blades: 9 Number of groups: 7 Special elements/coating: 1 aspherical and 1 double-sided aspherical Minimum Focus Minimum Focus 0.30 mt (11.81") Maximum Magnification: Full Time Manual No Weight: 265 g (0.58 lb) Dimensions (Dk1): 65 x 73mm (2.6 x 2.9 in.) Filter Thread: 52mm 5 Specification: Item type: Lens for camera MOUNT: E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS; LEMENTS: 8-9 ANGLE OF WIEW (35 MM) 29° ANGLE OF WIE				
Camera screw: UNCI/A". Max. load: 48g / 88.lbs. In The Box: VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Signa Max Aperture F1.4 Minimum Aperture F1.6 Diphragm Blades 9 Number of elements 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 26s g (0.58 lb) Dimensions (Dx1) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (18 MM) 29* ANGLE OF VIEW (18 MM) 67 MINIMUM APERTURE (F) 1.2 APERTURE RUBADES 9 CIRCULAR APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE (F) 25 APERTURE BLADES 9 CIRCULAR APERTURE (F) 25 APERTURE BLADES 9 CIRCULAR APERTURE (F) 27 APERTURE BLADES 9 CIRCULAR APERTURE (F) 28 MINIMUM MAGNIFICATION RATIO (X) 0.13 FLITER DIAMETER (MM) 67 MINACE STABILIZATION (STEADYSHOT) - (body-integrated) TILLECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROund, Dayonet type MINIMON (13 oft) 19 What's in The Box Hood (model): ALC-SH150 Lens front cap. ALC-F675				
Max. load: 4kg /8.8lbs. in The Box VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer Sigma Max Aperture F1.4 Minimum Aperture F1.6 Diaphragm Blades 9 Number of groups 7 Special elements / 20.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (Dx1) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm 5 Specification: Item type: Lens for camera MOUNT Emount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29' ANGLE OF VIEW (135 MM) 29' ANGLE OF VIEW (145 MM) 29' ANGLE OF VI				
In The Box: VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual & Warranty Card Specification: Item type: lens for camera Lens type: 90mm F1.4 DC DN Mount: For E Mount Manufacturer. Signa Max Aperture F1.4 Minimum Aperture F1.6 Diphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lib) Dimensions (Dx1) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52m Specification: Item type: Lens for camera MOUNTE-mount Hem type: Lens for camera MOUNTE-mount FORNAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (148 MM) 29* ANGLE OF VIEW (148 MM) 2				
4 Specification: Item type: lens for camera Lens type: 30mm f1.4 DC DN Mount: for E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F1.6 Diaphragm Blades 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (Dxi) 65 x 73mm (2.6 x 2.9 in.) Filter Thread \$22mm\$ 5 Specification: Item type: Lens for camera MOUNT Femount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29" ANGLE OF VIEW (APS-C) 19"2 MAXIMUM APERTURE (F) 1.3 MINIMUM APERTURE (F) 1.3 MINIMUM APERTURE (F) 1.3 MINIMUM APERTURE (F) 2 APERTURE BLADES 9 CIRCULAR APERTURE VES MINIMUM MONIFICATION RATIO (X) 0.13 FILTER DLAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, Buyonet type IMANSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 or (371 g) What's in the Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S				
Specification: Item type: lens for camera Lens type: 30mm F1.4 DC N		In The Box: VT-1500 Tripod, VT-1510 Fluid Head, Travel Zip Bag, Shoulder Strap, User Manual &		
Item type: lens for camera	i			
Item type: lens for camera		Warranty Card		
Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of elements 9 Number of eroups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (Dk1) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm 5 Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 3.5 MM FQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (73 MM) 29" ANGLE OF VIEW (74 SMM) 29" ANGLE OF VIEW (74 SMM) 29" ANGLE OF VIEW (75 C.19 T.2 ANGHAMMA PERTURE (F) 1.3 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE YES MINIMUM PERTURE (F) 2.3 APERTURE BLADES 9 THE DIAMETER (MM) 67 IMAGE STABILEATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, Bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 1.3.1 or (371 g) What's in The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S	4		1	
Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F1.6 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm 5 Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / LELMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (APS-C) 19*2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE Yes MINIMUM FOR DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, Bayonet type IMAENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) Weight 1.3.1 oz (37 1g) What's in The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S	4	Specification:	1	
Manufacturer: Sigma Max Aperture F1.6 Diaphragm Blades 9 Number of elements 9 Number of elements 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm Specification: 1 Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29" ANGLE OF VIEW (35 MM) 29" ANGLE OF VIEW (APS-C) 19*2 MAXIMUM APERTURE (F) 1.3 MINIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEAD/SHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, Bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 or (371 g) What's in The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S	4	Specification:	1	
Manufacturer: Sigma Max Aperture F1.6 Diaphragm Blades 9 Number of elements 9 Number of elements 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm Specification: 1 Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29" ANGLE OF VIEW (35 MM) 29" ANGLE OF VIEW (APS-C) 19*2 MAXIMUM APERTURE (F) 1.3 MINIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEAD/SHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, Bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 or (371 g) What's in The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S	4	Specification: Item type: lens for camera	1	
Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (Dxt.) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm 5 Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS, ELEMENTS 8-9 ANGLE OF VIEW (APS-C) 19"2 MAXIMUM APERTURE (F1.18 MINIMUM APERTURE (F1.18 MINIMUM APERTURE (F1.18 MINIMUM APERTURE (F1.22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FACTOR CATION (NO 1.03 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, Bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 or (371 g) What's in The Box Hood (Imode): ALC-SH150 Lens front cap: ALC-E67S	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN	1	
Minimum Aperture F16 Diaphragm Blades 9 Number of groups 7 Special elements (20 number of groups 7 Special elements (20 number of groups 7 Special elements (20 number of groups 7 Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (0xL) 65 x /73mm (2.6 x 2.9 in.) Filter Thread 52mm 5 Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPs / ELEMENTS 8-9 ANGLE OF VIEW (135 MM) 29° ANGLE OF VIEW (146 NM) 29° ANGLE OF VIEW (147 NM) 29° ANGLE OF VIEW (147 NM) 29° ANGLE OF VIEW (147 NM) 29° ANGLE OF STRUIP (150 NM) 29° ANGLE	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount	1	
Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (MS-C) 19"2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE YES MINIMUM APERTURE YES MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADVSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROund, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's in The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma	1	
Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (0xt) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (APS-C) 19*2 ANGLE OF VIEW (APS-C) 19*2 ANGLE OF VIEW (APS-C) 19*2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE YES MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADVSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROund, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's in The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4	1	
Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm 5 Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM FOULVIALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (35 FU) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM MACONIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 MAGG STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type MENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's in The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16	1	
Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm 5 Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS/ ELEMENTS 8-9 ANGLE OF VIEW (APS-C) 19"2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE (F) 25 MINIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, bayonet type ROUND, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's in The Box Hood (model): ALC-SH150 Lens front cap: ALC-F675	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9	1	
Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (50 g (0.58 lb) Dim	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9	1	
Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (0xL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm 5 Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (475-C) 19°2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE YES MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (5TEAD/SHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, Bay Can be a compared to the compared of the com	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7	1	
Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm Specification: Item type: Lens for camera MOUNT e-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (36 PS-C) 19*2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 2.2 APERTURE BLADES 9 CIRCULAR APERTURE (F) 2.2 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEAD/SHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, BOWN AND AND AND AND AND AND AND AND AND AN	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical	1	
Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm 5 Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MPS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (APS-C) 192 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE (F) 22 (CIRCULAR APERTURE F) MINIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (modde): ALC-SH150 Lens front cap: ALC-F67S	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81")	1	
Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm 5 Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29" ANGLE OF VIEW (APS-C) 19"2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MACNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x	1	
Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / LEMENTS 8-9 ANGLE OF VIEW (APS-C) 19*2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x	1	
Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / LEMENTS 8-9 ANGLE OF VIEW (APS-C) 19*2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No	1	
Filter Thread 52mm Specification: Item type: Lens for camera MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (APS-C) 19°2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE YES MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's in The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No	1	
Item type: Lens for camera	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb)	1	
Item type: Lens for camera	4	Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.)	1	
MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (APS-C) 19°2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE YES MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm		
MOUNT E-mount FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (APS-C) 19°2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE YES MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm Specification:		
FORMAT 35 mm full frame FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (APS-C) 19°2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F16 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) 65 x 73mm (2.6 x 2.9 in.) Filter Thread 52mm Specification:		
FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (APS-C) 19°2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 2.2 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM POCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (mode): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (APS-C) 19°2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE YES MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
LENS GROUPS / ELEMENTS 8-9 ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (APS-C) 19°2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
ANGLE OF VIEW (35 MM) 29° ANGLE OF VIEW (APS-C) 19°2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
ANGLE OF VIEW (APS-C) 19°2 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Item type: lens for camera		
MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
MINIMUM APERTURE (F) 22 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN		
APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN		
CIRCULAR APERTURE Yes MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
MINIMUM FOCUS DISTANCE 2.63 ft (0.8 m) MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Item type: lens for camera		
MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Item type: lens for camera		
FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Item type: lens for camera		
IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
HOOD TYPE Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
Round, bayonet type IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
IMENSIONS (DIAMETER X LENGTH) 3 1/8 x 3 1/4" (78 x 82 mm) WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
What's In The Box Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
Hood (model): ALC-SH150 Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
Lens front cap: ALC-F67S		Specification: Item type: lens for camera		
		Specification: Item type: lens for camera		
Lens rear cap. ALC-INILLIVI		Specification: Item type: lens for camera		
		Specification: Item type: lens for camera Lens type: 30mm F1.4 DC DN Mount: For E Mount Manufacturer: Sigma Max Aperture F1.4 Minimum Aperture F1.6 Diaphragm Blades 9 Number of elements 9 Number of groups 7 Special elements/coatings 1 aspherical and 1 double-sided aspherical Minimum Focus 0.30 m (11.81") Maximum Magnification 0.14x Motor Type Stepper motor Full Time Manual No Weight 265 g (0.58 lb) Dimensions (DxL) Filter Thread 55 x 73mm (2.6 x 2.9 in.) Filter Thread Specification: Item type: Lens for camera MOUNT E-mount FOCAL LENGTH (MM) 85 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 127.5 LENS GROUPS / LEMENTS 8-9 ANGLE OF VIEW (APS-C) 19°2 ANAIMUM APERTURE (F) 1.2 MINIMUM APERTURE (F) 1.2 MINIMUM APERTURE (F) 2.2 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM APERTURE (F) 2.3 MINIMUM APERTURE (F) 3.5 MINIMUM APERTURE (F) 3.5 MINIMUM APERTURE (F) 4.6 MINIMUM APERTURE (F) 5.6 MINIMUM APERTURE (F) 6.7 MAXIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 2.6 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 2.6 APERTURE BLADES 9 CIRCULAR APERTURE Yes MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 1.8 MINIMUM APERTURE (F) 2.6 APERTURE BLADES 9 CIRCULAR APERTURE YES MINIMUM APERTURE (F) 2.6 MAXIMUM MAGNIFICATION RATIO (X) 0.13 FILTER DIAMETER (MM) 67 IMAGE STABILIZATION (STEADYSHOT) - (body-integrated) TELECONVERTER COMPATIBILITY (X1.4) TELECONVERTER COMPATIBILITY (X2.0) HOOD TYPE ROUND, BAY 1.4 WEIGHT 13.1 oz (371 g) What's In The Box Hood (model): ALC-SH50 Lens front cap: ALC-F67S		

			Г
<u>6</u>	Specification:	1	
	Item type: Lens for camera		
	MOUNT E-mount		
	FORMAT APS-C		
	FOCAL LENGTH (MM) 50 mm 35 MM EQUIVALENT FOCAL LENGTH (APS-C) 75mm		
	LENS GROUPS / ELEMENTS 8/9		
	ANGLE OF VIEW (APS-C) 32°		
	MAXIMUM APERTURE (F) 1.8		
	MINIMUM APERTURE (F) 22		
	APERTURE BLADES 7 CIRCULAR APERTURE Yes		
	MINIMUM FOCUS DISTANCE 1.28 ft (0.39 m)		
	MAXIMUM MAGNIFICATION RATIO (X) 0.16x		
	FILTER DIAMETER (MM) 49 mm		
	IMAGE STABILIZATION (STEADYSHOT) Optical Steady Shot		
	DIMENSIONS (DIAMETER X LENGTH) 2-1/2 x 2-1/2" (62 x 62 mm)		
	WEIGHT 7.2 oz (202 g)		
	What's In The Box		
	Lens hood (ALC-SH116: round shape, bayonet type)		
7	Lens front cap Specification:	2	
<u>7</u>	Specification:	2	
	Item Type: Microphone		
	Active Flectronics IEET impedance converter		
	Active Electronics JFET impedance converter Capsule 0.50"		
	Address Type End		
	Frequency Range 40Hz - 20kHz (selected HPF @80)		
	Output Impedance 200Ω		
	Maximum SPL 134dBSPL Maximum Output Level 6.9mV (@ 1kHz, 1% THD into 1KΩ load)		
	Sensitivity -32.0dB re 1 Volt/Pascal (20.00mV @ 94 dB SPL) +/- 2 dB @ 1kHz		
	Equivalent Noise Level (A-weighted) 14dBA		
	Weight 85g		
	Dimensions 100mmH x 75mmW x 170mmD		
	Warranty 1 year with free Rycote® Lyre® shock mounting onboard		
	All-new capsule with lower noise and higher sensitivity		
	Broadcast recording quality condenser microphone		
	Compact form factor (150mm/6" length)		
	Ultra lightweight (85g/3oz) 9V battery powered - over 70 hours use (alkaline)		
	Integrated shock mounting		
	Integrated foam windscreen		
	3.5mm stereo mini-jack output (dual mono)		
	Two step High Pass Filter (flat, 80Hz)		
	Three position level control (-10dB, 0, +20dB) Camera shoe mount with 3/8" thread for easy boompole mounting		
	10 year extended warranty when you register your microphone		
8	Specification:	2	
-	Item type: Rig cage		
	compatibility: a6600 4K camera		
	BH #SMCCS2493		
	Formfitting Camera Cage		
	2 x Cold Shoe Mounts 1/4" 20 and 3/8" 16 Accessory Threads		
	1/4"-20 and 3/8"-16 Accessory Threads Single ARRI-Style Accessory Hole		
9	Specification:	2	
=		_	
	item type: rechargeable battery		
	compatibility: a6600 4K camera z- series rechargeable battery pack		
	Model: np - fz100		
	Dimensions (W × H × D): Approx. 38.7 x 22.7 x 51.7 mm (1 9/16 x 29/32 x 2 1/8 inches)		
	Capacity: 7.2V / 16.4Wh (2280mAh)		
40	Weight: Approx. 83 g (3.0 oz)	2	
<u>10</u>	Specification:	2	
	Item Type: SD memory card		
	64GB/ 170mb extreme pro UHS - SDXC memory card		
	64GB Storage Capacity		
	UHS-I / V30 / U3 / Class 10 Max Read Speed: 170 MB/s		
	Max Write Speed: 90 MB/s		
	Min Write Speed: 30 MB/s		
	Records Full HD, 3D, and 4K Video		
	Built-In Write-Protect Switch		

<u>11</u>	Specification:	1	
	item type: LED video light		
	Video Light: GD SL-60W White Video Light		
	AC Power Supply: AC 100-240V 50/60Hz		
	Color temperature: 5600±300K		
	Color Rendering Index: >95		
	R9: 90 ;TLCI (Qa): >90		
	100% illuminance (LUX): 4100(1m)		
	100% Luminous Flux: 4500		
	Wireless group control: 6 Groups (A, B, C, D, E, F)		
	Channel: 16; Cooling Fan: Yes		
	With Soft Box (Special Design for SL60W)		
	Heat dissipation with premium heatsink and built-in fan		
	SL-60W is suitable for outdoor photography, fluorescent lighting, children photography, as it is		
	Continuous Capacity		

Note: All the bidders are required to mention the details of their product being offered by them in the Technical proposal and also clearly mention the name & relevant major specifications of their offered product while quoting the financial bid as well. Mere reproduction of our tender documents will not serve the purpose and the bid may be liable to be rejected by the procuring agency in such cases.

INSTRUCTIONS / TERMS & CONDITIONS:

- 1. Bid should be proper sealed & stamped and addressed in the name of Treasurer, the Islamia University of Bahawalpur and reach in this office (Procurement Wing) as per schedule given in advertisement.
- 2. The Tender Opening Committee will open the bids on same date & time advertised in newspaper in the presence of bidders, who wish to attend. In case of bid submission / opening date falls on the public holiday, the submission / opening date will be next working day at same time.
- **3.** Bid received after due date / time will not be accepted under any circumstances.
- **4.** The bid should be submitted along with **2%** Earnest Money Demanded (EMD) in the form of Demand Draft or CDR (Separate for each category) in favor of the Treasurer, The Islamia University of Bahawalpur. No bid shall be acceptable without EMD.
- 5. Bid shall remain valid for 90 days which can be increased with the mutual consent of both parties from the date of opening of the financial bid.
- **6.** The vendor should ensure that no other Govt. organization is being offered / benefited more than this Price/discount. If the same is found at any stage recovery will be made accordingly.
- 7. For any Damages / Shortage during transit, bidder will be responsible & the same must be replaced within maximum 7 working days or within the time allotted by the University.
- **8.** 5% Security of the ordered value will be deducted at the time of payment and the said amount will be released upon the satisfactory report of end user.
- **9.** The supply will be checked by the Technical / Inspection Committee. However, the successful vendor / supplier will ensure / responsible to supply the goods / items according to complete specification mentioned in tender document / Supply order, otherwise the whole supply will be rejected.
- 10. In case the vendor fails to complete the job or provide substandard articles, or withdraw his offer for any reason, the EMD will be forfeited.
- 11. The material must be supplied in one lot. Part supplies will not be acceptable. However, if authorities issue instructions to provide supplies in parts, the instruction will be followed in letter & spirit.
- 12. No advance payment will be made in favor of tender awarded firm.
- 13. Item wise Lowest bid / offer will be accepted subject to the approval of the Competent Authority and the payment will be made according to policy of University / approval of competent authority.

- **14**. Stamp Duty (Stamp Papers) @ 0.25% of total amount must be attached with the bill as per rules at the time of payment.
- **15**. The supplies must be confirmed to the specification of supply order and free of defects in all respects. If the same is found defective, the same must be replaced immediately free of charge at the Islamia University of Bahawalpur.
- **16**. The Store Section on report of end user shall notify the supplier in writing / through telephone immediately of any defect that occurs during the warranty period. On receipt of such intimation / notification within the warranty period, the supplier shall attend the breakdown call within a maximum of 06 working hours.
- **17.** All the expenses for the above remedial measures including the repair / replacement if so required shall be borne by the supplier.
- **18.** Wherever a brand has been specified, equivalent will be entertained subject to technical evaluation according to PPRA Rules 2014.
- **19.** The rates should be quoted after allowing rebates / discounts, if any but including transportation, delivery at site, commissioning, packing charges, forwarding and all taxes.
- **20.** While quoting the rates of required / specified supplies, its make & model/brand should be written against each. The rates should be quoted only in Unit / Per Kg. / Per Litter / Pack/ Ream. Each according to the nature of the quotations / bids.
- **21.** The supply shall be accepted subject to the condition of final and unchallengeable approval of the Purchase / Inspection Committee of the University.
- **22.** The successful bidder /supplier will ensure/responsible to supply above items according to specifications.
- **23.** Any other term & condition specifically not mentioned in this tender document will be conveyed to the successful bidder at the time of issuance of Supply Order.
- **24.** In case of any dispute / violation of any term & condition of the tender clause, the decision of the Vice- Chancellor of IUB will be considered final, which will not be challengeable in any court of law.

ASSISTANT TREASURER (PROCUREMENT)

The bid amount will be quoted by the vendor along with this certificate:

I / We have read all the above terms & conditions Document's instructions and submit bids / rates in conformity / compliance with the given instructions.

Name of Firm:	
Name of Bidder:_	
Signature:	
Dated•	

Please attach the following:

- i) Copy of CNIC
- ii) Cop of original Tender Form Fee of HBL Challan / Demand Draft
- iii) Copy of CDR against each tender category. (Original must be attached with Financial Bid)
- iv) Copies of Income Tax, Sales Tax & Professional Tax
- v) Last six month bank statement attested by concerned bank.

Copy of current Sales Tax active / not black listed firm certificate issued by FBR



PROCUREMENT OF MISC ITEMS FOR SECURITY BRANCH TENDER-B FORM

1.	Name of Firm:		
2.	Mailing Address:		
3.	Phone No:	4. Fax No:	
5.	Tender Fee Challan No. & amount	CDR No. & Amount	
6.	General Sale Tax No:	7. Income Tax No	
8.	Professional Tax No:	 	
			Data nor

Sr.	Items	Qty	Rate per Item with all Taxes
1	Jacket	424Nos.	
	To be worn with Uniform sample available in Security Branch		
2	Rain Coat	424 Nos.	
	As per sample available in Security Branch		

Note: All the bidders are required to mention the details of their product being offered by them in the Technical proposal and also clearly mention the name & relevant major specifications of their offered product while quoting the financial bid as well. Mere reproduction of our tender documents will not serve the purpose and the bid may be liable to be rejected by the procuring agency in such cases.

INSTRUCTIONS / TERMS & CONDITIONS:

- 1. Bid should be proper sealed & stamped and addressed in the name of Treasurer, the Islamia University of Bahawalpur and reach in this office (Procurement Wing) as per schedule given in advertisement.
- 2. The Tender Opening Committee will open the bids on same date & time advertised in newspaper in the presence of bidders, who wish to attend. In case of bid submission / opening date falls on the public holiday, the submission / opening date will be next working day at same time.
- **3.** Bid received after due date / time will not be accepted under any circumstances.
- **4.** The bid should be submitted along with **2**% Earnest Money Demanded (EMD) in the form of Demand Draft or CDR (Separate for each category) in favor of the Treasurer, The Islamia University of Bahawalpur. No bid shall be acceptable without EMD.
- 5. Bid shall remain valid for 90 days which can be increased with the mutual consent of both parties from the date of opening of the financial bid.
- **6.** The vendor should ensure that no other Govt. organization is being offered / benefited more than this Price/discount. If the same is found at any stage recovery will be made accordingly.
- 7. For any Damages / Shortage during transit, bidder will be responsible & the same must be replaced within maximum 7 working days or within the time allotted by the University.
- **8.** 5% Security of the ordered value will be deducted at the time of payment and the said amount will be released upon the satisfactory report of end user.
- **9.** The supply will be checked by the Technical / Inspection Committee. However, the successful vendor / supplier will ensure / responsible to supply the goods / items according to complete specification mentioned in tender document / Supply order, otherwise the whole supply will be rejected.
- 10. In case the vendor fails to complete the job or provide substandard articles, or withdraw his offer for any reason, the EMD will be forfeited.

- 11. The material must be supplied in one lot. Part supplies will not be acceptable. However, if authorities issue instructions to provide supplies in parts, the instruction will be followed in letter & spirit.
- 12. No advance payment will be made in favor of tender awarded firm.
- 13. Item wise Lowest bid / offer will be accepted subject to the approval of the Competent Authority and the payment will be made according to policy of University / approval of competent authority.
- **14.** Stamp Duty (Stamp Papers) @ 0.25% of total amount must be attached with the bill as per rules at the time of payment.
- **15**. The supplies must be confirmed to the specification of supply order and free of defects in all respects. If the same is found defective, the same must be replaced immediately free of charge at the Islamia University of Bahawalpur.
- **16**. The Store Section on report of end user shall notify the supplier in writing / through telephone immediately of any defect that occurs during the warranty period. On receipt of such intimation / notification within the warranty period, the supplier shall attend the breakdown call within a maximum of 06 working hours.
- **17.** All the expenses for the above remedial measures including the repair / replacement if so required shall be borne by the supplier.
- **18.** Wherever a brand has been specified, equivalent will be entertained subject to technical evaluation according to PPRA Rules 2014.
- **19.** The rates should be quoted after allowing rebates / discounts, if any but including transportation, delivery at site, commissioning, packing charges, forwarding and all taxes.
- **20.** While quoting the rates of required / specified supplies, its make & model/brand should be written against each. The rates should be quoted only in Unit / Per Kg. / Per Litter / Pack/ Ream. Each according to the nature of the quotations / bids.
- **21.** The supply shall be accepted subject to the condition of final and unchallengeable approval of the Purchase / Inspection Committee of the University.
- **22.** The successful bidder /supplier will ensure/responsible to supply above items according to specifications.
- **23.** Any other term & condition specifically not mentioned in this tender document will be conveyed to the successful bidder at the time of issuance of Supply Order.
- **24.** In case of any dispute / violation of any term & condition of the tender clause, the decision of the Vice- Chancellor of IUB will be considered final, which will not be challengeable in any court of law.

ASSISTANT TREASURER (PROCUREMENT)

The bid amount will be quoted by the vendor along with this certificate:

I / We have read all the above terms & conditions Document's instructions and submit bids / rates in conformity / compliance with the given instructions.

Name of Firm:	
Name of Bidder:_	
Signature:	
Dated:	

Please attach the following:

- i) Copy of CNIC
- ii) Cop of original Tender Form Fee of HBL Challan / Demand Draft
- iii) Copy of CDR against each tender category. (Original must be attached with Financial Bid)
- iv) Copies of Income Tax, Sales Tax & Professional Tax
- v) Last six month bank statement attested by concerned bank.

Copy of current Sales Tax active / not black listed firm certificate issued by FBR



PROCUREMENT OF BINDING MATERIAL FOR MAIN LIBRARY TENDER-C FORM

1.	1. Name of Firm:	
2.	2. Mailing Address:	
	3. Phone No: 4. Fax	
5.	5. Tender Fee Challan No. & amount	CDR No. & Amount
6.	6. General Sale Tax No:	7. Income Tax No
Q	8 Professional Tay No:	

Sr.	Items	Qty	Rate per Item
#			with all Taxes
1	Maraco Leather in fine quality	350 Meter	
2	Maraco Leather dana dar	150 Meter	
3	Cloth for newspaper binding in cotan	50 Meter	
4	Kashmira Malmal Cloth white	200 Meter	
5	Drawing sheet different color	500 sheet	
6	Craft Paper fine quality	700 Sheet	
7	Binding Tape 3 inch (20 yard)	20 Dozen	
8	Binding Tape 2 inch (20 Yard)	20 Dozen	
9	Samad bond half kg packing	5kg	
10	Japani Cloth for binding	100 Meter	
11	Gillo 1 kg paching (German white 270)	60 kg	
12	Maida (Fine floor)	40 kg	
13	Neela Thota	2 kg	
14	Scoth Tape 1 inch (Deer Brand)	20 Dozen	
15	Scoth Tape 2 inch (Deer Brand)	10 Dozen	
16	Wood Stick for cutting machine	10 Nos	
17	Soap for hand washing (life Boy)	3 Dozen	
18	Thread (dhaga) 21 No. size	12 Nos	
19	Gatta (Card board) fine quality Karachi wala	700 Sheet	

Note: All the bidders are required to mention the details of their product being offered by them in the Technical proposal and also clearly mention the name & relevant major specifications of their offered product while quoting the financial bid as well. Mere reproduction of our tender documents will not serve the purpose and the bid may be liable to be rejected by the procuring agency in such cases.

INSTRUCTIONS / TERMS & CONDITIONS:

- 1. Bid should be proper sealed & stamped and addressed in the name of Treasurer, the Islamia University of Bahawalpur and reach in this office (Procurement Wing) as per schedule given in advertisement.
- 2. The Tender Opening Committee will open the bids on same date & time advertised in newspaper in the presence of bidders, who wish to attend. In case of bid submission / opening date falls on the public holiday, the submission / opening date will be next working day at same time.
- **3.** Bid received after due date / time will not be accepted under any circumstances.

- **4.** The bid should be submitted along with **2%** Earnest Money Demanded (EMD) in the form of Demand Draft or CDR (Separate for each category) in favor of the Treasurer, The Islamia University of Bahawalpur. No bid shall be acceptable without EMD.
- 5. Bid shall remain valid for 90 days which can be increased with the mutual consent of both parties from the date of opening of the financial bid.
- **6.** The vendor should ensure that no other Govt. organization is being offered / benefited more than this Price/discount. If the same is found at any stage recovery will be made accordingly.
- 7. For any Damages / Shortage during transit, bidder will be responsible & the same must be replaced within maximum 7 working days or within the time allotted by the University.
- **8. 5%** Security of the ordered value will be deducted at the time of payment and the said amount will be released upon the satisfactory report of end user.
- **9.** The supply will be checked by the Technical / Inspection Committee. However, the successful vendor / supplier will ensure / responsible to supply the goods / items according to complete specification mentioned in tender document / Supply order, otherwise the whole supply will be rejected.
- 10. In case the vendor fails to complete the job or provide substandard articles, or withdraw his offer for any reason, the EMD will be forfeited.
- 11. The material must be supplied in one lot. Part supplies will not be acceptable. However, if authorities issue instructions to provide supplies in parts, the instruction will be followed in letter & spirit.
- **12.** No advance payment will be made in favor of tender awarded firm.
- **13.** Item wise Lowest bid / offer will be accepted subject to the approval of the Competent Authority and the payment will be made according to policy of University / approval of competent authority.
- **14**. Stamp Duty (Stamp Papers) @ 0.25% of total amount must be attached with the bill as per rules at the time of payment.
- **15**. The supplies must be confirmed to the specification of supply order and free of defects in all respects. If the same is found defective, the same must be replaced immediately free of charge at the Islamia University of Bahawalpur.
- 16. The Store Section on report of end user shall notify the supplier in writing / through telephone immediately of any defect that occurs during the warranty period. On receipt of such intimation / notification within the warranty period, the supplier shall attend the breakdown call within a maximum of 06 working hours.
- **17.** All the expenses for the above remedial measures including the repair / replacement if so required shall be borne by the supplier.
- **18.** Wherever a brand has been specified, equivalent will be entertained subject to technical evaluation according to PPRA Rules 2014.
- **19.** The rates should be quoted after allowing rebates / discounts, if any but including transportation, delivery at site, commissioning, packing charges, forwarding and all taxes.
- **20.** While quoting the rates of required / specified supplies, its make & model/brand should be written against each. The rates should be quoted only in Unit / Per Kg. / Per Litter / Pack/ Ream. Each according to the nature of the quotations / bids.
- **21.** The supply shall be accepted subject to the condition of final and unchallengeable approval of the Purchase / Inspection Committee of the University.
- **22.** The successful bidder /supplier will ensure/responsible to supply above items according to specifications.

- **23.** Any other term & condition specifically not mentioned in this tender document will be conveyed to the successful bidder at the time of issuance of Supply Order.
- **24.** In case of any dispute / violation of any term & condition of the tender clause, the decision of the Vice- Chancellor of IUB will be considered final, which will not be challengeable in any court of law.

ASSISTANT TREASURER (PROCUREMENT)

The bid amount will be quoted by the vendor along with this certificate:

I / We have read all the above terms & conditions Document's instructions and I submit bids / rates in conformity / compliance with the given instructions.

Name of Firm:	
Name of Bidder:_	
Signature:	
Dated:	

Please attach the following:

- i) Copy of CNIC
- ii) Cop of original Tender Form Fee of HBL Challan / Demand Draft
- iii) Copy of CDR against each tender category. (Original must be attached with Financial Bid)
- iv) Copies of Income Tax, Sales Tax & Professional Tax
- v) Last six month bank statement attested by concerned bank.

Copy of current Sales Tax active / not black listed firm certificate issued by FBR