The Islamia University of Bahawalpur

Construction of Girls Hostel Ist Floor at Bahawalnagar Campus

Estimate Based on MRS 01 January 2020 to 30 June , 2020 BWN Estimate

A) Civil Work			
I Schedule Items	Rs.	56,520,604.79	
II Non-Schedule Items	Rs.	21,079,561.94	
,Total of Civil Work:	Rs.	77,600,166.73	
B) Electrical Work			
I Schedule Items	Rs.	3,162,156.75	
Il Non-Schedule Items	Rs.	4,935,154.20	
Total of Electrical Work	Rs.	8,097,310.95	
C) Plumbing Work			
I Schedule Items	Rs.	206,052.45	
II Non-Schedule Items	Rs.	3,364,295.92	
Total of Plumbing Work	Rs.	3,570,348.37	
Total of (A,B,C) Rs.	89,267,826.05	
Add 5 % PST		4,463,391.30	
11000 70 10 10 1	al	93,731,217.35	./

Ist Floor+2nd Floor

Coverd Area

(29813+2000)

31813.00Sft

Rate P/Sft

2,946:32

Sub Engineer,

Assistant Engineer,

Executive Engineer,

Approved

Technicaly Sanctioned Rs:

93,731,217.00

The Islamia university of Baha Construction of Girls Hostel Ist Floor at Baha

-					
_	-	м.	-	-	
-	•	71	m	м	10
E	-			ш	

	1	1	
-	Description	Ref.	Quantity
Sr.			
1	Civil Work (Shedule Item) Dismantling cement concrete reinforced, separating reinforcement from concrete, cleaning and	4/00	
	straightening the same.	4/20.	1745.66
2	Dismantling brick work in lime or cement mortar.	4/13.	4440.27 Cft
3	Dismantling 1st class tile roofing.	4/22.a	31256.00 Sft
4	Providing and laying reinforced cement concrete and screened graded and washed aggregate, in required shape and design,including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete (but excluding the cost of steel reinforcement, its fabrication and placing in position, etc.):- (a) (i) Reinforced cement concrete in roof slab, beams, extra. columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects:- B	6/6-ai- 2c	
	i) First Floor (nominal mix 1: 1½: 3) i) 2nd Floor (nominal mix 1: 1½: 3)		25042.65 Cft
	iii) First Floor (nominal mix 1: 2:4)		2599.84 Cft
	iv) 2nd Floor (nominal mix 1: 2: 4)		724.89 Cft
5	Fabrication of mild steel reinforcement for cement concrete		1389.55 Cft
	including cutting, bending, laying in position, making joints and fastenings,including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars) Deformed Bars		
	ii) 60-Grade iii) 40-Grade	6/9-c	94039.75
6	Spraying anti-termite liquid mixed with	6/9-b	6473.99 Kg
	water in the ratio of 1:40	26/42	31633.07 Sft
7	Pacca brick work in Cement, sand mortar:-		311
	Ratio 1:4 Ground Floor		
	i) First Floor iii) 2nd Floor	7/5.	22229.76
8	iii) 3rd Floor		8639.60 2718.04 Cft
0	First class brick walling laid in 1:3 cement sand mortar, reinforced with 1" (25 mm) wide 18 gauge hoop iron: 4½" (113 mm) thick walling with hoop iron, bonding 12" (300 mm) apart.	7/0.1.11	
9	3/8" thick cement plaster under soffit of	7/21.ii	31964.56 Sft
	RCC roof slabs Ratio 1:3 upto 20' height		
10	ii) First Floor	11/10-է	37340.40 Sft
10	a) 1/2" Thick Cement plaster Ratio (1:4) i) Upto 20' height b) 3/4" thick Cement plaster Ratio (1:4)	11/9-b	100985.23
	i) Upto 20' heights	11/9-b	31326.66
0	gradie _ behat		
	A'R		

No	Description	Ref.	Quantity
	c) 1/2" Thick Cement plaster Ratio (1.4) ii) Upto 20' to 30' heights		18404.58 Sft
11	Supplying and filling sand under floor; or plugging in wells.	7/30	13570.00 Cft
12	Cement concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate): Ratio 1:2:4	6/5-f	4083.60 Cft
13	'Dry rammed brick or stone ballast, 1½" to 2"(40 mm to 50 mm) gauge.	6/2.	11983.40 Cft
14	Supplying and laying polythene sheet over D.P.C. under 'floors and on roofs, etc. 500 gauge (.005" thick)	26/37-i	62512.00
15	Providing and Laying Insulation material of Extruded Polystyrene XPS in Rigid Insulation/Foam Board on roof or walls, Density32-38Kg/M, compressive strength250-400kpa, R-value 5 per inch thickness and water absorption (1% by volume, cell structure colored cell) i/c cutting and placing in position. complete in all respect. 1-1/2" thick	9/ 4 5b	Sft 31256.00
16	Single layer of tiles 9"x4½"x1½" (225x113x40 mm) laid over 4"(100 mm) earth and 1" (25 mm) mud plaster without Bhoosa, grouted with cement sand 1:3 on top of RCC roof 'slab, provided with 34 lbs. per %Sft. or 1.72 Kg/Sq.mbitumen coating sand blinded.	9/5.	31256.00
17	Khuras on roof 2'x2'x6" (600 x 600 x 150 mm)	9/15.	40.00
18	Providing and fixing mild steel chowkat of doors, windows, C.window, etc. including holdfast, making and threading holes for hinges, etc.complete: M.S. angle iron 1½"x 1½"x ¼" (40x40x6 mm) welded with M.S. flat 2"x ¼"		Each
		12/14-a	4035.00 Sft
			311
19	Providing and fixing 1½" (40mm) thick solid flush door shutter sterling or equivalent with commercial ply (5 mm thick) on both sides double pressed and deodar wood lipping 1½"x3/8" (40mm x 10mm) around shutter including chromium plated fitting, iron hinges with aluminum kick plate 22 SWG on both sides & finger plate complete in all respect.		

1	130	Description	Ref.	Quantity	
A3CTO	3	Second class tile roofing consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %5ft or 1.72 Kg/sq.m of hot bitumen coating sand blinded, provided over one layer of 12"x6"x2" (300x150x50 mm) tiles laid in 1:6 cement mortar, including 1:2 cement pointing underneath of tiles complete including curing, etc. Providing and laying topping of cement concrete 1:2.4,including surface finishing and dividing in panels:-1½"(40 mm) thick 'Supplying and laying polythene sheet over D.P.C. under 'floors and on roofs, 500 gauge (.005" thick)	9/2	873.13	
2	21	Providing and fixing terrace railing of 2" (50 mm) i/d conduit pipe 16 SWG, welded with 5/8"x5/8" (16x16 mm) square bar 2.75 ft. (838 mm) high fixed at 5"		Sft	
		(125 mm) centre to centre, in reinforced cement concrete slab with suitable arrangement, complete in all respects, as per design and drawing.			
			25/35	483.43 Rft	
2		Preparing surface and painting with emulsion paint:- new surface 3 coats	13/31	166321.09 Sft	
2		Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect: i)new surface: Up to 20' height ii) From 20' to 30' height New surface	13/32.A	23265.42 15767.52	
		Old Surface		20420.65 Sft	
24		Preparing surface and painting of doors and windows any type (including edges):- new surface 3 coats	13/5- c i+ii+ii	10996.00 Sft	
25		Providing and fixing sliding bolt to doors:-		O.K	
		i) iron sliding bolt, 12" (300 mm) long	12/18-i	62.00 No	
	li	i) iron sliding bolt, 10" (250 mm) long	12/18-	5.00	
1	, r	Civil Work (Non Shedule Item) Providing & laying 3/4" thick Marbale floor Boticina/Lasbela (Fancy) of approved quality square shape (12"x12" size) 1:2 cement sand mortar 3/4" thick for laying of marbale tiles including tubbing grinding and polishing, complete in all espects as approved design & pattern and as directed by the Engineer Incharge.			
			NS	28830.5 Sft	0
2	3 0	Providing & Fixing Marble motive in Floor pattern of approved shape & design on PCC (1:2:4) 1½" and 8/4" thick cement plaster ratio (1:3) rubbing, polishing, grinding complete in all respects as approved by the Engineer Incharge.	f NS	12.00	
L	1	Brondt's-E	1		
			A:E		

Sir.		Ref.	Quantity
No	Description	-	
3	Previding and fixing windows consisting of M.S. box section frame 3°x11½°, leaves frame 1.14"x1" box section section frame 3°x11½°, leaves frame 1.14"x1" box section section frame for glazing 1/2"x1/2" using 16 SWO sheet 'U' frame for glazing 1/2"x1/2" using 16 SWO sheet 'U' dia 3/16" (8 mm) thick coloured tinted glass panes 1/2" dia 3/16" (8 mm) thick coloured tinted glass panes 1/2" dia 3/16" (8 mm) thick coloured tinted glass panes 1/2" dia 3/16" (8 mm) thick coloured tinted glass panes 1/2" dia M.S. for fixed in channel I/c two pair of 1" dia M.S. round M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wheel for sliding of leaves M.S. box section 1/2"x1/2" of wh	NS	3062.00
	approved by the Engineer In charge.	No	Sft
	Making and errecting in position MS Grill of MS Box pipe 1/2"x1/2", 18 SWG complete in all respects and duly painted as approved by the engineer incharge.	NS	2660.54 Sft
	Making and errecting in position MS Grill Door with M.S box pipe 1.5"x1.5" main frame and M.S Box pipe 1/2"x1/2", 18 SWG for grill, complete in all respects and duly painted as approved by the		
	engineer incharge	NS	1333.48
	Providing & Fixing uPVC rubber water stopper of size 3/8"x 10" best quality for jointing of RCC slabs atc complete in all respects	NS	400.00 Rft
F	Providing, laying placing & finishing of two coats of wall putty, (ICI, Berger Brighto, Master) on finish plaster surface complete in all respects as directed and approved by the Engineer Incharge.		
		NS	166321.09 Sft
1 m gi	Providing & Laying 3/4" thick marble slab Boticina ancy), size 5'x1'x3/4" of approved quality including 22 cement sand mortar 3/4" thick for laying of parble tiles i/c chemical polishing, rubbing & rinding complete and as approved by the Engineer-Charge.		
		NS	1450.00 Sft
re	roviding & Fixing upvc door complete in all spects as approved by the Engineer Incharge.	NS	1050.00
SE cei mo	oviding & laying Granite with dry/wet/venied plication, DWV series Polished (Dark color) class 3 16"x16" size for floor of Master i/c laid in white ment & pigment and on a bed of cement sand ortor 3/4" thick Ratio 1:2 complete in all respects approved by the Engineer Incharge.		
4 0		NS	2754.96
dad and mor	viding & laying SP Series on matching color le (Glossy) Dark Color Rectified SB 12"x18" size lo/skirting of Master i/c white cement & pigment on a bed of laid in 3/4" thick cement sand for 1:2 complete in all respects as approved by Engineer Incharge.		
	a the man and the	NS	14353.60
etc o	viding & Fixing false ceiling of Gypsum 9mm including all accessories, network & hardware complete in all respects as per approved design sample and as directed by the Engineer arge.		
A	Johnst Johnst	NS	3293.00 Sft

13			
V	Description	Ref.	Quantity
15	Subsequent carriage of crushed stone aggregate total distance from Sargodha to Bahawalnagar IUB Campus at site of work average 278 KM Stone Ballast	1/1.	11983.46
14	providing and fixing 10 in(250 mm), wide curved sheet of required shape fixed on face of the construction joint with G.I. screw, 1.5 in (40 mm) long to cover construction joints vertically & horizontally with drill machine:- G.I. sheet, 20 SWG		Cfl
	Will Common out of Street, 20 5440	NS	1402.00 Rft
	Providing and fixing 3/4" thick laminated Board shutter with 3/4" x 3/4" deodar wood beading wardrobe frame 3"x1.5" M.S Box pipe 18 SWG including tower bolts on top & bottom ,hanger rod pipe stainlessteel best quality fixed with suitable accessories , hinges, 3-coat painting complete in all respects including aluminum hanger rod etc. as approved by the Engineer Incharge.	NS	5334.82
			Sft
	Electrical Work (Schodule Hours)		
1	Electrical Work (Schedule Items) Supply and erection of PVC pipe for wiring recessed in walls, including inspection boxes, pull boxes, nooks, cutting jharries, and repairing surface, etc., complete with all specials.		
_) 3/4" i/d (20 mm)	24/3-i	12500.00
_	i) 1" i/d (25 mm) v) 2" i/d (50 mm)	24/3-ii 24/3-vi	13500.00 550.00 Rft
o o	Supply and erection of single core PVC insulated opper conductor cables, in prelaid PVC pipe/M.S. onduit/G.I pipe/wooden strip batten/wooden casing n capping/G.I. wire/trenches (rate for cables only). 50/440 volts, PVC insulated:		
li	3/0.74 mm (3/0.029")	24/10-i	12668.00
	3/0.91 mm (3/0.036")	24/10-i	34248.00
iii		24/10-ii	20125.00
iv	7/0.91 mm (7/0.036")	24/10-i	10553.00
(v)	7/1.12 mm (7/0.044")	24/10-	2208.00
vi	7/1.63 mm (7/0.064")	24/12-i	6677.00 Rft
			Mic
Su (22	ectrical Work (Non-Schedule) pply & installation of LED 2'x 2' Ceiling Panel Light 40W 0V~, 6500K) i/c any accessories required at site. Complete in respect as directed and approved by the Engineer Incharge	,	400.00
(Pt	illips RC09led 40S/865 or Equivalent)	NS	128.00 No
incl	uding casing bracket, hanging arrangement complete in all pects as approved by the Engineer Incharge.	NS	24.00 No
220 resp	ply & installation of LED 17W Down Light (Surface Mounted, V~) i/c any accessories required at site. Complete in all sect as directed and approved by the Engineer Incharge lips Essential or Equivalent)	NS	300.00
(220 all re	ply & installation of Strip (patti) with 20W Led tube rod IV~, 6500K) i/c any accessories required at site. Complete in espect as directed and approved by the Engineer Incharge lips or Equivalent)	NS	350.00

		Ref	Quantity
-	T Description	-	
St	Wall Bracket Fan 24"		
No 5	Supply & Installation of Metal Body Wall Bracket Fan 24" Supply & Installation of Metal Body Wall Bracket Fan 24" (see 99% Copper) vic any accessories (i.e. widing of mounting holes and 4 00nos of rawl bolks 14" etc) as required at site. Holes and 4 00nos of rawl bolks 14" etc) as required at site. Complete in all respect as directed and approved by the complete in all respect as directed and approved by the labels are ISK mega or Equivalent).	NS	12.00
	Engineer Incharge (SK mega or Equired Fan 14" swipe		
6	at site. Complete in all respect as directed at site.	NS	30.00
7	Supply & installation of Ceiling Fan 56" (99.99% Copper) I/c any supply & installation of Ceiling Fan 56" (99.99% Copper) I/c any supply a supply of the complete in all respect as directed accessories required at site. Complete in all respect as directed accessories required in the complete in the com	NS	107.00 No
8	Supply & installation of Metal body Exhaust fan 20" (99.99% Copper) with metal mounting frame 1/c any accessories (i.e. screw. Rawl plug/rawl bolt etc.) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (Tamoor, Indus, Pakfan or Equivalent)	NS	5.00 No
9	Supply & installation of PVC Exhaust fan 12" (99.99% Copper) Vc any accessories (i.e. screw. Rawl plug or steel nail, etc.) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (GFC, Indus, Pakfan or Equivalent)	NS	10.00
10	Supply and lead to the supply and the	173	No
10	Supply and Installation of Stainless Steel/Aluminum Exhaust Hood with exhaust fan (170W) and 4 x20W halogen lamp i/c any other accessories required at site. Complete in all respects as approved by Engineer Incharge. (Canon-HD-GL9011 or Equivalent)	NS	1.00
			No
	Supply & installation of Universal 3-Pole Socket with 13A Switch with plastic back box 3"x 3" i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips ECO Series Q2 or Equivalent)		
		NS	57.00 No
	Supply & installation of a Power plug 15A with plastic back box 3" x 3" I/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge(Philips ECO Series Q2 or Equivalent)	NS	9.00 No
1	Supply & installation of a Fan Dimmer 300W with plastic back pox 3"x 3" i/c any accessories required at site. Complete in all espect as directed and approved by the Engineer		NO
ľ	ncharge(Philips ECO Series Q2 or Equivalent) Supply & installation of a Single Pole Switch Plate with plastic	NS	8.00 No
a	pack box 3"x 3" i/c any accessories required at site. Complete in a surface and approved by the Engineer ancharge(Philips ECO Series Q2 or Equivalent)	NS	4.00
5 S	supply & installation of a Double Single Pole Switch Plate with	NO	4.00 No
C	complete in all respect as directed and approved by the	7.30	
-	ngineer Incharge(Philips ECO Series Q2 or Equivalent)	NS	3.00
C	upply & installation of a Four Single Pole Switch Plate with astic back box 3"x 3" i/c any accessories required at site. omplete in all respect as directed and approved by the		No
-	inglineer incharge(Philips ECO Series Q2 or Equivalent)	NS	7.00 No
C	upply & installation of a Six Single Pole Switch Plate with astic back box 3"x 6" i/c any accessories required at site. omplete in all respect as directed and approved by the		
8 St	upply & installation of a Fight Single Pole Switch Distance.	NS	4.00 No
C	omplete in all respect as directed and approved by		
	ngineer Incharge. (Phillips ECO Series Q2 or Equivalent)	NS	5.00
-	10.		No

4	Description	But I	Fire or and a second
1	y & installation of a Four Single Pota Suitch & Two 5 July	Ref	Quantity
SSOR!	g Plate with plastic back box 5'v 8" is any accessories as at site. Complete in at respect as directed and and by the Engineer Incharge. (Philips ECI) Series (V) so	NS	8 00 No
goard cance breath and si suitable to 8 s annual color a of all r installe Françai Voltma No 8 s inchan	y, installation and commissioning of Sue Main Duare and of M.S. steel sheet 18 SWG (18" x 24") totally enclosed aled type. With main incoming & sub-main out going circulture, internal wiring for connections between main MCCB drivens MCBs. Also including earthing bar, resultal bar, is to system voltage 415 V, 50 Hz. 3 Phase Body of Main half be degressed and de rusted having one cost of a paint with further 2 Coats of powder paint of approved and shall be equisped as mentioned below, including cost excessing materials required at site. All Breakers to be ad shall be of one make only. Make Legrand (Made in b) (180 A. TP Main Incoming MCCB 01 No. 10/20 e, SP Sub-main out going MCBs 24 No's, Digital ster (2" x 2") 03 No. Neon phase indicator lights 03 (c). Complete in all respects as approved by the engineer ge (for MCCB & MCBs Hitachi, Schneider Electric, id or equivalent).		8.00
3-Digit 3-Neor Outgol	Amps TP MCCB al Voltmeter (2"x2") n phase light		
to mois copper Nos ba Vd, 1% include	sture level (up to 60' below ground level) 4" I/d including strip 14" x 2" x 1/4" (350 x 50 x 6 mm) connecting with 1 are copper wire of No.8 SWG to be run in PVC pipe 20mm ("I/d GI pipe 5' long, GI tee & plug for watering also as common salt, Lime (slaked) and charcoal around strip I/c connecting with Electric machine. Complete in all that approved and as directed by the engineer incharge.		
		NS	8.00 No
water s capacit comple	ing & Fixing main power panel board for 3-phase motor of upply magnetic controller 35 Amp TP power factor or CT temperature control censor, power button etc te in all respects as approved by the Engineer In charge.	NS	1.00 No
supply	ng & Fixing of Golden Electric Pump 3.0 H.P for Water including connection & testing with MS Steel safety box tric pump in working condition, complete in all respects, oved by the Engineer In charge.	NS	2.00 No
Providir fan hoo	ng & Fixing Fan hook popular or equitant quality with PVC k cover sheet 8" dia	N.S	114.00 No
	1		
Provid closet,	oing Work (Schedule Items) ing and fitting glazed earthen ware water squatter type (Orisa pattern), combined with st. Colored	19/3.ii	22.00
Providing hand b	ing and fitting glazed earthen ware wash lasin 56x40 cm (22"x16") including bracket laste pipe and waste coupling, etc.	19/6.ii	No. 5.00
ii) colo	red, with pedestal	19/0.11	No.
Providi ii) '1.5	ng and fixing chromium plated bib cock:- cm (½")		61.00 No.
	ADi I		15 19

Sr.	Description	Ref.	Quantity
4	Providing and fitting plastic made low down flushing cistern 13 63 liter (3 gellons) capacity, including bracket set, copper connection, etc. complete.		autoty
	ny colored	19/12.1	22.00 No.
5	Providing and fixing stainless steel sink with drain		NO.
0	board size 120x60 cm (48"x24") including bracket	19/7.	2.00
	set, waste pipe and waste coupling.	15/7.	No.
6	Providing and fixing chromium plated tee stop cock	19/24.i	77.00
	'15mm (½").	10/2	No.
7	Providing and fixing chromium plated pillar-cock,		
	heavy:- ii) '2 cm (3/4")	19/23.	4.00
	the testing walks	19/29	No.
8	Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.		27.00 No.
9	Providing, laying, cutting, jointing, testing and disinfecting High Density Polyethylene Pipe (HDPE-		
	100) working pressure pipe in trenches. complete in all respects:-PN-8 (SDR-21) 4" (110mm).	23/42 .a.ii	150.00
		.a.II	Rft
10	Providing and fitting:	19/22.	
	i) plastic soap dish		12.00
	ii) plastic toilet paper holder		12.00
	iii) plastic towel rail iv) plastic shelf (24"x5") with bracket and railing.		12.00
	with bracket and failing.	1 4	12.00 No.
1	Plumbing Work (Non Schedule)		
	Providing, laying, cutting, jointing, testing and disinfecting PPRC pipeline for hot & cold (Polypropylene random copolymer) water supply complete in all respects, i/c specials such as coupler, reducing socket, elbow, end caps, male/female, threaded, fittings, like tease, adaptors to connect polydex pipes to other pipe and shower,		
1	wash basin, bibcock etc. as required at site Master/Beta/Dadex (For internal wiring of pathrooms)		
-) 1/2" i/d (25 mm o/d)	N.S	592.82
) 3/4"i/d (32 mm o/d)	N.S	1495.00
111) 2.5" i/d (63 mm o/d)	N.S	1274.50
s a w c C	Providing, laying, fixing and testing uPVC plain end ocketed pipes Soil Waste, vent & rain water as perperoved make & quality including uPVC fittings with solvent cement jointing or rubber ring joints complete in all respects i/c clamps, tees, Y-tees, cowl reducers, clean out WC- Elbow Adopter to.complete in all respects. 4" dia pipe		Rft
		N.S	1958.18
			Rft
1	Anadors E Loshart		

M	Description	Ref	Quantity
Y	providing & Fixing Earthenware Couple set including Flush Tank fixed with Commode, gakelite Sheet Cover Flush Tank fixed with Commode, Bakelite Sheet Cover Thimble, Connection Pipe Complete in all respects as directed and approved by the Engineer Incharge. (Porta/Bosch)		
	Providing & Fiving Muslim at	N.S	5.00 No
	Providing & Fixing Muslim shower with double bib cock with one meter flexible pipe complete unit in functino and as complete in all respects as approved by the Engineer Incharge. (Sonex/Master/Faisal)		
	Providing & Fixing Bath set (GA_COMPLETE SETS	N.S	5.00 No
	(8 PCS) 1/2" (CP) Caspian Set (3083B) P complete in all respects as approved by the Engineer Incharge. (Master/Faisal/Equivalent)	NO	20.00
	Providing & Fixing looking glass 5 mm thick best quality including aluminum frame 2'x1' complete in	N.S	29.00 No
	all respects Providing & Fixing counter basin colored best	N.S	60.00 Sft
The latest and the la	as approved by the engineer in charge.	N.S	24.00 No
3	Providing & fixing floor trap Jali Stainlessteel complete in all respect and as approved by the Engineer Incharge.	N.S	40.00
9	Providing & fixing floor trap Jali plastic complete in all respect and as approved by the Engineer		No
0	Providing & Fixing super Tuff Imported quality Water Tank 1000 Gallon capacity placing on the top of roof of the Building including Treatment with Jumbolan arrangement for Heat & Cold proofing & in working condition complete in all respects and as approved by	N.S	38.00 No
	the Engineer Incharge.	N.S	4.00
11	Providing & Fixing Stop valve PPRC complete in all respects as approved by the Engineer Incharge. a) 32 mm o/d	N.S	4.00
	b) 63 mm o/d		4.00
12	Providing & Fixing UPVC P-Trap 4" best quality, connecting with pipe, wc, Tee, Elbow, socket etc. as required at site, fixing with PCC 1:2:4 as approved by the Engineer Incharge.		
		N.S	65.00 No

The Islamia University of Bahawalpur Construction of Academic Block (1st Floor Remaining portion) of IUB Sub Campus at Bahawalnagar

Estimate Based on MRS 01 January 2020 to 30 June , 2020 BWN

A) Civil Work	•	Rs.	26,902,966.50
Schedule Item	Items	Rs.	7,594,191.71
Non-Schedule Total of Civil	Nork:	Rs.	34,497,158.21
Floatrical Wol			
Schedule Iten	ns	Rs.	4,382,508.30
- 1 - 1 - 1	Items	Rs.	3,365,705.20
Non-Schedule Total of Elect	rical Work	Rs.	7,748,213.50
C) Plumbing Wo I Schedule Iter II Non-Schedul Total of Plum	ns e Items	Rs. Rs. Rs.	243,881.05 1,531,524.93 1,775,405.98
	Total of IA	,B,C) Rs.	44,020,777.69
	Total of (A	1,0,0,110.	
Add 5 % PST	Total of (A	1,5,0,110.	2,201,038.88

Coverd Area Rate P/Sft Rs 15,200.00 Sft 3,040.91

Sub Engineer,

Assistant Engineer,

Executive Engineer,

Approved

Technicaly Sanctioned Rs:

46,221,817.00

The Islamia University of Bahawal Construction of Academic Block (1st Floor Remaining portion) Bahawalnagar Estimate

Sr.	Description	Ref.	Quantity
NO. 1	Civil Work (Schedule Item) Dismantling cement concrete reinforced, separating reinforcement from concrete, cleaning and straightening the same.	4/20.	3315.34
2	Dismantling brick work in lime or cement mortar.	4/13.	2021.50
3	Dismantling 1st class tile roofing.	4/22.a	Cft 15047.19
4	Providing and laying reinforced cement concrete (including prestressed concrete), using coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete (but excluding the cost of steel reinforcement, its fabrication and placing in position, etc.):- (a) (i) Reinforced cement concrete in roof slab, beams, extra, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects:-		Sft
	B i) First Floor (nominal mix 1: 1½: 3) ii) First Floor (nominal mix 1: 2:4) iii) 2nd Floor (nominal mix 1: 2: 4)	6/6-ai-2c	12194.43 286.66 2825.00 Cft
5	Fabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars) Deformed Bars i) 60-Grade		
	ii) 40-Grade	6/9-c 6/9-b	54502.51 877.70 Kg
6	Spraying anti-termite liquid mixed with water in the ratio of 1:40	26/42	11439.30 Sft
7	Pacca brick work in Cement, sand mortar:- Ratio 1:4 Ground Floor i) First Floor iii) 2nd Floor	7/5.	14813.82 Cft
8	First class brick walling laid in 1:3 cement sand mortar, reinforced with 1" (25 mm) wide 18 gauge hoop iron:-4½" (113 mm) thick walling with hoop iron, bonding 12" (300 mm) apart.	7/21.ii	1599.84 Cft 3630.84
9	3/8" thick cement plaster under soffit of RCC roof slabs Ratio 1:3 upto 20' height ii) First Floor	14/40	Sft
10	a) 1/2" thick Cement plaster Ratio (1:4)	11/10-b	15175.81 Sft
	i) Upto 20' heights b) 3/4" Thick Cement plaster Ratio (1:4) i) Upto 20' height	11/9-b	14824.70
	ii) Upto 20' to 30' heights	11/9-b	17938.55 Sft 3665.28
			Sft

Sr. No.	Description	Ref.	Quantity
11	Supplying and filling sand under floor; or plugging in wells.	7/30	7229.44 Cft
12	Cement concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate):		7.07
	ii) Ratio 1:2:4	6/5-f	2337,02 Cft
13	'Dry rammed brick or stone ballast, 1½" to 2"(40 mm to 50 mm) gauge.	6/2.	10515.43 Cft
14	Supplying and laying polythene sheet over D.P.C. under 'floors and on roofs, etc. 500 gauge (.005" thick)	26/37-ii	30264.78 Sft
15	Providing and Laying Insulation material of Extruded Polystyrene XPS in Rigid Insulation/Foam Board on roof or walls, Density32-38Kg/M, compressive strength250-400kpa, R-value 5 per inch thickness and water absorption (1% by volume, cell structure colored cell) i/c cutting and placing in position. complete in all respect. 1-1/2" thick	9/45b	15132.39
16	Single layer of tiles 9"x4½"x1½" (225x113x40 mm) laid over 4"(100 mm) earth and 1" (25 mm) mud plaster without Bhoosa, grouted with cement sand 1:3 on top of RCC roof 'slab, provided with 34 lbs. per %Sft. or 1.72 Kg/Sq.mbitumen coating sand blinded.	9/5.	15132.39
17	Khuras on roof 2'x2'x6" (600 x 600 x 150 mm)	9/15.	6.00 Each
18	Providing and fixing mild steel chowkat of doors, windows, C.window, etc. including holdfast, making and threading holes for hinges, etc. complete: M.S. angle iron 1½"x 1½"x ½" (40x40x6 mm) welded with M.S. flat 2"x ½"	12/14-a	1037.00 Sft
19	Providing and fixing 1½" (40mm) thick solid flush door shutter sterling or equivalent with commercial ply (5 mm thick) on both sides double pressed and deodar wood lipping 1½"x3/8" (40mm x 10mm) around shutter including chromium plated fitting, iron hinges with aluminum kick plate 22 SWG on both sides & finger plate complete in all respect.	12/50.	817.00 Sft
	Second class tile roofing consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m of hot bitumen coating sand blinded, provided over one layer of 12"x6"x2" (300x150x50 mm) tiles laid in 1:6 cement mortar, including 1:2 cement pointing underneath of tiles complete including curing, etc. Providing and laying topping of cement concrete 1:2:4,including surface finishing and dividing in panels:- 1½" (40 mm) thick Supplying and laying polythene sheet over D.P.C. under 'floors and on roofs, 500 gauge (.005" thick)	9/2	635.17 Sft

new surface 3 coats Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect: i)new surface? Up to 20' height ii) From 20' to 30' height New surface Old Surface Preparing surface and painting of doors and windows any type (including edges):- new surface 3 coats Providing and fixing sliding bolt to doors:- i) iron sliding bolt, 12" (300 mm) long ii) iron sliding bolt, 10" (250 mm) long Cement concrete brick or stone ballast 1½" to 2" (40 mm to 50 mm) gauge, in foundation and plinth:- Ratio 1: 6:12 Providing and laying Tuff pavers, having 7000 PSI, crushing strength of approved manufacturer, over 2" to 3"and cushion i/o grouting with sand in joints 1/c finishing to require slope. complete in all respect. (50% Grey / 50% Colored 60 mm thick Civil Work (Non Schedule Item) Providing a laying 3/4" thick Marbale floor Boticina/Lasbela (Fancy) of approved quality, square shape (12"x12" size) 1.2 cement sand mortar 3/4" thick for laying of marbale tiles including rubbing, grinding and polishing, complete in all respects as approved design & pattern and as directed by the Engineer Incharge. Providing and fixing windows consisting of M.S. box section frame 3"x15", leaves frame 1-1/4"x1" box section frame for glazing 1/2"x1/2" using 16 SWG sheet 'U' shaped rubber 'supported with 1"x1/4" M.S. flat for fixing 3/16" (6 mm) thick coloured tinted glass panes 1/2" dia M.S bar fixed in channel i/c two pair of 1" dia M.S round wheel for sliding of leaves M.S. box section 1/2"x1/2" of 16 SWG for fixing 24 SWG wire gauze on 'outer side by means of 1"x1/4" M.S. flat and screws I/C all C.P. litting and painting 3 coats complete in all respect & as approved by the Engineer In charge. Making and errecting in position MS Grill of MS Box pipe 1/2"x1/2", 18 SWG complete in all respects and duly painted	0	Description	Ref.	Quantity
new surface 3 coats Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect: i)new surface. Up to 20' height ii) From 20' to 30' height New surface Old Surface Preparing surface and painting of doors and windows any type (including edges):- new surface 3 coats Providing and fixing sliding bolt to doors:- i) iron sliding bolt, 12" (300 mm) long ii) iron sliding bolt, 10" (250 mm) long 12/18-ii No iii) iron sliding bolt, 10" (250 mm) long 12/18-ii 70 mm) gauge, in foundation and plinth:- Ratio 1: 6:12 71 Providing and layingTuff pavers, having 7000 PSI, crushing strength of approved manufacturer, over 2" to 3'sand cushion i/c grouting with sand in joints i/c finishing to require slope. complete in all respect. (50% Grey / 50% Colored 60 mm thick 1 Civil Work (Non Schedule Item) 1 Providing & laying 3/4" thick Marbale floor Boticina/Lasbela (Fancy) of approved quality, square shape (12"x12" size) 1:2 cement sand mortar 3/4" thick for laying of marbale tiles including rubbing, grinding and polishing, complete in all respects as approved design & pattern and as directed by the Engineer Incharge. Providing and fixing windows consisting of M.S. box section frame for glazing 1/2"x1/2" using 16 SWG sheet "U" shaped rubber supported with "x1/4" "M.S. flat for fixing 3/16" (5 mm) thick coloured tinted glass panes 1/2" dia M.S bar fixed in channel i/c two pair of 1" dia M.S round wheel for sliding of leaves M.S box section 1/2"x1/2" of 16 SWG for fixing 24 SWG wire gauze on "outer side by means of 1"x1/4" M.S. flat and screws I/C all C.P. fitting and painting 3 coats complete in all respect & as approved by the Engineer In charge. 2 Making and errecting in position MS Grill of MS Box pipe 1/2"x1/2", 18 SWG complete in all respects and duly painted as approved by the engineer incharge. NS Making and errecting in position MS Grill of MS Box pipe 1/2"x1/2", 18 SWG complete in all respects and duly pai	-	pipe 16 SWG, welded with 5/8"x5/8" (16x16 mm) square bar 1.75 ft. (838 mm) high fixed at 5" (125 mm) centre to centre, in reinforced cement concrete slab with suitable intrangement, complete in all respects, as per design and	25/35	
quality on external surface of building including preparation of surface, application of primer complete in all respect: 1)new surface Up to 20' height 1) From 20' to 30' height New surface Old Surface Preparing surface and painting of doors and windows any type (including edges):- new surface 3 coats Providing and fixing sliding bolt to doors:- i) iron sliding bolt, 12" (300 mm) long 12/18-i i) iron sliding bolt, 10" (250 mm) long 12/18-i i) iron sliding bolt, 10" (250 mm) long 12/18-i 77 Providing and laying Tuff pavers, having 7000 PSI, crushing strength of approved manufacturer, over 2" to 3"sand cushion i/c grouting with sand in joints i/c finishing to require slope; complete in all respect. (50% Grey / 50% Colored 60 mm thick Civil Work (Non Schedule Item) Providing & laying 3/4" thick Marbale floor Boticina/Lasbela (Fancy) of approved quality, square shape (12"x12" size) 1:2 cement sand mortar 3/4" thick for laying of marbale tiles including rubbing, grinding and polishing, complete in all respects as approved design & pattern and as directed by the Engineer Incharge. Providing and fixing windows consisting of M.S. box section frame 3"x15", leaves frame 1-1/4"x1" box section frame for glazing 1/2"x1/2" using 16 SWG sheet "U" shaped rubber "supported with 1"x1/4" M.S. flat for fixing 3/16" (5 mm) thick coloured tinted glass panes 1/2" dia M.S. bar fixed in channel i/c two pair of 1" dia M.S. round wheel for sliding of leaves M.S. box section 1/2"x1/2" of 16 SWG for fixing 24 SWG wire gauze on "outer side by means of 1"x1/4" M.S. flat and screws I/C all C.P. fitting and painting 3 coats complete in all respect & as approved by the Engineer In charge. Making and errecting in position MS Grill of MS Box pipe 1/2"x1/2", 18 SWG complete in all respects and duly painted as approved by the engineer incharge. Making and errecting in position MS Grill of MS Box pipe 1/2"x1/2", 18 SWG complete in all respects and duly painted as approved by the engineer incharge.			13/31	58094.16 Sft
any type (including edges):- new surface 3 coats Providing and fixing sliding bolt to doors:- i) iron sliding bolt, 12" (300 mm) long ii) iron sliding bolt, 10" (250 mm) long Cement concrete brick or stone ballast 1½" to 2" (40 mm to 50 mm) gauge, in foundation and plinth:- Ratio 1: 6:12 Providing and layingTuff pavers, having 7000 PSI, crushing strength of approved manufacturer, over 2" to 3"sand cushion l/c grouting with sand in joints l/c finishing to require slope . complete in all respect. (50% Grey / 50% Colored 60 mm thick Civil Work (Non Schedule Item) Providing & laying 3/4" thick Marbale floor Boticina/Lasbela (Fancy) of approved quality, square shape (12"x12" size) 1:2 cement sand mortar 3/4" thick for laying of marbale tiles including rubbing, grinding and polishing, complete in all respects as approved design & pattern and as directed by the Engineer Incharge. Providing and fixing windows consisting of M.S. box section frame 3"x1½", leaves frame 1-1/4"x1" box section frame for glazing 1/2"x1/2" using 16 SWG sheet "U" shaped rubber "supported with 1"x1/4" M.S. flat for fixing 3/16" (5 mm) thick coloured tinted glass panes 1/2" dia M.S bar fixed in channel l/c two pair of 1" dia M.S round wheel for sliding of leaves.M.S. box section 1/2"x1/2" of 16 SWG for fixing 24 SWG wire gauze on 'outer side by means of 1"x1/4" M.S. flat and screws I/C all C.P. fitting and painting 3 coats complete in all respect & as approved by the Engineer In charge. Making and errecting in position MS Grill of MS Box pipe 1/2"x1/2", 18 SWG complete in all respects and duly painted as approved by the engineer incharge. NS 841.52 Sft Providing & Fixing uPVC rubber water stopper of size 3/8"x 10" best quality for jointing of RCC slabs etc complete in all		quality on external surface of building including preparation of surface, application of primer complete in all respect: ()new surface: Up to 20' height (ii) From 20' to 30' height New surface Old Surface		5155.28 7377.25
ii) iron sliding bolt, 12" (300 mm) long iii) iron sliding bolt, 10" (250 mm) long 12/18-ii 16/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3. 929.61 6/3.	4			
27 Providing and layingTuff pavers, having 7000 PSI, crushing strength of approved manufacturer, over 2" to 3"sand cushion i/c grouting with sand in joints i/c finishing to require slope. complete in all respect. (50% Grey / 50% Colored 60 mm thick 2817.02 Sft 28	5	i) iron sliding bolt, 12" (300 mm) long		No 10.00
strength of approved manufacturer, over 2" to 3"sand cushion I/c grouting with sand in joints I/c finishing to require slope. complete in all respect. (50% Grey / 50% Colored 60 mm thick 10/43.b 2817.02 Sft	6	50 mm) gauge, in foundation and plinth:- Ratio 1: 6:12	6/3.	
Providing & laying 3/4" thick Marbale floor Boticina/Lasbela (Fancy) of approved quality ,square shape (12"x12" size) 1:2 cement sand mortar 3/4" thick for laying of marbale tiles including rubbing ,grinding and polishing, complete in all respects as approved design & pattern and as directed by the Engineer Incharge. Providing and fixing windows consisting of M.S. box section frame 3"x1½", leaves frame 1-1/4"x1" box section frame for glazing 1/2"x1/2" using 16 SWG sheet 'U' shaped rubber 'supported with 1"x1/4" M.S. flat for fixing 3/16" (5 mm) thick coloured tinted glass panes 1/2" dia M.S bar fixed in channel i/c two pair of 1" dia M.S round wheel for sliding of leaves.M.S. box section 1/2"x1/2" of 16 SWG for fixing 24 SWG wire gauze on 'outer side by means of 1"x1/4" M.S. flat and screws I/C all C.P. fitting and painting 3 coats complete in all respect & as approved by the Engineer In charge. Making and errecting in position MS Grill of MS Box pipe 1/2"x1/2", 18 SWG complete in all respects and duly painted as approved by the engineer incharge. NS 841.52 Sft Providing & Fixing uPVC rubber water stopper of size 3/8"x 10" best quality for jointing of RCC slabs etc complete in all	27	strength of approved manufacturer, over 2" to 3"sand cushion i/c grouting with sand in joints i/c finishing to require slope. complete in all respect. (50% Grey / 50% Colored 60	10/43.b	2817.02 Sft
charge. NS 968.50 Making and errecting in position MS Grill of MS Box pipe 1/2"x1/2", 18 SWG complete in all respects and duly painted as approved by the engineer incharge. NS 841.52 Sft Providing & Fixing uPVC rubber water stopper of size 3/8"x 10" best quality for jointing of RCC slabs etc complete in all	1	Providing & laying 3/4" thick Marbale floor Boticina/Lasbela (Fancy) of approved quality ,square shape (12"x12" size) 1:2 cement sand mortar 3/4" thick for laying of marbale tiles including rubbing ,grinding and polishing, complete in all respects as approved design & pattern and as directed by the Engineer Incharge. 'Providing and fixing windows consisting of M.S. box section frame 3"x1½", leaves frame 1-1/4"x1" box section frame for glazing 1/2"x1/2" using 16 SWG sheet 'U' shaped rubber 'supported with 1"x1/4" M.S. flat for fixing 3/16" (5 mm) thick coloured tinted glass panes 1/2" dia M.S bar fixed in channel i/c two pair of 1" dia M.S round wheel for sliding of leaves.M.S. box section 1/2"x1/2" of 16 SWG for fixing 24 SWG wire gauze on 'outer side by means of 1"x1/4" M.S. flat and screws I/C all C.P. fitting and painting 3 coats	NS	13818.74
1/2"x1/2", 18 SWG complete in all respects and duly painted as approved by the engineer incharge. NS 841.52 Sft Providing & Fixing uPVC rubber water stopper of size 3/8"x 10" best quality for jointing of RCC slabs etc complete in all			NS	968.50
Providing & Fixing uPVC rubber water stopper of size 3/8"x 10" best quality for jointing of RCC slabs etc complete in all	2	1/2"x1/2", 18 SWG complete in all respects and duly painted	NS	841.52 Sft
P/Rft		10" best quality for jointing of RCC slabs etc complete in all	NS	

	S			
Si	No	Providing Inc.	Ref.	Quantity
N		(ICI, Buerger Brighto, Master) on finish plaster surface Complete in all respects as directed and approved by the	NS	58094.16 Sft
1:	5	Providing & Fixing Marble motive in floor pattern of approved shape & design on PCC (1:2:4) 1½" and 3/4" thick cement plaster ratio (1:3) rubbing, polishing, grinding complete in all respects as approved by the Engineer Incharge.	NS	4.00 No
1	6	Providing & Laying 3/4" thick marble slab Boticina (fancy), size 5'x1'x3/4" of approved quality including 1:2 cement sand mortar 3/4" thick for laying of marble tiles i/c chemical polishing, rubbing & grinding complete and as approved by the Engineer; in-Charge.	NS	450.00 Sft
1	7	Providing & laying Granite with dry/wet/venied application, DWV series Polished (Dark color) class SB 16"x16" size for floor of Master i/c laid in white cement & Providing & Lavine Station 1:2 complete in all respects as approved by the Providing & Lavine Station 1:2 to the station of the s	NS	523.56
		Providing & laying SP Series on matching color base (Glossy) Dark Color Rectified SB 12"x18" size dado/skirting of Master i/c white cement & pigment and on a bed of laid in 3/4" thick cement sand mortor 1:2 complete in all respects as approved by the Engineer Incharge	NS	4330.45
	9	Providing & Fixing uPVC door 1.25" thick wooden color i/c hinges, door handle with locking arrangement complete in all respects.	NS	250.00
		Providing & Fixing false ceiling of Gypsum 9mm thick including all accessories, network & hardware etc complete in all respects as per approved design and sample and as directed by the Engineer Incharge.	NS	2150.00 Sft
		Subsequent carriage of crushed stone aggregate total distance from Sargodha to Bahawalnagar IUB Campus at site of work average 278 KM Stone Ballast	NS	11445.04 Cft
	V	Providing and fixing 10 in(250 mm). wide curved sheet of equired shape fixed on face of the construction joint with G.I.screw,1.5 in (40 mm) long to cover construction joints ertically & horizontally with drill machine:- G.I. sheet, 20 WG	NS	450.00
Y	1 S	lectrical Work (Schedule Items) upply and erection of PVC pipe for wiring cessed in walls, including inspection boxes, pull oxes, hooks, cutting jharries, and repairing rface, etc., complete with all specials.		
4		3/4" i/d (20 mm)	24/3-i	7500.00
	ii)	1" i/d (25 mm)	24/3-ii	Rft 12625.00 Rft
		1.5" i/d (40 mm)	24/3-v	14589.00 Rft
2		2" i/d (50 mm)	24/3-vi	350.00 Rft
	cond	ply and erection of single core PVC insulated per conductor cables, in prelaid PVC pipe/M.S. duit/G.I pipe/wooden strip batten/wooden ng an capping/G.I. wire/trenches (rate for es only). 250/440 volts, PVC insulated:		11.0
		Brooks & E		_ bsh

			1 3
			# 2
		100	B
	P	18	
10	No.	120	NN
		104	E N
	Description	NON 2	RM.
100	3/0.91 mm (3/0.036°)	411	SELIN
1	ii) 7/0.74 mm (7/0.029")	24/10-4	W.
	(ii) 7/0.91 mm (7/0.036")		1
	(v) 7/1.12 mm (7/0.044")		
3	Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 660/1100 volts PVC sheathed copper conductor, 660/1100 volts	24/12-iii	1950.00 Rft
	pipe/G.I. wire/trenches, etc (rate for cable only)		2850.00
	1) 19/1.63 mm (19/0.064")	24/12-1	Rft
4	ii) 7/1.63 mm (7/0.064")		
4	Supply and erection of copper conductor cables for service connection, in prelaid pipe/G.I.		3150.00
	wire/trenches, etc. (rate for cable only):- PVC insulated, PVC sheathed 4 core, 660/1100 volt	24/13-cvi	Rft
	non armored cable:- 7/1.63 mm (7/0.064")		20.00
5	Supply and erection of 3 pin switch and plug combined, recessed type. 10/15 Amp.	24/36-ii	No
6	Supply and erection of ceiling rose, bakelite.	24/30	36.00 No
	Electrical Work (Non-Schedule)		
1	Supply & installation of LED 2'x 2' Ceiling Panel Light 40W (220V~, 6500K) i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips RC09led 40S/865 or Engineer)	NS	32.00 No
2	Supply & installation LED flood light 100 watt Philips quality including casing bracket, hanging arrangement complete in all respects as approved		
1	by the Engineer Incharge.	NS	32.00 No
3	Supply & installation of LED 17W Down Light (Surface Mounted, 220V-) i/c any accessories required at site. Complete in all respect as directed and accrowed by the Engineer Incharge (Philips Essential or Equivalent)	NS	150.00 No
4	Supply & installation of LED Ceiling Light 17W (recessed type, 220V-) l/c cutting holes to install in false (any type) i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philins Essential or Equivalent)	NS	24.00
5	Supply & installation of Strip (patti) with 20W Led tube rod (220V~, 6500K) i/c any accessories required at site. Complete in all respect as directed and		No
	approved by the Engineer Incharge (Philips or Equivalent)	NS	150.00 No
6	Supply & installation of Metal Body Wall Bracket Fan 24" (99.99% Copper) i/c any accessories (i.e. widing of mounting holes and 4.00nos of rawl bolts %" etc) as required at site. Complete in all respect as directed and annoved by the Engineer Incharge (SK mega or Equivalent)	NS	12.00
7	Supply & installation of 2' x 2' False Ceiling Fan 14" swipe (99.99% Copper), remote controlled (c any accessories required at site. Complete		No
	in all respect as directed and approved by the Engineer Incharge (Royal, Super-asia or Fourivalent)	NS	16.00
8	Supply & installation of Ceiling Fan 56" (99.99% Copper) i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Younis-Deluxe, Tamoor-Deluxe, Pakfan-Deluxe or Engineer)	NS	No No
	AND	140	90.00 No
9	Supply & installation of Metal body Exhaust fan 20" (99.99% Copper) with metal mounting frame i/c any accessories (i.e. screw. Rawl plug/rawl bolt etc.) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (Tamoor Indias Pakfan or Engivalent)	NS	6.00 No
	Anarthis-E	oshert A'E	

10	Supply & Installation of Proceedings of the Control		0
	Description Supply & installation of PyC Exhaust fan 12' (99 99% Copper) Vc any roph India Pakfan re Emiliation Supply & installation of PyC Exhaust fan 12' (99 99% Copper) Vc any roph India Pakfan re Emiliation Supply & installation	Ref.	Quantity
	Complete in an Aspect as directed and approved by the Engineer Incharge Supply & installation of Universal as		
11	Manager 1		
	Petronic - Continues of the	NS	3.00
	respect as directed and approved by the Engineer Incharge (Philips ECO any accessories required at site. Complete in all Supply & installation of a Power et		No
	Of he Emilyaland approved by the Emilyaland and Switch with		The same of the same of
12	Street a	NS	3.00
	any accessories required power plug to	No	No .
	any accessories required at site. Complete in all respect as directed and Supply & installation of a Factor of the Engineer Incharge(Philips ECO Series O2 or Equivalent).		- B - 1
13	Supply & Instance Character and Incharacter	NS	32.00
	approved by the Engineer Incharge(Philips ECO Series OZ or Equivalent) Vo any accessories required at site. Complete in all respect as directed and Supply & installation of a Fan Dirmmer 300W with plastic back box 3"x 3" or any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge(Philips ECO).	No	No
	approved by the Engineer Is. Complete in plastic back box 3"x 3"		1
4	Vc any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge(Philips ECO Series Q2 or Equivalent) Supply a installation of a Fan Dimmer 300W with plastic back box 3"x 3" Supply a installation of a Fan Dimmer 300W with plastic back box 3"x 3" Supply a installation of a Fan Dimmer 300W with plastic back box 3"x 3" Supply a installation of a Fan Dimmer 300W with plastic back box 3"x 3" Supply a installation of a Fan Dimmer 300W with plastic back box 3"x 3" Supply a installation of a Fan Dimmer 300W with plastic back box 3"x 3" Supply a installation of a Fan Dimmer 300W with plastic back box 3"x 3" Supply a installation of a Fan Dimmer 300W with plastic back box 3"x 3" Supply a installation of a Fan Dimmer 300W with plastic back box 3"x 3" Supply a installation of a Fan Dimmer 300W with plastic back box 3"x 3" Supply a installation of a Fan Dimmer 300W with plastic back box 3"x 3"		
4	approved by the Engineer Incharge(Phillips ECO Series QZ or Equivalent) Supply & installation of a Single Pole Switch Plate with plastic back box 3"x 3" Vo any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge(Phillips ECO Series QZ or Equivalent) Supply & installation of a Single Pole Switch Plate with plastic back box 3"x and approved by the Engineer Incharge(Phillips ECO)	NS	90.00
	3" Vc any accessories required at site. Complete in all respect as directed provided by the Engineer Incharge(Philips ECO Series Q2 or		No
	and approved by the Engineer Incharge(Phillips ECO Series Q2 or Supply & Installation		
		NS	10.00
	directed and accessories of a Double Single Pole Switch Plate with		No
	Supply & installation of a Double Single Pole Switch Plate with plastic back box 3"x 3" I/c any accessories required at site. Complete in all respect as Foliable (Phillips ECO Series Q2 or		100000
	Incharge(Philips ECO Series Q2 or	NO	10.00
6	9	NS	10.00
"	box 3" 2"		No
0	Supply & installation of a Four Single Pole Switch Plate with plastic back directed and approved by the Engineer Incharge(Philips ECO Series O2 or		
1	directed and approved by the Engineer Incharge(Philips ECO Series Q2 or		
		NS	10.00
			No
0	3"x 6" i/c any accessories required at site. Complete in all respect as or Folivalent)		1
1	or Fourivalent)		100000
	V mips LCO Series Q2	NS	10.00
U	Supply & install		No
C	box 3"x 6" i/c any accessories required at site. Complete in all respect as or Followell the Engineer Incharge. (Philips ECO Series O2)		
1	directed and approved by the Engineer Incharge. (Philips ECO Series Q2		1 - 2 - 3
	t timpo 200 Series Q2	NS	10.00
9 5	Supply & installation of a Four Single Pole Switch & Two 2-Pin Socket Complete in all respect to 3"x 6" i/c any accessories required at aits		No
,	Plate with plastic back box 3"x 6" i/c any accessories required at site.	1000	
li	Complete in all respect as directed and approved by the Engineer Oncharge (Philips FCO Series O2 or Equivalent)		
	Saries O2 or Fauivalent)	NS	10.00
, S	Supply, installation and commissioning of Sub Main Distribution Board of Dain incoming 8 cub. (18" x 24"), totally enclosed concealed the Main incoming 8 cub.		No
n	1.S. steel sheet 16 SWG (18" x 24"), totally enclosed concealed type, With onnections between the steel sheet 16 swg (18" x 24"), totally enclosed concealed type, With onnections between the steel s	1000	
c	nain incoming & sub main out going circuit breakers, internal wiring for arthing bar, payth main MCCB and sub main MCRs. Also included the carried to the control of the carried to the ca		
		1000	3000
			A COLUMN
	out of difficient with a subsequent of the first having and		1000
	cossally materials read		
	one make only Make I		1000
	Continue Michigan Agree		1000
	05, Digital Voltmeter (2)1 and of Sub Itialii out going MCRe 24	1000	
In	o's,etc). Complete in all respects as approved by the engineer charge.(for MCCB & MCBs Hitach). Sobreids.		1. 6. 11. 15. 1
ec	charge.(for MCCB & MCBs Hitachi, Schneider Electric, Legrand or	- 151	
(a)	DB	11.10	
In	coming !		
1-	125 Amps TP MCCB	12,71	
3-	Digital Voltmeter (2"x2") Neon phase light		
1	itacina	N.C	500
		N.S	5.00
Pr	oviding and Laying earthing for Electric Machines I/c boring up to		1 12 11/11
			THE THE
		G L	1 37 3 1
	No.8 SWG to be run in PVC pipe 20mm i/d, 1½" i/d GI pipe 5' long, GI e & plug for watering also includes common salt, Lime (slaked) and	11.00	
ch	arcoal around copper strip I/c connecting with Electric machine	100	THE REAL PROPERTY.
Co	implete in all respects as approved and as directed by the engineer		
	the engineer	NS	3.00
:			
:			A CONTRACTOR
:			1 15/19

0	Description	Ref.	Quantity	F
6,178.2	Plumbing Work (Non Schedule) Providing, laying, cutting, jointing, testing and disinfecting PPRC pipeline for hot & cold water supply complete in all respects, I/c specials such as coupler, reducing socket, elbow, endcaps, male/female, threaded, fittings, like teese,			
	adaptors to concrete polydex pipes to other pipe and shower, wash basin, bibcock etc. as required at site (For internal wiring of bathrooms) i) 1/2" i/d (25 mm o/d)	N.S	175.00	
	ii) 3/4"i/d (32 mm o/d)	N.S	Rft 475.00	
	ii) 2.5" i/d (63 mm o/d)	N.S	1274.50 Rft	
2	Providing, laying, fixing and testing uPVC plain ends socketed pipes Soil Waste, vent & rain water as per approved make & quality including uPVC fittings with solvent cement jointing or rubber ring joints complete in all respects i/c clamps, tees, Y-tees, Cowl reducers, clean out WC- Elbow Adopter etc.complete in all respects. 4" dia pipe	N.S	650.00 Rft	
3	Providing & Fixing Earthenware Couple set including Flush Tank fixed with Commode, Bakelite Sheet Cover Thimble, Connection Pipe Complete in all respects as directed and approved by the Engineer Incharge. (Porta/Bosch)	N.S	4.00 No	
4	Providing & Fixing Muslim shower with double bib cock with one meter flexible pipe complete unit in function and as directed by the Engineer Incharge. (Master/Faisal)	N.S	4.00 No	
5	Providing & Fixing looking glass 5 mm thick best quality including aluminum frame 2'x1' complete in all respects	N.S	60.00 Sft	
6	Providing & fixing floor trap Jali Stainlessteel complete in all respect and as approved by the Engineer Incharge.	N.S	31.00 No	
7	Providing & Fixing super Tuff Imported quality Water Tank 1000 Gallon capacity placing on the top of roof of the Building including Treatment with Jumbolan arrangement for Heat & Cold proofing & in working condition complete in all respects and as approved by the Engineer Incharge.	N.S	4.00	
8	Providing & Fixing Stop valve PPRC 50mm complete in all respects as approved by the Engineer Incharge. a) 32 mm o/d b) 63 mm o/d	N.S	4.00	
9	Providing & Fixing Floor trap jali plastic colored complete in all respects	N.S	4.00 10.00 No	
10	Providing & Fixing UPVC P-Trap 4" best quality, connecting with pipe, wc, Tee, Elbow, socket etc. as required at site, fixing with PCC 1:2:4 as approved by the Engineer Incharge.			
	r Charge Linguiser incharge.	N.S	44.00	

Authi SE

Si	Description	Ref.	Quantity
No 22	a make some panel heard for	NS	1.00 No
23	Providing & Fixing of Golden Electric Pump 3.0 H.P for Water supply including connection & testing with MS Steel safety box for electric pump in working condition, complete in all respects, as approved by the Engineer Incharge.	NS	2.00
24	Providing & Fixing Fan hook popular or equilant quality with PVC fan hook cover sheet 8" dia		No 90.00
			No
1	Providing and Fitting		
_	Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Colored	19/3.ii	10.00
	Providing and fitting glazed earthen ware wash hand basin 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc. ii) colored, with pedestal	19/3.11	No.
3	Providing and fixing chromium plated bib cock:- ii) '1.5 cm (½")	19/6.ii	14.00 No.
4	Providing and fitting plastic made low down flushing cistern		13.00 No.
	ii) colored	19/12.ii	10.00
5	Providing and fixing stainless steel sink with drain board, size 120x60 cm (48"x24") including bracket set, waste pipe and waste coupling.		No.
_	Providing and fixing chromium plated tee stop cock '15mm (½").	19/7.	1.00 No.
7	Providing and fixing glazed earthen ware flat back urinal.	19/24.ii	36.00 No.
8	Providing and fixing chromium plated pillar-cock, heavy:-	19/10.	6.00 No.
9	Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.	19/23.i	14.00 No.
10	Providing, laying, cutting, jointing, testing and disinfecting High Density Polyethylene Pipe (HDPE-100) working	19/29.	1.00 No.
		23/42.a.i i	650.00
	Providing and fixing, chromium plated toilet paper holder. Providing and fitting:	19/17.	Rft 4.00
l) plastic soap dish i) plastic toilet paper holder ii) plastic towel rail	19/22.	4.00
	v) plastic towel rail v) plastic shelf (24"x5") with bracket and railing.		4.00 4.00 4.00 4.00
	Anastlis-E		No.

The Islamia University of Wahawalpur

Upgradation of Jamia Masjid & External Walk Way at Baghdad-ul-Jadeed Campus Estimate Based on MRS Jan to Jun, 2020

A)	Extension of Building	F COST	020
a)	Schedule Items		
1)	Civil Work		
ii)	Electrical Work	Rs.	5,304,733.00
	Total of "a"	Rs.	1 912 242 00
	. ottar or a	Rs.	1,913,313.00
b)	Non-School		7,218,046.00
i)	Non-Schedule Items Civil Work		
ii)	Plumbing Work	Rs.	10,074,410.00
iii)	Electrical Work	Rs.	1,385,542.00
	Total of "b"	Rs.	6,919,077.00
	, D	Rs.	18,379,029.00
	Total A (a + b)		5,070,023.00
	(4 . 5)	Rs.	25,597,075.00
B)	External Development		
i)	Civil Work		
ii)	Civil Work (Non-Schedule)	Rs.	4,554,181.00
iii)	Liectrical Work	Rs.	2,593,520.00
iv)	Electrical Work (Non-Schedule)	Rs.	191,433.00
	(Non-Schedule)	Rs.	4,273,697.00
	Total B	The state of the s	,
		Rs.	11,612,831.00
	Total (A + B)	Wallette,	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
	,	Rs.	37,209,906.00
	Add 05% Punjab Sales Tax		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
		Rs.	1,860,495.00
	Grand Total	-	7.00
		Rs.	39,070,401.00
			, 1.00

Sub-Engineer

Assistant Engineer

Executive Engineer

Technically Sanctioned for Rs.39,070,401.00

The Islamia University of Bahawa Upgradation of Jamia Masjid & External Walk Way at Baghda

	Emil	Civil Work		
	Ref#	Description	Quantit	/
1	3/21-4	Excavation in foundation of building, bridges and other structures including deg-belling, dressing, refilling around structure with excavated earth, watering and ramming lift upto 5 ft in ordinary soil	15000.00	Cft
-	6/3-b	Cement concrete brick or stone ballast 1½ " to 2" (40 mm to 50 mm) gauge, in foundation & plinth: i) Ratio 1:4:8 ii) Ratio 1:6:12	1200.00 3600.00	Cft Cft
3	7/4	Pacca brick work in foundation & plinth with cement sand mortor (1:6)	3540.00	Cft
4	3/15	Filling, watering and ramming earth under floors:- i) with surplus earth from foundation, etc. ii) with new earth excavated from outside	13000.00	Cft
		lead upto 1/4 mile	12665.00	Cft
5	7/5	Pacca Brick work in Ground Floor with cement sand mortor i) Ratio 1:5 ii) Ratio 1:3	2200.00 1200.00	Cft Cft
6	6/9	Fabrication of mild steel reinforcement for cement concrete, i/c cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars) 40-Grade	1500.00	Kg
7	6/6	Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid position, or prestressed members cast in situ, complete in all respects Type B (nominal mix 1:1.5:3) Type C (nominal mix 1:2:4)	1200.00 1500.00	Cft Cft
8	11/10	Cement plaster 3/8" (10 mm) thick under soffit of R.C.C. roof slabs only, upto 20' height. 1:3	6000.00	Sft
9	11/9b	Cement plaster upto 20' (6.00 mm) height:- ½" (13 mm) thick i) Ratio 1:4	12000.00	Sft
10	7/30	Supplying and filling sand under floor; or plugging in wells.	1500.00	Cft
11		Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels Size 1½" x 3/8"	1800.00	Rft
12		Painting door and window any type on new surface 3 coats	3800.00	Sft
13	10/15	Providing and laying topping of cement concrete 1:2:4, including surface finishing and dividing in panels 2" (50 mm) thick	2000.00	Sft
14	6/5f f	Cement concrete plain including placing, compacting, inishing and curing complete (including screening and washing of stone aggregate): Ratio 1:2:4	450.00	Cft

	Ael n	Description	- Ourselle	-
	6/2	Dry rammed brick or stone ballast, 11/2" to 2"(40 mm to 50 mm) gauge	Quantity	<u>y</u>
1			2000.00	C
B	13/31	Preparing surface and painting with emulsion paint - 2 coats	22000.00	60
17	13/32	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect, old Surface	17000 00	
18	4/49	Scraping Ordinary distemper, oil bound distemper, or paint of wall.	12000.00	00
19	25/10	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, 'tanks, etc., including cutting, drilling, revitting, handling, assembling and fixing, including erection in position	2000.00	5
20	25/53	Providing and fitting all types of glazed aluminium windows of anodised bronze colour partly fixed and partly sliding using delux sections of M/s Al-Cop or Pakistan 'Cables having frame size of 100 x 20 mm (4"x¾") and 'leaf frame sections of 50 x 20 mm (2"x¾"), all of 1.6mm 'thickness including 5 mm thick imported tinted glass with rubber gasket using approved standard latches, hardware etc., as approved by the Engineer in	750.00	K
21	10/38	charge. 1.6mm thick Coloured glazed tile dado ¼" (6mm) thick in pigment over 1:2 cement, sand mortar 3/4"(20mm) thick, including finishing.	180.00	S
1	N.S	Civil Work (Non-Schedule) Providing and fixing Door Lock (RW-46 MSN Royalwand) including all hardware fitting best quality complete in all respect as approved by Engineer	10.00	N
2	N.S	Providing & Fixing false ceiling of Gypsuim 9mm thick including all accessories, network & hardware etc complete in all respects as per approved design and sample and as directed by the engineer incharge.	4500.00	
3		Providing and laying Marble Slab (Suni white) 1" thick (2'x4' size) including 05% Wastage laid in cement with pigment on a bed of 3/4" thick cement sand mortar 1:2 including grinding & chemical polishing complete in all respects as approved by Engineer incharge		
4		Providing and fixing all types of Double glazed aluminium windows of anodized bronze colour partly fixed and partly sliding using deluxe section of M/s AL-Cop or 101mm x 41mmx 2mm using frame (70501) at bottom, (70502) at top and side Pakistan cables/Al-Cop having frame of size 31mmx60mmx2mm (70506) at top & bottom and size 35mm x60mmx2mm (70505) at center and size 35mm x 60mm x2mm (70503) at sides, Jali leaf frame 70509 size 45mm x 14mm x1.6mm i/c fine quality aluminum jali, fixing double glass 5mm thick brown tinted tempered + 12mm thick air space + 5mm thick	11000.00	3

	ETH	Description	6		
1	1	approved standard latches, wheel, stopper, brush chennel angle joint and hardware etc complete in all respect as approved by the engineer incharge	Quantity 1000.00	Sft	Ra 23
8	NS	Providing & laying 3/8" thick marble dado/skirting (Suni white) of approved quality including 1:2 cement sand mortar 3/4" thick for laying of marble tiles i/c rubbing grinding and wax polishing,complete in all respects as per drawings and specifications	450.00	Sft	2
6	N.S	Providing & Fixing 3/8" Thick Marble Patti (2" to 4" wide) with floating coat of cement over a bed of 3/4" thick cement sand mortor 1:2 over 1.5" thick PCC 1:2:4 Gray cement, including colour pigment to match with the colour of marble tiles laid with cement sand mortor 1:2 rubbing and chemical Polishing, as approved by Engineering Incharge	2000.00	Sft	
7	N.S	Providing and fixing MS sheet door frame size 10x13, 6" wide & 1.5" thick of 14 SWG for main frame and 6" wide & 1.5" thick of 16 SWG for arch portion. MS flat size 2"x1/4" for bottom and MS flat 1.50"x1/8" for face work of arch fixed with MS sheet of 16 SWG and pipe of 1/2"x1/2" for fixing of glazed panes using with MS flat 1/2"x1/8" for support and fixing of MS sheet complete inlcuding holdfast, hinges, screws, handle. sliding bolts, painting 3 coats, glass panes 4mm, locking arrangements and all accessories required at site complete in all respects as directed and approved by the Engineer Incharge	390.00	Sft	
1	N.S	Plumbing Work (Non-Schedule) Providing, laying, fixing and testing uPVC Soil Waste, vent & rain water down pipe "NIKASI PIPES Durafit/Beta/ Pak Arab/Equalvent" including uPVC fittings with solvent cement jointing or rubber ring joints complete in all respects including clamps, bends tees, Y-tees, Cowl reducers, clean out WC- Elbow Adopter etc. Complete in all respects and as approved by Engineer Incharge			
		i) 4" dia ii) 6" dia iii) 8" dia	200.00 350.00 600.00	Rft Rft Rft	
2	N.S	Providing and laying, cutting, jointing, testing and disinfecting PPRC pipe line(M.S Minhas pvt Ltd) for hot & cold water supply complete in all respects, i/c specials such as coupler, reducing socket, elbow, endcaps, male/female,threaded, fittings, like teese, adoptors to conect polydex pipes to other pipe and shower, wash basin, bibcock etc, Complete in all respect as per specifications and drawings and as approved by the Engineer Incharge.			
		i) PPRC pipe 32 mm dia ii) PPRC pipe 40 mm dia	450.00 700.00	Rft Rft	
		iii) PPRC pipe 63 mm dia iv) PPRC pipe 110 mm dia	350.00 200.00	Rft Rft	1
3	N.S	Providing & Fixing Gate valve of PPRC best quality complete in all respect as per specifications and drawings and as approved by the Engineer Incharge			
		i) PPRC Gate Valve 32 mm	6.00	No	1

	1	II Description	Quantity	I
	1	ii) PPRC Gate Valve 40 mm iii) PPRC Gate Valve 63 mm	4.00	No
	1	III) PPRE Gate valve 65 mm	4.00	No
	AN	S Providing & Fixing uPVC "P" trap 4" dia complete in all respect as approved by the Engineer Incharge.	10.00	No
1	5 N	Providing & Fixing PVC Bib Cock I/c CP niple of suitable size best quality complete in all respect as per specifications and drawings and as approved by the Engineer Incharge	100.00	No
	6 N.	Providing & Fitting Steel floor jali best quality complete in all respect as per specifications and drawings and as approved by the Engineer Incharge.	10.00	No
1				
	1 24/1	Electrical Work Supply and erection of single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches (rate for cables only). 250/440 volts, PVC insulated:		
		i) 3/0.74 mm (3/0.029")	4000.00	Rft
	100	ii) 7/0.74 mm (7/0.029")	3500.00	Rft
		iii) 7/1.12 mm (7/0.044")	2000.00	Rft
1		iv) 7/1.63 mm (7/0.064")	1200.00	Rft
2	2 24/1 b)	Supply and erection of copper conductor cables for service connection, in prelaid pipe/G.I. wire/trenches, etc. (rate for cable only):- i) PVC insulated, PVC sheathed 3 core, 660/1100 volt cable:- 7/1.12 mm (7/0.044")	7000.00	Rft
	c)	ii) PVC insulated, PVC sheathed 4 core, 660/1100 volt non armoured cable:- 7/1.12 mm (7/0.044")	1250.00	Rft
	d)	iii) PVC insulated, PVC sheathed 4 core 660/1100 volt grade cable, armoured with G.I. wire 16 SWG. a) 19/1.63 mm (19/0.064") b) 19/2.11 mm (19/0.083")	300.00 180.00	
3	24/4	Supply and erection of PVC pipe for wiring on surface including clamps inspection boxes, pull boxes, bends, tees, repairing surface, etc., complete with all specials:-		
		i) 25 mm i/d ii) 50 mm i/d	4000.00 1000.00	
4	24/7	Supply and erection of PVC pipe for surface wiring (main and sub-main) including clamps, inspection boxes, pull boxes bends etc., complete with all specials:-		
		i) 80 mm i/d ii) 100 mm i/d	400.00 100.00	

	Ref#	Description	Quantity
1	NS	Electrical Work (Non-Schedule) Supply & installation of LED 2'x 2' Ceilling Panel Light 36W (220V~, CW or WW) i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips 36S/865 PSU W60L60 GM G2 or Equivalent)	72.00 No
2	N.S	Supply & installation of Wall Mounted LED Batten Light 20W (220V~, 6500K) i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips Slimline or Equivalent)	60.00 No
3	NS	Supply & installation of 2' x 2' False Ceiling Fan 14" swipe (99.99% Copper), remote controlled i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Royal, Super-asia or Equivalent)	90.00 No
4	N.S	Supply and Installation of Heat and Cocl Split DC inverter Air-conditioner 2.0 Ton (24000BTU) complete with Installation Kit (Supplied with Thermal insulated Copper pipe) i/c any other accessories required at site. Complete in all respects as approved by Engineer Incharge. (PEL fit PINV-24k, Gree, Diakan or Equavalent)	7.00 No
5	N.S	Supply and Installation of Heat and Cool Split DC inverter Air-conditioner 4.0 Ton (48000BTU) complete with Installation Kit (Supplied with Thermal insulated Copper pipe) i/c any other accessories required at site. Complete in all respects as approved by Engineer Incharge. (PEL Gree, diakan or Eqvalent)	12.00 No
6	N.S	Supply & installation of Angle Bracket Set for Split AC Out Door Unit with 4.00Nos of Rawl bolts 5/8" i/c any accessories (i.e. screw. Rawl plug or steel nail, etc.) as required at site. Complete in all respect as directed and approved by the Engineer Incharge	7.00 N o
7	N.S	Providing & laying of PVC/PVC 2-Core flexible 23/0.0076" copper conductor cable i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (KM, Eagle or Equivalent)	50.00 M
8	N.S	Providing & laying of PVC/PVC 3-Core flexible 110/0.0076" copper conductor cable i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (KM, Eagle or Equivalent)	40.00 M
9	N.S	Providing & laying of PVC/PVC 4-Core flexible 110/0.0076" copper conductor cable i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (KM, Eagle or Equivalent)	65.00 M

Ant.	Description	Quanti	tv
A N	Supply, installation, connection & commissioning of distribution boards. (DBs), Floor Standing design, made of M.S. Sheet 14 SWG with hinged door, handle, catchers and 2 coats of Approved paint, (Size 4 x5 x12") including Incoming. Main Molded Case Circuit Breaker 630 Amps T-p (50KA) 1.00 No, distribution Molded Case Circuit Breaker 200 Amps T-p (18KA) 2.00 Nos. 8125 Amps T-p (15KA) 2.00 Nos respectively. Digital Volt, Selector switches, LED Phase lights, Copper bus bars, Earthing bar, Neutral bar and any accessories required at site. Complete in all respects as approved by the engineer incharge. (for MCCB General Electric, Schneider Electric & Legrand).) No
11 N.S	Supply, installation, connection & commissioning of distribution boards, (DBs), Floor Standing design, made of M.S. Sheet 16 SWG with hinged door, handle, catchers and 2 coats of Approved paint, (Size 4'x3'x12") including Incoming Main Molded Case Circuit Breaker 200 Amps T-p (18KA) 1.00 Nos, distribution Molded Case Circuit Breaker 25 Amps T-p (10KA) 6.00 Nos & 20 Amps T-p (6KA) 6.00 Nos Miniature bircuit breakers respectively, Digital Volt, Selector switches, LED Phase lights, Copper bus bars, Earthing bar, Neutral bar and any accessories required at site. Complete in all respects as approved by the engineer incharge. (for MCCB General Electric, Schneider Electric & Legrand).	2.00	No
12 N.S			
13 N.S	Supply, installation, connection & commissioning 3-pole MCB 32A (6KA) with Plastic Enclosure i/c any accessories required at site. Complete in all respects as approved by the engineer incharge. (for MCB General Electric, Schneider Electric & Legrand). Supply, installation, connection & commissioning 2-pole MCB 20A (6KA) with Plastic Enclosure i/c any	12.00	No
	accessories required at site. Complete in all respects as approved by the engineer incharge. (for MCB General Electric, Schneider Electric & Legrand).	10.00	No
1 10/43	External Work Civil Work Providing and laying Tuff pavers, having 7000 PSI, crushing strength of approved manufacturer, over 2" to 3" sand cushion i/c grouting with sand in joints i/c finishing to require slope. Complete in all respect.		
2 3/44 E	Excavation of trenches in all kinds of soil, except cutting 'rock, for water supply pipe lines upto 5 ft. (1.5 m) depth from ground level, including trimming, dressing sides, levelling the beds of trenches to correct grade and cutting pits for joints, etc.	40000.00	Sft
	тобрось.	30000.00	Cft

	af #	Description	T Overette	
2	NS	Civil Work (Non-Schedule) Providing & Fixing Pre-Cast Kerb stone size 12"x14"x6" (300mmx350mmx150mm) and duly embedded on a bed of PCC 1:6:12 (4" thick), PCC 1:2:4 for hanuching, laid with cement sand mortor 1:3, 3/4" thick I/c painting of 3 coats complete in all respects as per design & as approved by the engineer incharge made (Izhar/Banu Mukhtar/ Mukhtar Sons) Horizontal boring underneath roads, walking path & ramps of houses for crossing of Electric power cables, PVC pipes or Water lines. Complete in all	Quantity 8000.00	
		respects as approved and as directed by the engineer incharge.	150.00	Rft
1	d-viii	External Electrical Work Supply and erection of copper conductor cables for service connection, in prelaid pipe/G.I. wire/trenches, etc. (rate for cable only):- PVC insulated, PVC sheathed 4 core 660/1100 volt grade cable, armoured with G.I. wire 16 SWG.37/2.62 mm (37/0.103")	50.00	Rft
2	24/6	Supply and erection PVC pipe for recessed wiring (main and sub-main) purpose, including bends, specials, etc. in floor, wall or trenches:- 80 mm i/d	50.00	Rft
1	N.S	External Electrical Work (Non-Schedule) Supply & Installation & commissioning of 200 KVA (11 KV/415V) 3-phase, 50 Hz step down Pad mounted / enclosed type distribution Transformer having connection group, DY-11 oil immersed natural cooled with HV & LV protections (as per WAPDA standard) i/c any other accessories required at site. Complete in all respects as approved by the Engineer incharge. (with complete purchase and tax documents) (PEL, Transfopower or Equivalent)	1.00	No
2	N.S	Providing and Laying earthing for Electric Machines I/c boring up to moisture level (up to 60' below ground level) 4" i/d including copper strip 14" x 2" x 1/4" (350 x 50 x 6 mm) connecting with 1 Nos.bare copper wire of No.8 SWG to be run in PVC pipe 20mm i/d, 1½" i/d GI pipe 5' long, GI tee & plug for watering also includs common salt, Lime (slaked) and charcoal around copper strip I/c connecting with Electric machine. Complete in all respects as approved and as directed by the engineer incharge.	8.00	No
3		Supply & Laying of 3-core, 120mm², XLPE/PVC/ SWA/PVC, 8.7/15Kv Aluminum conductor cable i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Fast Cable or Equivalent)	400.00	M
4		Supply and installation of 120mm², 3-core, 11-KV Termination Kit i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge.(Raychem or Equavalent)	2.00	No
5		Supply and installation of 120mm², Aluminum Alloy Parallel Groove Clamp complete with nut/bolts i/c any		
		accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge.	4.00	No

ef #	Description	Quantit	
	Supply, installation & connection of Garden light ground mounted 2" dia G.I pipe Light quality 10' height with 18 W LED blub (Philips) i/c mounting foundation of RCC pipe 12" dia 3' deep with cement concrete and any accessories required at site. Complete in all respects as approved by the engineer incharge.	120.00	N
1			

The Islamia University of Bahawalpur

Providing & Laying Brick Soling of Boundry Wall Sandy Track i/c 4 Nos Pipe Culverts 24' wide at Baghdad-ul-Jadeed Campus

Estimate Based on MRS Jul to Dec, 2019

ABSTRACT OF COST

Schedule Items A) Brick Soling	Rs.	35,605,235.00
B) 4 Nos Pipe Culvert 24" wide	Rs.	499,481.00
Total	Rs.	36,104,716.00
Add 5% PST	Rs.	1,805,236.00
Grand Total	Rs.	37,909,952.00

Sub-Engineer

Assistant Engineer

Executive Engineer

Technically Sanctioned for Rs.37,909,952.00

Project Director 6/9/219.

The Islamia University of Bahawalz

Providing & Laying Brick Soling of Boundry Wall Sandy Track i/c 4 No at Baghdad-ul-Jadeed Campus

		Brick Soling Description	Quantity
No 1	Reff. 3/5- iii+ 17/a	Earthowrk in ordinary soil for embankments including ploughing and mixing with blade grade or disc harrow or other suitable equipment, and compaction by mechanical means at optimum moisture content and dressing to designed section, complete 85% maximum modified	
		AASHO dry density. i) Lead upto 1/4 mile ii) Lead upto 100 ft.	740000.00 Cft 700000.00 Cft
2	18/5	Providing and laying road edging of 3" (75 mm) wide and g" (225 mm) deep brick on end, complete in all respects.	72000.00 Rft
3	3 18/1	Providing and laying dry brick pavement/soling in streets or roads, etc. sand grounted, laid in proper camber, including preparation, watering, compaction of bed to proper camber, and sand cushion.	159840.00 Cft
-	+		

Construction of 4 Nos Pipe Culverts 24' wide

2 6	.,	Description Excavation in foundation of building, bridges and other structures including deg-belling, dressing, refilling around structure with excavated earth, watering and ramming lift upto 5 ft in ordinary soil	Quantit	
2 6	.,	and other structures including deg-behing, dressing, refilling around structure with excavated earth, watering and ramming lift upto	1920.00	04
3 4 1		excavated earth, watering and ramming int upto 5 ft in ordinary soil	1920.00	04
3 4 1	- 1			Cft
4		Cement concrete brick or stone ballast 1½ " to 2" (40 mm to 50 mm) gauge, in foundation and plinth:- Ratio 1:4:8	320.00	Cft
	7/4	Pacca broik work in foundation and plinth in Cement Sand Mortar Ratio 1:3	1757.10	Cft
1 - 1		Cement Plaster 1:4 upto 20' height 1/2" thick	1152.0	Sft
5 2	21/3	Providing and laying R.C.C. pipe sewers, moulded with cement concrete 1:11/2:3 conforming to ASTM Specification C-76-79, Class II. Wall B, including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing with	96.00	Rft
		rubber ring, cutting pipes where necessary, testing, etc., complete. 18" i/d	90,00	
6	6/5-	f Cement concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate): Ratio 1: 2: 4	96.00	Cft



The Islamia University of Bahawalpur

Up-gradation of Water Supply System at Baghdad-ul-Jadeed Campus

Estimate Based on MRS Jan to Jun, 2020

ABSTRACT OF COST

1 Civil Works (Schedule Work)	Rs.	1,167,330.00
2 Water Supply (Schedule)	Rs.	399,445.00
3 Water Supply (Non-Schedule)	Rs.	17,055,903.00
Total	Rs.	18,622,678.00
Add 5% PST	Rs.	931,134.00
Grand Total	Rs.	19,553,812.00

Assistant Engineer 20

Executive Engineer 20/4/2020

Technically Sanctioned for Rs.19,553,812.00

The Islamia University of Bahawalpu Up-gradation of Water Supply System at Baghdad-ul-Jadeec

	Civil w	Description	Quantity		
t	through condition	rork in excavation of drains, irrigation channels the excavator / drag lines in all kind of soil and sons(dry, wetslush, daldal and under water) ing its disposal and preparation of working paderation of machinery. (Lead upto 100 ft)	101250.00	Cft	
1/45	Disma	antling and removing road metalling.	500.00	Cft	
4/46	includ	antling and removing road pavement, etc., ding screening and stacking of byproducts upto chain lead (30 metre).	400.00	Cft	
6/3	mm	nent concrete brick or stone ballast 1½ " to 2" (40 to 50 mm) gauge, in foundation and plinth:- io 1:4:8	500.00	Cft	
7/4		cca brcik work in foundation and plinth in Cement nd Mortar Ratio 1:6	2000.00	Cft	
11	1/9 Ce	ement Plaster 1:4 upto 20' height 1/2" thick	3600.0	Sft	
6	fin	ement concrete plain including placing, compacting, hishing and curing complete (including screening and ashing of stone aggregate): Ratio 1: 2: 4	350.00	Cft	
9	6/6	cabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars) Deformed bar-40-Grade Reinforced cement concrete in slab of rafts / strip foundation, base slab of column and retaining walls; etc and other structural members other than those mentioned in 5(a) (i) above not requiring form work (i.e. horizental shuttering) complete in all respects Type C (nominal mix 1: 2: 4)	1500.00	Kg	
		Western Committee Line			
1	23/28 +b-ii	'B' (such as bend, tee cross collar, reducer, tail piece, flanged spigot, cap, flanged socket, taper, angle branch, plug etc.) for cast iron pipe line, complete:- C.I. flanged specials, with flanged and flanged joints:- i) 3" to 6" (80 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d	450.0 2800.0	K <u>ç</u> Kç	
2	23/41	Making connection for new watersupply lines with the running main, including excavation of trench and refilling, complete, but excluding cost of pipe and specials, etc.Diameter of running main: i) upto 6" i/d (150 mm) ii) upto 8" i/d (200 mm)	20.0	C	0 0

Description	Quantit	y
Water Supply Line (Non-Schedule)		
Supply & Erection of Butter fly valve of kitz Japan for 'B' class working pressure uPVC water supply line including uPVC flangs etc complete in all respects as		
approved by the engineer incharge		
i) 4" dia	12.00	No
ii) 6" dia	10.00	No
iii) 8" dia	8.00	No
Providing, laying, cutting, jointing, testing and disinfecting uPVC pipeline for water supply 'B' class working pressure including all specials as required at site of work (Bita/Dadex or equialent quality) complete in all respects as approved by the engineer incharge i) 4" dia ii) 6" dia iii) 8" dia	7000.00 9000.00 6000.00	K Per
Supply & Erection of jabal joint for 'B' class working pressure uPVC water supply line to connect with Asbostos water supply line complete in all respects as approved by the engineer incharge. i) 4" dia	6.00	No
ii) 6" dia	10.00	No
iii) 8" dia	8.00	No
N.S Making connection for new watersupply lines with the running main to building of all size of pipe, including excavation of trench and refilling, connection clamp of uPVC and all other accessories as required at site complete in all respects as approved by the engineer incharge.	250.00	No
		100000

The Islamia University of Wahawalpur

Extension of University College of Art & Design at Baghdad-ul-Jadeed Campus Estimate Based on MRS Jan to Jun, 2020

ABSTRACT OF COST

A) Schedule Items		
i) Civil Work	Rs.	21,183,197.00
ii) Plumbing Work	Rs.	130,101.00
iii) Electrical Work	Rs.	688,295.00
Total of "A"	Rs.	22,001,593.00
B) Non-Schedule Item	<u>IS</u>	
i) Civil Work	Rs.	8,012,185.00
ii) Plumbing Work iii) Electrical Work	Rs.	716,109.00
iii) Electrical Work Total of "B"	Rs.	4,185,380.00
TOTAL OF B.	Rs.	12,913,674.00
Total "A + B"	Rs.	34,915,267.00
Add 05% Punish Sal	oo Toy	

Sub-Engineer

Grand Total

Assistant Engineer 20

Rs.

Rs.

Executive Engineer 1000

1,745,763.00

36,661,030.00

Technically Sanctioned for Rs. 36,661,030.00

The Islamia University of Bahawa

- C University	College of	Art &	Design at	Baghdad-
Extension of University				

		Civil Work Description	Quanti	ty	
		Pacca Brick work with cement sand mortor			
		Ratio 1:3 (Ground Floor)	500.00	Cft	
	1	7 Datio 1:5 (Ground Floor)	1550.00	Cft	
	/	1.5 (1ct Floor)	17250.00		
		- 1.2 (1st Floor)	1500.00	Cft	
		1.5 (2nd Floor)	2756.25	Cft	
1		(v) Ratio 1.5 (210 1 1861)		Cit	
	2 6/9	Fabrication of mild steel reinforcement for cement concrete, i/c cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars) 40-Grade	24250.00	Kg	
3		Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid position, or prestressed members cast in situ, complete in all respects Type C (nominal mix 1:2:4) 1st Floor	8250.00	Cft	
4	1	Cement plaster 3/8" (10 mm) thick under soffit of R.C.C. roof slabs only, Above 20' height. 1:3	12855.00	Sft	, A
5	11/9b	Cement plaster upto 20' (6.00 mm) height:-			
	11/50	1/2" (13 mm) thick i) Ratio 1:4	28560.00	Sft	2
		72 (13 mm) thick if Tradio 1.4			
6	9/5	Single layer of tiles 9"x4½"x1½" (225x113x40 mm) laid over 4"(100 mm) earth and 1" (25 mm) mud plaster without Bhoosa, grouted with cement sand 1:3 on top of RCC roof 'slab, provided with 34 lbs. per %Sft. or 1.72 Kg/Sq.mbitumen coating sand blinded.	15250.00	Sft	7
7	9/45	Providing and Laying Insulation material of Extruded Polystyrene XPS in Rigid Insulation/Foam Board on roof or walls, Density 32-38Kg/M, compressive strength 250-400 kpa, R-value 5 per inch thickness and water obsorbtion (1% by volume, cell structure clored cell) i/c cutting and placing in position			
		complete in all respect 2" thick	15250.00	Sft	1
8	26/37	Supplying and laying polythene sheet over D.P.C. supplying and laying polythene sheet over D.P.C. under 'floors and on roofs,etc. 500 gauge (.005" thick)	30500.00	Sft	
9	6/2	Dry rammed brick or stone ballast, 1½" to 2"(40 mm to 50 mm) gauge.	4175.00	Cft	
10	13/5	Painting door and window any type on new surface 3 coats	5525.00	Sft	
11	6/5f	Cement concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate): Ratio 1:2:4	1875.00	Cft	
			16.00	No	1
2	9/15	Making Khuras on roof 2'x2' size			
4	3/13				

	Provid	Description	Quantity	
	and p manu using section 45mi sides quali glas lated hard	bescription ling and fixing all types of glazed aluminium ws of anodized champagne colour partly fixed arty sliding using deluxe section of approved facturer having Frame of size100mmx 30mm frame at bottom, at top and side leaf frame cans of 60mm x 23mm at top & bottom and size on x25mm at center and size 45mm x 25mm at s, Jali leaf frame size 43mm x 13mm i/c fine ity aluminum jali, 5mm thick imported tinted s with rubber gas ket using approved standard thes, wheel, stopper, brush chennel angle joint and dware etc.complete in all respect 1.6 mm thick	3650.00	Sft
14 12/5	shu thic lip inc al	utter sterling or equivalent with commercial ply (5 mm ping 1½"x3/8" (40mm x 10mm) around shutter uminium kick plate 22 SWG on both sides & finger		Sit
15 12	2/18-ii P	Providing and fixing sliding bolt to doors:- iron sliding bolt, 2" (300 mm) long	1380.00	Sft
1 . 1	12/45	Glazing with panes (24 oz. to 26 oz.), using putty and deodar wooden fillets.	26.00	No
17	25/39	wooden illiets.	100.00	Sft
18	25/35	Providing and fixing stair railing of 2½" (63 mm) i/d G.I. pipe, welded with 5/8"x5/8" (16x16 mm) square M.S. bars 2'-9" (838 mm) high, fixed in each step, complete in all respects, including painting, polishing three coats. Providing and fixing terrace railing of 2" (50 mm) i/d conduit pipe 16 SWG, welded with 5/8"x5/8" (16x16 mm) square bar 2.75 ft. (838 mm) high fixed at 5" (125 mm) centre to centre, in reinforced cement concrete slab with suitable arrangement, complete in all respects, as per design and drawing.	75.00	Rft
19	6/12		248.00	Rft
20	11/23	Providing and fixing ornamental cement jali 2" (50 mm) thick (1: 2: 4), without steel.	665.00	Sft
		Distempening on new surface 3 coats	12855.00	Sft
21	13/31	Preparing surface and painting with emulsion paint:- i) New surface 3 coats ii) old surface 2 coats	27750.00 27750.00	Sft Sft
22	13/32A	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect: New Surface 2 Coats		Sft
23	4/50	Dismantling glazed or encaustic tiles, etc.	3350.00	
24	4/13	Dismantling brick work in lime or cement mortar.	150.00	Cf
		The state of the s	130.00	U

Civil Work (Non s	Quantity	
color for skirting / dado size 9"x26"x3/8" laid over white cement sand mortar (1.2) i/c filling joints in charges complete in all respect as approved & Equivalent) N S Providing and laying prepolished tile Floor/dado Tile style bons.	7000.00	
approved by Engineering incharge.(SPM-110 Master N.S Providing 8	10255.00	Sft
Providing & laying 3/4" Thick Marble Slab (Boticeena corner) and 1:2 cement sand mortar for laying of chemical polishing, complete in all respects as per Engineer Incharge. (for stair steps/kitchen cabinet) M.S Steel Grill for windows comprising of 1/2"x1/2" frame including	380.00	Sft
respect as shown on the drawings, specification and/	3650.00	Sft
Providing & Fixing Kitchen Cabnet consisting of lamination board 3/4" thick for leaves, kail wood frame polish for gola complete in all respects as per design, incharge (Down portion) N.S Providing & Fixing Cabnet upper portion consisting of lamination board 3/4" thick box and leaves, Partal wood frame 3" x 1", Gola for 'leaf 3/4" x 3/4" including siprit polish for gola complete in all respects as per design, drawing a per design drawing a per	45.00	Sft
by the Engineer Incharge	36.00	Sft
Providing & laying colored glazed Multani Tile 1/4" thick laid with cement sand mortor 1:2, 3/4" thick complete in all respect as approved & as directed by the Engineer Incharge	136.00	Sft
N.S Providing, Fabricating and fixing 16 SWG M.S sheet hollow pressed Jamb frame (Factory primme) for door welded with MS flat size 10"x1"x1/8", hold fast i/c welding/screwing 4" long iron hinges, filling concrete for the jamb frame and embedding hold fast in the adjointing walls with 1:2:4 concrete, enamel painting etc. complete in all respects as show on the drawing and/ or as directed by the engineer, in conformance	1550.00	Sft
with following size 10"x2-1/2" N.S Providing & fixing Hydraulic door closer Japan made		
or approved quality complete in all respects as approved by the engineer Incharge.	10.00	No

	Providence	Quantity	1
11 N	board of size 600x600mm x 7.5mm over 1"x1" aluminum tees longitudinally & traversally & accessories, network & hardware etc complete in all	8500.00 2000.00	
	or as directed by the	648.00	Sf
	Plumt	0,0.00	
1 19	with foot rest. Coloured watern), combined	36.00	No
19/	bracket set, copper connection etc.		
3 19/3	4 P/F "P" trap:- 10 cm (4") glazed.	36.00	No
4 19/2	Providing and fixing chromium plated tee stop	36.00 42.00	No
	Providing and fixing chromium plated bib cock:-	14.00	No
1972	Providing and fixing chromium plated pillar-cock, heavy:- 1/2"	2.00	No
1 N.S	Plumbing Work (Non-Schedule) Providing, laying, fixing and testing uPVC Soil Waste, vent & rain water down pipe "NIKASI PIPES Durafit/ Beta/ Pak Arab/Equalvent" including uPVC fittings with solvent cement jointing or rubber ring joints complete in all respects including clamps, bends tees, Y-tees, Cowl reducers, clean out WC- Elbow Adopter etc. Complete in all respects and as approved by Engineer Incharge i) 4" dia ii) 6" dia iii) 8" dia Providing and laying, cutting, jointing, testing and disinfecting PPRC pipe line(M.S Minhas pvt Ltd) for hot & cold water supply complete in all respects, i/c specials such as coupler, reducing socket, elbow,	200.00 100.00 100.00	Rftt Rftt

		1	Description	Quantity	
		A IN	nd shower, wash basin, bibcock etc, Complete in all espect as per specifications and drawings and as		
		(1)	pproved by the Engineer Incharge. 25mm dia 32mm dia	400.00	Rft
	1	_	i) 40mm dia	1000.00	Rft Rft
1	6	10	Providing & Fixing Gate valve of PPRC best quality complete in all respect as per specifications and		
A		10	drawings and as approved by the Engineer Incharge 25mm dia	0.00	
۱			ii) 32mm dia	8.00 4.00	No No
			iii) 40mm dia	2.00	No
	4	N.S	Providing & Fixing uPVC "P" trap 4" dia complete in all respect as approved by the Engineer Incharge.	26.00	No
	5	N.S	Providing & Fitting Steel floor jali best quality complete in all respect as per specifications and		
	6	N.S	and as approved by the Engineer Incharge.	16.00	No
		14.5	Providing and fitting glazed earthen ware Counter basin/Vanity (HD16 Porta or equivalent company) including waste pipe and waste coupling, etc. best quality complete in all respects as approved by the engineer incharge		
	7	N.S	Providing and fitting glazed earthen ware water closet (WC) Orisa pattern, combined with foot rest best quality complete in all respects as approved by the engineer incharge (HDD9 Porta or equivalent company)	14.00	No
	8	N.S	Providing and fixing Looking Glass best quality 2'x2' complete in all respects as approved by the engineer incharge	18.00	No
	9	N.S	Providing and fitting chromium Muslim Shower best quality complete in all respects as approved by the engineer incharge (Porta or equivalent company)	88.00	Sft
	10	N.S	Providing and fitting chromium plate to bu	4.00	No
			best quality complete in all respects as approved by the engineer incharge (Porta or equivalent company)	20.00	No
	1	24/3	Electric Work Supply and erection of PVC pipe for wiring recessed in walls, including inspection boxes, pull boxes, hooks, cutting jharries, and repairing surface, etc., complete with all specials. i) 20 mm i/d	1	
			ii) 25 mm i/d	150.00 75.00	
	2	24/10	Supply and erection of single core PVC insulated coppe conductor cables, in prelaid PVC pipe/ M.S conduit/G.l pipe/wooden strip batten/wooden casing an capping/G.l wire/trenches (rate for cables only).250/440 volts, PVC insulated:		
			7/1.63 mm (7/0.064")	3168.0	00 F
				C	

			Quantit	
	1	Description Supply and erection of copper conductor cables for service connection, in prelaid pipe/G.I. wire/trenches, etc. (rate for cable only):- PVC insulated, PVC sheathed 4 core 660/1100 volt grade cable, armoured with G.I. wire 16 SWG. 19/2.11 mm (19/0.083")	300.00	Rft
1		Supply and erection of ceiling rose, bakelite.	50.00	No
/	5 24/27	Supply and erection of bakelite button holder shade, large size.	60.00	No
	1 N.S	Electric Work (Non-Schedule) Supply & installation of LED 2'x 2' Ceilling Panel Light 36W (220V~, CW or WW) i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips 36S/865 PSU W60L60 GM G2 or Equivalent)	40.00	No
2	N.S	Supply & installation of LED 17W Down Light (6" Surface Mounted, 220V~) i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips Meson or Equivalent)	55.00	No
3		Supply & installation of Wall Mounted LED Batten Light 20W (220V~, 6500K) i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips Slimline or Equivalent)	160.00	No
4	a	Supply & installation of Wall Bracket Fan 18" (99.99% Copper) i/c any accessories (i.e. mounting screws & etc) is required at site. Complete in all respect as directed and approved by the Engineer Incharge (Younis, famoor, Pakfan or Equivalent)	6.00	No
5	m re-	upply & installation of Metal Body Wall Bracket Fan 24" 19.99% Copper) i/c any accessories (i.e. widing of ounting holes and 4.00nos of rawl bolts ¼" etc) as quired at site. Complete in all respect as directed and proved by the Engineer Incharge (SK mega or juivalent)	10.00	No
6	res Incl	pply & installation of Ceiling Fan 56" (99.99% Copper) any accessories required at site. Complete in all pect as directed and approved by the Engineer harge (Younis-Deluxe, Tamoor-Deluxe, Pakfanuxe or Equivalent)	50.00	No
7 1	acce requ appr	oply & installation of Metal body Exhaust fan 20" 99% Copper) with metal mounting frame i/c any essories (i.e. screw. Rawl plug/rawl bolt etc.) as sired at site. Complete in all respect as directed and roved by the Engineer Incharge (Tamoor, Indus,		
	Paki	fan or Equivalent)	8.00	No

	Description	Quanti	W
	Supply & installation of PVC Exhaust fan 12" (89.89% Copper) it any accessories (i.e. screw. Rawl plug or steel nall, etc.) as required at site. Complete in all respect as directed and approved by the Engineer incharge (GFC, Indus, Pakfan or Equivalent)	8.00	No
/	N S Supply & installation of Universal 3-Pole Socket with 13A Switch with plastic back box 3"x 3" i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips ECO Series Q2 or Equivalent)	80.00	No
10	N.S. Supply & installation of a Power plug 15A with plastic back box 3"x 3". I/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips ECO Series Q2 or Equivalent)	40.00	No
11	N.S Supply & installation of a Fan Dimmer 300W with plantic back box 3"x 3" i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips ECO Series Q2 or Equivalent)	50.00	Ne
	N.S Supply & installation of a Double Single Pole Switch Plate with plastic back box 3"x 3" i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips ECO Series Q2 or Equivalent)	10.00	No
13	N.S Supply & installation of a Four Single Pole Switch Plate with plastic back box 3"x 3" i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips ECO Series Q2 or Equivalent)	10.00	No
	Supply & installation of a Eight Single Pole Switch Plate with plastic back box 3"x 6" i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge. (Philips ECO Series Q2 or Equivalent)	36.00	No
5 N.	Supply & installation of a Four Single Pole Switch & Two 2-Pin Socket Plate with plastic back box 3"x 6" i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge. (Philips ECO Series Q2 or Equivalent)	20.00	No
6 N.S	Supply & installation of PVC cable trunk (Duct) 16x25mm i/c any accessories (i.e. screw. Rawl plug or steel nail, etc.) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (GM, Popular or Equivalent)	50.00	Rfi
N.S	Supply & installation of PVC cable trunk (Duct) 40x40mm i/c any accessories (i.e. screw. Rawl plug or steel nail, etc.) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (GM, Popular or Equivalent)	50.00	Rf

Description	(Quantity	
Description I.S Supply & Installation & commissioning of 200 KVA (11 KV/415V) 3-phase, 50 Hz step down Pad mounted / enclosed type distribution Transformer having connection group, DY-11 oil immersed natural cooled with off load tap changer +2.1/2 % - 5% and 7.5% (as per WAPDA standard) i/c any other accessories required at site. Complete in all respects as approved by the Engineer incharge. (with complete purchase and tax documents) (PEL, Transfopower or Equivalent)		1.00	No
N.S Supply, installation, connection & commissioning of distribution boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main Molded Case Circuit Breaker of 125 Amps T-p (15KA) 1.00 No, Distribution Miniature Circuit Breaker of 10/20 Amps S-p (6KA) 24.00 Nos, LED phase light volt meter type (RYB), Earthling bar, Neutral bar and any accessories (i.e. Earth/neutral bar, Nut/bolts, Screws/rawl plugs, Jumper connections & etc.) required at site. Complete in all respects as approved by the engineer incharge. (for MCCB & MCBs Hitachi, Schneider Electric, Legrand or equivalent).			
N.S Supply, installation, connection & commissioning of distribution boards, (DBs), Floor Standing design, made of M.S. Sheet 14 SWG with hinged door, handle, catchers and 2 coats of Approved paint, (Size 4'x4'x12' including Incoming Main Molded Case Circuit Breaker 400 Amps T-p (36KA) 1.00 No, distribution Molded Case Circuit Breaker 100 Amps T-p (15KA) 2.00 Nos &125 Amps T-p (15KA) 2.00 Nos respectively, Digital Volt, Selector switches, LED Phase lights, Copper bus bars, Earthing bar, Neutral bar and any accessories required site. Complete in all respects as approved by the engineer incharge. (for MCCB General Electric, Schneider Electric & Legrand).	') e	4.00	No
N.S Providing and Laying earthing for Electric Machines I/o boring up to moisture level (up to 60' below ground lev 4" i/d including copper strip 14" x 2" x 1/4" (350 x 50 x mm) connecting with 1 Nos.bare copper wire of No.8 SWG to be run in PVC pipe 20mm i/d, 1½" i/d GI pipe long, GI tee & plug for watering also includs common salt, Lime (slaked) and charcoal around copper strip I connecting with Electric machine. Complete in all respects as approved and as directed by the enginee incharge.	el) 6 e 5'	1.00	No
N.S Supply and installation of 120mm², Aluminum Alloy Parallel Groove Clamp complete with nut/bolts i/c any accessories required at site. Complete in all respect directed and approved by the Engineer Incharge.	y as	2.00	No No
N.S Providing & laying of PVC/PVC 2-Core flexible 23/0.0076" copper conductor cable i/c any accessor required at site. Complete in all respect as directed approved by the Engineer Incharge (KM, Eagle or Equivalent)		60.00	Rft

- 3	#		Description	Quar	ntity	
	N.S	with insul pipe casi pipe resp	ng of light or fan point from switch board to the point 3-Nos of 1.5 mm² (3/0.029") single core PVC lated copper conductor cables, in prelaid PVC /M.S. conduit/G.I pipe/wooden strip batten/wooden ing an capping/G.I. wire/trenches in 20mm (3/4") PVC is i/c any accessories required at site. Complete in all pect as directed and approved by the Engineer marge.	200.00	Rf	ft
	25 N	boa sin pre ba 25	cuit wiring from MCBs board to gang switch ard/multi light plug with 3-Nos of 2.5 mm² (7/0.029") agle core PVC insulated copper conductor cables, in elaid PVC pipe/M.S. conduit/G.I pipe/wooden strip atten/wooden casing an capping/G.I. wire/trenches in form (1") PVC pipe i/c any accessories required at site. complete in all respect as directed and approved by the ingineer Incharge	80.00	Rft	
	26		Viring of light or fan from point to point with 3-Nos of 1.5 mm² mm (3/0.029") single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches in 20mm (3/4") PVC pipe i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge	33.33		
Vice Chareel	27	N.S	Wiring of Multi/light plug from point to point with 3-Nos of 2.5 mm² (7/0.029") single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches in 20mm (¾") PVC pipe i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge	150.00	Rft	
	28	N.S	Circuit wiring from MCBs board to Power Plug with 3-Nos of 6 mm² (7/0.044") single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches in 25mm (1") PVC pipe i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge	70.00	Rft	8
				30.00	Rft	150
	100				11 1	

Extension of Directorate of Engineerring & Establishment of Civil & Electric Work Shop at Baghdadul-Jadeed Campus

Estimate Based on MRS Jan to Jun 2020

ABSTRACT OF COST

A)	SCHEDULE WORK		
-1	Civil Works	Rs.	8,229,135.00
Ш	Plumbing Works	Rs.	84,391.00
Ш	Electrical Works	Rs.	149,020.00
	Total of "A"	Rs.	8,462,546.00
B)	NON-SCHEDULE WORK		
1	Civil Works	Rs.	1,633,170.00
- 11	Plumbing Works	Rs.	144,766.00
Ш	Electrical Works	Rs.	122,816.00
	Total of "B"	Rs.	1,900,752.00
	Total of (A+B)	Rs.	10,363,298.00
	PST 5%		518,165.00
	Grand Total	Rs.	10,881,463.00

Covered Area
Per Sft Cost

6,787.00 Sft

1,603.00

Sub-Engineer

Executive Engineer

Technically Sanctioned for Rs.10,881,463.00

Project Director /

The Islamia University of Baha nof Directorate of Engineerring & Establishment of Civil & Elect

	Civil work Description	Quan	tity
101	Excavation in foundation of building, bridges and other structures including deg-belling, dressing, refilling	7981.00	Cf
	ramming lift upto 5 Ft. Ordinary 3011	7901.00	CI
2	Spraying anti-termite liquid mixed with water in the ratio of 1:40	5320.00	Sft
3	Cement concrete brick or stone ballast 1½ " to 2" (40 mm to 50 mm) gauge, in foundation and plinth:-Ratio 1: 4: 8	1330.00	Cft
4	Providing & Laying pacca B/Work in foundation and plinth in Cement Sand Mortar Ratio 1:6	500.00	Cft
5	Providing & Laying Damp Proof Course of Cement oncrete (1:2:4) using Cement, Sand and Shingle including hot Bitumen coating of Grade-10 / 20. 2" thick with 1-coats of Bitumen & Polythene One Layer.	1199.99	Sft
6	Pacca B/Work in Cement Sand Mortar Ground floor, i) Ratio (1:6)	11172.00	Cft
7	concrete, including cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars) Defarmed bar.	4066.80	Kg
	Providing & laying reinforced C. Concrte using coarse sand and screened graded washed aggrigate in required shape & design i/c frames, moulds, shuttering, lifting, compacting, curing, rendering & finishing exposed surface Complete but excluding the cost of steel. reinforcement & its fabrication and placing in position. Reinforced Cement Conc in roof slabs beams, columns, lintles and other structural members cast-in-situ. Complete in all respect. i) Ground Floor Type-C Ratio 1:2:4	3463.12	Cft
	9 Reinforced cement concrete in slab of rafts / strip foundation, base slab of column and retaining walls; etc and other structural members other than those mentioned in 5(a) (i) above not requiring form work (i.e. horizental shuttering) complete in all res Type-C Ratio 1:2:4	1330.00	Cft
	10 Cement Plaster 1:4 upto 20' height 1/2" thick	26165.0	Sft
	11 3/8" thick Cement Plaster under soffit RCC slab ratio (1.3) Ground Floor	6201.00	Sft
	12 Supplying & Filling Sand under Floors or Plugging in wells	1980.00	Sft
	 Dry rammed brick or stone ballast, 1½" to 2"(40 mm to 50 mm) gauge. Providing and laying topping of cement concrete 	1980.00	Sft
	14 Providing and laying topping or certain cases as 1:2:4,including surface finishing and dividing in panels: 1.50" thick	680.00	Sft

	Description	Quantit	V
	nt concrete plain including placing, compacting,	Quantit	
1	shing and curing complete (including screening and washing of stone aggregate): Ratio 1:2:4	750.00	Cft
16	Filling, watering and ramming earth under floors:- i) with surplus earth from foundation, etc. ii) with new earth excavated from outside, lead upto one chain (30 m) 'upto ¼ mile (400 m).	3000.00 4250.00	Cft Cft
17	Painting new surface: Preparing surface and painting of doors and windows any type (including edges):- 3 coats	1540.00	Sft
18	Preparing surface and painting with emulsion paint:- 3 coats	22911.00	Sft
19	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect: new surface 3 coats	4350.00	Sft
20	Providing and fixing 1½" (40mm) thick solid flush door shutter sterling or equivalent with commercial ply (5 mm thick) on both sides double pressed and deodar wood lipping 1½"x3/8" (40mm x 10mm) around shutter including chromium plated fitting, iron hinges with aluminium kick plate 22 SWG on both sides & finger plate complete in all respect.	567.00	Sft
21	Providing and fixing mild steel chowkat of doors, windows, C.window, etc. including holdfast, making and threading holes for hinges, etc. complete:- M.S. angle iron 1½"x 1½"x ¼" (40x40x6 mm) welded with M.S. flat 2"x ¼"	567.00	Sft
22	Providing and fixing windows consisting of M.S. box section frame 2"x1½", leaves frame 1-½"x1" box section frame for glazing 3/8"x3/8" using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" M.S. flat for fixing 3/16" thick glass panes M.S. box section ½"x½" of 16 SWG for fixing 24 SWG wire gauze on 'outer side by means of ¾"x1/8" M.S. flat and screws I/C all C.P. fitting & painting 3 coats complete in all respect.	280.00	Sft
23	Providing and laying roof insulation, comprising of single layer of tiles 9"x4½"x1½" (225x113x40 mm) grouted with cement sand mortar 1:3 laid over 2" (50 mm) thick earth (including mud plaster) over thermopore sheet, over polythene sheet 300 gauge over a layer of bitumen,complete in all respects:-Thermopore sheet 1" (25 mm) thick	6587.00	Sft
24	Khuras on roof 2'x2'x6" (600 x 600 x 150 mm)	4.00	No
25	Providing & laying vertical damp proof course with cement sand plaster and bitumen coating but exculding polythene sheet 500 gauge With two coat of bitumen 1:3, 1/2" thick	3192.00	Sft
26	Laying floor of approved coloured glazed tiles ½ "(6 mm) thick, laid in white cement and pigment on a bed of ¾" (20 mm) thick cement mortar 1:2.	711.00	Sft

	Description	Quar	tity
	ed glazed tile dado 1/4" (6mm) thick in pigment		
	1.2 cement, sand mortar 3/4"(20mm) thick.		80
	roluding finishing	2187.25	Sft
1			
28	Providing and fixing sliding bolt to doors - iron sliding	20 00	Nos
	bolt, 12" (300 mm) long	20.00	NOS
		5004.00	Sft
29	Distempering - new surface - iii) three coats	5384.00	311
_	Civil work (Non-Schedule)		
No	Description	Quant	ity
1	Providing and laving Floor Tile 24"x24" Granite Effect		
	(GEM) Dark Polished SB including 05% Wastage laid		
	in cement with pigment on a bed of 3/4" thick cement		
	sand mortar 1.2, complete in all respects as approved	5500.00	Sft
	by Engineering incharge		
	Electrical Work	Quant	ty
No	Description Technique recessed	3,50,70	
1	Supply and erection of PVC pipe for wiring recessed		
	in wall including inspection boxes pull boxes, hooks,		
	cutting jharries and repairing surface etc complete		
	with all specials.	400.00	Rft
	i) 3/4" i/d (20 mm)	650.00	Rft
	ii) 1" i/d (25 mm)		
2	Supplying and erection of single core PVC insulated		
-	copper conductor PVC insulated cables in prelaid		
	PVC pipe (rate for cables only)	3800.00	Rft
	a) Cable 3/0.029"	1150.00	Rft
	b) Cable 7/0.029"	1150.00	
1	a transfer of coiling rose, bakelite	40.00	No
3	Supply and erection of ceiling rose, bakelite.		
4	Supply and erection of switches 5 Amp.		
	Piano type	95.00	No
5	Supply and erection of M.S. sheet box of 16 SWG,		
	10 cm (4") deep, with 4.75 mm thick (3/16") bakelite		
	sheet top, for recessed wiring, including making holes		
	for regulators, switches, plugs, etc.	20.00	No
	i) 10 x 10 cm (4"x4") ii) 17.5 x 10 cm (7"x4")	25.00	No
	iii) 17.5 x 10 cm (7 x4 7) iii) 20 x 25 cm (8"x10")	20.00	No
6	Supply and erection of 3 pin switch and plug		
	combined, recessed type.		
	i) 5 Amp	30.00	No
	ii) 10/15 Amp	20.00	No
	Electrical Work (Non-Schedule)		4:4.
No	Description	Quan	tity
	ALED DILLE 19 Mottilo Glassi of		
1	Supply & Erection of LED Blub 18 Watt i/c Glassi of approved quality complete in all respects as approved		
	by engineering incharge. (Philips)	80.00	No
	Plumbing Work	T Oues	otity.
No	Description P/F water closet squatter type (orisa pattern)	Quar	itity
1	combined with foot rest. Coloured, or as		
	approved by the engineer incharge.	10.00	No
100			

	-3			
		Description	Quantit	У
		ng and fitting plastic made low down flushing ern (3 gallons capacity) including bracket set oper connection, etc complete coloured, as	E.	
,	/	approved by the engineer incharge.	10.00	No
	3	Providing and fixing Looking Glass 55x40 cm (22"x16") size, and 5 mm thick, first quality.	6.00	No
	4	Providing and fitting: i) plastic soap dish	6.00	No
		ii) plastic towel rail	6.00	No
		iii) plastic shelf (24"x5") with bracket and railing.	6.00	No
	5	Providing and fitting glazed earthen ware wash hand basin 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc.		
		coloured, with pedestal	8.00	No
	6	Providing & fixing chromium plated tee stop cock 1/2"	18.00	No
	7	Providing and fixing chromium plated Bib cock 1/2"	28.00	No
	8	Providing and fitting "P" trap: 10 cm (4") glazed.	20.00	No
	9	Providing and fixing chromium plated shower rose:- 1.5x10 cm (½"x4")	5.00	No
	10	Providing and fixing chromium plated pillar-cock, heavy: 1.5 cm (½")	8.00	No
t				
Г		Plumbing Work (Non-Schedule) Description	Quantit	V
	s fi jo Y	Providing, laying, fixing and testing uPVC plain ends socketed pipes Type-B Soil Waste, vent & rain water as per approved make and quality including uPVC littings with solvent cement jointing or rubber ring pints complete in all respects including clamps, tees, retees, Cowl reducers, clean out WC- Elbow Adopter to complete in all respects i) 3" dia Pipe Dadex/Beeta ii) 4" dia Pipe Dadex/Beeta	185.00 360.00	Rft Rft
2	dis cor ma cor	oviding, laying, cutting, jointing, testing and sinfecting PPRC pipeline for hot & cold water supply implete in all respects, i/c specials such as upler, reducing socket, elbow, endcaps, ile/female, threaded, fittings, like teese, adoptors to nect polydex pipes to other pipe and shower, wash sin, bibcock etc. as required at site.		
		i) 32 mm o/d (Dadex / Beta / BBJ)ii) 25 mm o/d (Dadex / Beta / BBJ)	140.75 365.50	Rft Rft
		viding & fixing floor plastic Jali complete in all ect & as approved by the Engineer Incharge.	13.00	No
1				

The Islamia University of Bahawalpur Renovation of Ground Floor & 1st Floor of Old DMS Building at Baghdad-ul-Jadeed Campus

Estimate Based on MRS (Jan to Jun) 2020

ABSTRACT OF COST

A)	Schedule Items		
il	Civil Work	Rs.	4,172,852.92
m	Plumbing Work	Rs.	53,946.20
""	Electric Work	Rs.	2,517,003.00
	Total of "A"	Rs.	6,743,802.12
B)	Non-Schedule Items Civil Work		
11	Plumbing Work	Rs.	2,686,905.00
III	Electric Work	Rs.	164,717.55
	TISSUITE WORK	Rs.	4,971,659.44
	Total of "B"	Rs.	7,823,281.99
C)	Total of "A+B"		.,020,201100
	ATB	Rs.	14,567,084.11
D)	Add 16% Punjab Sales Tax	Rs.	2,330,733.00
	Total of "C+D"	Rs.	16,897,817.00

Assistant Engineer

Technically Sanctioned for Rs.16,897,817.00

Project Director 20/22.

Renovation of Ground Floor & 1st Floor of Old DMS Building at Baghdad-u

		Civil Work Description	Quantity
No.	MRS R 25/51	Providing and fixing all types of partly fixed and partly operable government of the Al-Cop of anodised bronze colour aluminium doors, using delux section of M/s Al-Cop of anodised bronze colour aluminium doors, using delux section of M/s Al-Cop of anodised bronze colour aluminium doors, using the cost of M/s and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakistan Cables, having chowkat frame of size 40 x 100 mm (1/s" x '4") and Pakist	1284.50 Sft
2	25/52	Providing and fitting all types of glazed aluminium windows of anodised Providing and fitting all types of glazed aluminium windows of anodised bronze colour partly fixed and partly sliding using delux sections of M/s Al-Copbronze colour partly fixed and partly sliding using delux sections of M/s Al-Copbronze colour partly fixed and partly sliding using 20 mm (4"x¾") and 'leaf frame or Pakistan 'Cables having frame size of 100 x 20 mm (4"x¾") and 'leaf frame or Pakistan 'Cables having frame size of 100 x 20 mm (4"x¾"), all of 1.6mm 'thickness including 5 mm thick sections of 50 x 20 mm (2"x¾"), all of 1.6mm 'thickness including 5 mm thick sections of 50 x 20 mm (2"x¾"), all of 1.6mm 'thickness including 5 mm thick sections of 50 x 20 mm (2"x¾"), all of 1.6mm 'thickness including 5 mm thick sections of 50 x 20 mm (2"x¾"), all of 1.6mm 'thickness including 5 mm thick sections of 50 x 20 mm (2"x¾"), all of 1.6mm 'thickness including 5 mm thick sections of 50 x 20 mm (2"x¾") thickness including 5 mm thick sections of 50 x 20 mm (2"x¾"), all of 1.6mm 'thickness including 5 mm thick sections of 50 x 20 mm (2"x¾") thickness including 5 mm thick sections of 50 x 20 mm (2"x¾"), all of 1.6mm 'thickness including 5 mm thick sections of 50 x 20 mm (2"x¾").	1975.50 Sft
3	7/21-i	First class brick walling laid in 1:3 cement sand mortar, reinforced with 1" (25 mm) wide 18 gauge hoop iron:- 4½" (113 mm) thick walling with hoop iron, bonding 6" (150 mm) apart.	1677.00 Sft
4	11/9-b	Cement plaster 1:4 upto 20' (6.00 m) height:- 1/2" (13 mm) thick	3420.00 Sft 64,932.50
5	13/31-i4	Preparing surface and painting with emulsion paint:- old surface 2 coats	Sft
6	13/31- i+li+ii	Preparing surface and painting with emulsion paint:- new surface 3 coats	3354 Sft
7	13/4-c	Painting old surfaces:- Painting doors and windows, any type: old surface 2 coats	7105.00 Sft
8	12/50	Providing and fixing 1½" (40mm) thick solid flush door shutter sterling or equivalent with commercial ply (5 mm thick) on both sides double pressed and deodar wood lipping 1½"x3/8" (40mm x 10mm) around shutter including chromium plated fitting, iron hinges with aluminium kick plate 22 SWG on both sides & finger plate complete in all respect.	159.50 Sft
9	13/5-c	Painting new surfaces:- Painting doors and windows, any type: new surface 3 coats	319.00 Sft
10	10/25	Laying floor of approved coloured glazed tiles ½ "(6 mm) thick, laid in white cement and pigment on a bed of ¾" (20 mm) thick cement mortar 1:2.	250.00 Sft
1	10/38	Coloured glazed tile dado ¼" (6mm) thick in pigment over 1:2 cement, sand mortar 3/4"(20mm) thick, including finishing.	1400.00 Sft
2	10/26	Rubbing and polishing old grit/ mosaic floor, including repairing voids, uneven surface, complete in all respects.	13108.00 Sft
	N.S	Civil Work N.S Providing & Fixing false ceiling of Gypsum 9mm thick as per approved design and sample and as directed by the engineer incharge. (N.S)	13108.00
		Providing and applying Textured resin plaster coating of Rockwall / sandtex / Graffiato with recommended sealer and thinner on the surface of cement plaster on the exterior surface of the building. The coaring shall be of approved colour and pattern. Surface should be prepared by removing dust, dirt, oil, sand and other foreign matters. Honey combing and stepped irregularities shall be corrected by toweling, apply it strictly in accordance with manufacturer's instructions, as per drawing, specification. Final coat shall be applied after the base coat has been inspected and approved by the Engineer Incharge.	Sft 23960.00
	N.S	Providing and fixing Door Hydraulic Machine (KB) including all hardware fitting pest quality complete in all respect as approved by Engineer Incharge.	Sft 10.00 No
	19/10 F	Plumbing Work Providing and fixing glazed earthen ware flat back urinal.	5.00 Nos
1	9/3-ii F	Providing and fitting glazed earthen ware water closet, squatter type (Orisa attern), combined with foot rest. Coloured	5.00 Nos

	1		
K	19/0-1	Description Providing and fitting glazed earthen ware wash hand basin 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc. coloured, with	Quantity
1		pedestal Providing and fitting plastic made low down flushing distern 13.63 litre (3	5.00 Nos
		gallons) capacity, including bracket set, copper connection, etc. complete. Coloured	5.00 Nos
5	19/29	Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.	5.00 Nos
6	19/27	Providing and fixing chromium plated tee stop cock '15mm (½").	10.00 Nos
7 8	19/26-11	Providing and fixing chromium plated bib cock:- 1.5 cm (½") Providing and fitting "P" trap:- 10 cm (4") glazed.	7.00 Nos 15.00
9	19/22	Providing and fitting:-	Nos
i		plastic soap dish	5.00 Nos
iii		plastic towel rail plastic shelf 60x13 cm (24"x5") with bracket and railing.	5.00 Nos 5.00 Nos
			1405
1	N.S	Plumbing Work N.S Providing, laying, fixing and testing uPVC Soil Waste, vent & rain water down pipe "NIKASI PIPES Durafit/ Beta/ Pak Arab/Equalvent" including uPVC fittings with solvent cement jointing or rubber ring joints complete in all respects including clamps, bends, tees, Y-tees, Cowl reducers, clean out WC- Elbow Adopter etc. 4" dia. Complete in all respects and as approved by Engineer Incharge	50.00
2		Providing and laying, cutting, jointing, testing and disinfecting PPRC pipe line(M.S Minhas pvt Ltd) for hot & cold water supply complete in all respects, i/c specials such as coupler, reducing socket, elbow, endcaps, male/female,threaded, fittings, like teese, adoptors to conect polydex pipes to other pipe and shower, wash basin, bibcock etc, Complete in all respect as per specifications and drawings and as approved by the Engineer Incharge.	Rft 100.00
3	N.S	Providing and laying, cutting, jointing, testing and disinfecting PPRC pipe line(M.S Minhas pvt Ltd) for hot & cold water supply complete in all respects, i/c specials such as coupler, reducing socket, elbow, endcaps, male/female, threaded, fittings, like teese, adoptors to conect polydex pipes to other pipe and shower, wash basin, bibcock etc, Complete in all respect as per specifications and drawings and as approved by the Engineer Incharge.	Rft
4	N.S	Providing & Fitting Steel floor jali best quality complete in all respect as per specifications and drawings and as approved by the Engineer Incharge.	150.00 Rft
5	N.S	Providing and fitting chromium Muslim Shower pest quality complete in all respects as approved by the engineer incharge (Porta or equivalent company)	Nos
6	N.S	Providing and fixing Coloured Glazed Earthen ware water closet Europen type Couple set including Flush Tank fixed with comode, hydraulic seat cover, sheet cover thimble, connection pipe Complete in all respect and approved by Factors (see the cover thimble).	5.00 Nos
-		(HD201 Porta or equivalent company)	5.00 No
1		Electric Work	
	24/10	Supply and erection of single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.l pipe/wooden strip batten/wooden casing an capping/G.l. wire/trenches (rate for cables only), 250/440 volts, PVC insulated: 3/0.74 mm (3/0.029")	1530.00
i		7/0.74 mm (7/0.029")	Meter 1260.00
ii		7/0.91 mm (7/0.036")	Meter 1260.00 Meter
ii		7/1.12 mm (7/0.044")	1260.00 Meter
2		7/1.63 mm (7/0.064") Supply and erection of copper conductor cables for service connection, in	1260.00 Meter
	24/13- viii		150.00 Meter
-	-		

		Description	Quantity
114		Description	1
Ti	NS	Electric Work N.S Supply & installation of PVC Exhaust fan 12" (99.99% Copper) I/c any supply & installation of PVC Exhaust fan 12" (99.99% Copper) I/c any accessories (i.e. screw. Rawi plug or steel nail, etc.) as required at site. accessories (i.e. screw. Rawi plug or steel nail, etc.) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (GFC, Royal, Pakfan or Equivalent)	20.00 No
2	N.S	Supply and Installation of Heat and Cool Floor Standing Split DC Inverter Air- sconditioner 2 00 Ton (24000BTU) complete with Installation Kit (Supplied with conditioner 2 00 Ton (24000BTU) complete with Installation Kit (Supplied with Thermal insulated Copper pipe) I/o any other accessories required at site. Thermal insulated Copper pipe) I/o any other accessories required at site. Complete in all respects as approved by Engineer Incharge. (PEL, Orient, Haier or Equivalent)	15.00 No
3	N.S	Supply & installation of Wall Bracket Fan 18" (19.99% Copper) I/c any accessories (i.e. mounting screws & etc.) as required at site. Complete in all accessories and approved by the Engineer Incharge (Younis, Tamoor, Pakfan or Equivalent)	50.00 No
4	N.S	Supply & installation of Multilight plug i/c any accessories (i.e. screw. Rawl plug or steel nail, etc.) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (KM, Hero, PPi or Equivalent)	100.00 No
5	N.S	Supply & installation of a Power plug 15A with plastic back box 3"x 3" i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips ECO Series Q2 or Equivalent)	100.00 No
6	N.S	Supply & installation of LED Ceiling Light 17W (recessed type, 220V~) i/c cutting holes to install in false (any type) i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips Essential or Equivalent)	750.00 No
7	N.S	Supply & installation of PVC cable trunk (Duct) 16x25mm i/c any accessories (i.e. screw. Rawl plug or steel nail, etc.) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (GM, Popular or Equivalent)	1000.00
8	N.S	Supply & installation of a Four Single Pole Switch Plate with plastic back box 3"x 3" i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips ECO Series Q2 or Equivalent)	100.00
9	N.S	Supply & installation of Wall Mounted LED Batten Light 20W (220V~, 6500K) i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips Slimline or Equivalent)	No 24.00
10	N.S	Supply & installation of Metal Body Wall Bracket Fan 24" (99.99% Copper) i/c any accessories (i.e. widing of mounting holes and 4.00nos of rawl bolts ¼" etc) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (SK mega or Equivalent)	No 2.00
11	N.S	Supply & installation of 2' x 2' False Ceiling Fan 14" swipe (99.99% Copper), remote controlled i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Royal, Super-asia or Equivalent)	No 30.00
12	N.S	Supply & installation of PVC cable trunk (Duct) 40x40mm i/c any accessories (i.e. screw. Rawl plug or steel nail, etc.) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (GM, Popular or Equivalent)	No 200.00
13	N.S	Providing & laying of PVC/PVC 3-Core flexible 40/0.0076" copper conductor cable i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (KM, Eagle or Equivalent)	70.00 Meter
14	N.S	Providing & laying of PVC/PVC 3-Core flexible 70/0.0076" copper conductor cable i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (KM, Eagle or Equivalent)	70.00 Meter
15	N.S	Supply and Installation of Heat and Cool Split DC inverter Air-conditioner 1.50 Ton (18000BTU) complete with Installation Kit (Supplied with Thermal insulated Copper pipe) i/c any other accessories required at site. Complete in all respects as approved by Engineer Incharge (GREE 18 FITH13,KENWOOD or Equivalent)	5.00 No

Established Lab Funded by PSF & HEC in Room 76 & 79 for the Department of Biochemistry & Biotechnology at Baghdad-ul-Jadeed Campus

Estimate Based on MRS, Jan to Jun, 2020

ABSTRACT OF COST

A)	Schedule Work		
1	Civil Work	Rs.	573,752.00
2	Electric Work	Rs.	519,331.00
	Total	Rs.	1,093,083.00
B)	Non-Schedule Work		
1	Civil Work	Rs.	3,356,558.00
2	Electric Work	Rs.	1,076,773.00
3	Plumbing Work	Rs.	161,749.00
	Total	Rs.	4,595,080.00
	Total A+B	Rs.	5,688,163.00
	Add 05% Punjab Sales Tax	Rs.	284,408.00
	Grand Total	Rs.	5972571.00

Sub-Engineer

Assistant Engineer

Executive Engineer 6 2010

Technically Sanctioned for Rs.5,972,571.00

Project Director

The Islamia University of Bahawalpur Established Lab Funded by PSF & HEC in Room 76 & 79 for the Departme Biotechnology at Baghdad-ul-Jadeed Campus

N	IRS Ref	Description	Quantity	
2000	4/49-b	Scraping Ordinary distemper, oil bound distemper, or paint of wall.	5634.00	Sft
	11/36	Petty repair to small room	2.00	No
	11/37	Petty repair to verandah room	2.00	No
	4/32-1	Removing door with chowkat.	3.00	No
5	4/32-ii	Removing windows and sky lights with chowkat.	8.00	No
3	4/48	Removing cement or lime plaster.	400.00	Sft
7	4/13	Dismantling brick work in lime or cement mortar.	36.00	Cft
8	4/19a	Dismantling cement concrete plain 1:4:8.	200.00	Cft
9	4/19c	Dismantling cement concrete 1:2:4 plain.	32.00	Cft
		b Preparing surface and painting with emulsion paint:-old surface 2 coats	5634.00	Sft
11	7/5	Pacca brick work in ground floor:- Cement, sand mortar:-	400.00	Cft
12	11/8-5	Cement plaster 1:3 upto 20' (6.00 m) height:- ½" (13 mm) thick		Sft
13	6/6	(a) (i) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects:- (3) (c) Type C (nominal mix 1: 2: 4)		Sit
14	6/9-1	Pabrication of mild stool reinfer	70.00	Cft
		Pabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars) deformed bars 40-Grade	250.00	
15	5 6/5		250.00	Kg
1	6 26/4		325.92	Cf
1	7 25/		2700.00	Sf
		Providing and fixing all types of partly fixed and partly openable glazed anodised bronze colour aluminium doors, using delux section of M/s Al-Cop or Pakistan 'Cables, having chowkat frame of size 40 x 100 mm (1½" x '4") and leaf frame of 60x40mm (2½"x1½") wide sections including the cost of ½" (5 mm) thick imported tinted 'glass with		
		aluminium triangular gola and rubber gasket to support the glass and leaf edging, using approved 'standard fittings, locks, 3" (75 mm) wide long handles etc., and hardware any required as approved by the engineer in-charge.	112.00	S

M. Asla -.

	RS Ref	Description	Quantit	y
1	75/63	Providing and fixing all types of glazed aluminium windows of anodized champagne colour partly fixed and party sliding using deluxe section of approved manufacturer having Frame of size 100mmx 30mm using frame at bottom, at top and side leaf frame sections of 60mm x 23mm at top & bottom and size 45mm x25mm at center and size 45mm x 25mm at sides, Jali leaf frame size 43mm x 13mm i/c fine quality aluminum jali, 5mm thick imported tinted glass with rubber gas ket using approved standard latches, wheel, stopper, brush chennel angle joint and hardware etc.complete in all respect 2 mm thick	126.00	Sf
1	N.S	Civil Work (Non-Schedule) Providing and laying Floor Tile 24"x24" Granite Effect (GEM) Dark Polished SB including 05% Wastage laid in cement with pigment on a bed of 3/4" thick cement sand mortar 1:2 i/c bond for fixing of tile complete in all respects as approved by Engineering incharge	5350.00	Sft
2	N.S	Providing and laying Tile Dado 9"x26" Size (51SF MPD538 & 757 Multi 9x26 Master and 24SF MPD748 Multi 9x26 Master) including 05% Wastage laid in cement with pigment on a bed of 3/4" thick cement sand mortar 1:2, complete in all respects as approved by Engineering incharge	800.00	04
3	N.S	Providing and laying Granite Marble Slab (SADU Grey) including 05% Wastage laid in cement with pigment on a bed of 3/4" thick cement sand mortar 1:2 including grinding & chemical polishing complete in all respects as approved by Engineering incharge	240.00	Sft
4	N.S	Providing, Fabricating and fixing 16 SWG M.S sheet hollow pressed Jamb frame (Factory primme) for door welded with MS flat size 6"x1.5"x3/16", hold fast i/c welding/screwing 5" long iron hinges, filling concrete for the jamb frame and embedding hold fast in the adjointing walls with 1:2:4 concrete, enamel painting etc. complete in all respects as show on the drawing and/ or as directed by the engineer, in conformance with following size 10"x2-1/2"		
5	N.S	Providing and fixing wooden door shutter soild (Red Oak-859 imported) 40mm thick including tower bolt and all hardware fitting best quality complete in all respect as approved by	56.00	Sft
6	N.S	Providing and fixing Door Closer (Royalwand 604 Coffee) including all hardware fitting best quality complete in all respect as approved by Engineer Incharge.	56.00 4.00	Sft
7	N.S	Providing and fixing Door Lock (RW-46 MSN Royalwand) including all hardware fitting best quality complete in all respect as approved by Engineer Incharge.	2.00	No
8	N.S	Polishing of doors with best quality Mat polish complete in all respect as approved by Engineer Incharge.	200.00	Sft
9	N.S	Providing and fixing of Glass Window 8mm thick with Aluminum Section D-15, D-16 2mm thick for fix portion including any asscessories required at site completed in all respect as approved by Engineer Incharge.	132.00	Sft

, m_Lateralnut

M. Aslow.

	AS Ref	Description	Quantity	,
	N.S	Providing and fixing Roller Blinds fixing in position as per approved design and sample complete in all respect as approved by the engineer incharge.	300.00	Sft
k	N.S	M.S Steel Grill for windows comprising of 1/2"x1/2" square bar with 1.25"x1.25"x1/8" MS angle iron for frame including painting 3 coats complete in all respect as shown on the drawings, specification and/ or as directed by the Engineer incharge	150.00	Sft
13	N.S	Providing and fixing 3/4" thick Leminated Board shutter for laboratory cabinet with 3/4" x 3/4" deodar wood beading including tower bolts on top & bottom lock 808, hinges, polishing complete in all respects as approved by the Engineer Incharge.	105.00	Sft
14	N.S	Providing & Fixing false ceiling of Gypsuim 9mm thick including all accessories, network & hardware etc complete in all respects as per approved design and sample and as directed by the engineer incharge.	1100.00	Sft
15	N.S	Providing & Fixing wooden drawer consisting of kail wood 3/4" thick size 1.50'x1.50'x6", wooden frame vertical 2"x2", Horizantol 1"x2", 3.50'x1.58' and hard board for drawer bottom including siprit polish complete in all respects as per design, drawing & patern as approved by the Engineer Incharge	70.00	Sft
16		Providing & Fixing Cabnet upper portion consisting of lamination board 3/4" thick box and leaves, Partal wood frame 3" x 1", Gola for 'leaf 3/4" x 3/4" including siprit polish for gola complete in all respects as per design, drawing & patern as approved by the Engineer Incharge	243.00	Sft
17	N.S	Supply, farbication and erection/ installation of fully glazed curtain wall comprising of tempeed 12 mm thick approved quality/ make, fixing with approved size and shade aluminum section (powder coated / anodized), including tear resistant saftey film (125 micorn) of approved pattern on glass, complete with all accessories to complete the installation.	423.00	Sft
18	N.S	Providing and Making Wooden Table 15'x6' using 3/4" thick Leminated Board, Kail wood for frame, PVC Gola 3/4", lemination sheet for top, leaves and lasani hard board for back side including Handle, Lock, Kitchen hinges, press sheet complete in all respects as approved by the Engineer Incharge.	1.00	No
		Electrical Work		
1	24/3	Supply and erection of PVC pipe for wiring recessed in walls, including inspection boxes, pull boxes, hooks, cutting jharries,and repairing surface, etc., complete with all specials i) 3/4" i/d (20 mm) ii) 1" i/d (25 mm)	260.00 450.00	Rft Rft
2	24/4	Supply and erection of PVC pipe for wiring on surface including clamps inspection boxes, pull boxes, bends, tees, repairing surface, etc., complete with all specials:- i) 3/4" i/d (20 mm) ii) 2" i/d 50 mm i/d	100.00 300.00	Rft Rft
3	24/10a-i	Supply and erection of single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches (rate for cables only).250/440 volts, PVC insulated:		
		3/0.74 mm (3/0.029") 7/0.74 mm (7/0.029") 7/0.91 mm (7/0.036")	4000.00 3500.00 100.00	Rft Rft Rft

4	5 Ref	Description	Quantity	
A		7/1.12 mm (7/0.044")	4600.00	Rf
r		7/1.63 mm (7/0.064")	1000.00	R
		19/1.32 mm (19/0.052")	875.00	R
	N.S	Electric Work (Non-Schedule) Supply & installation of LED 2'x 2' Ceilling Panel Light 40W		
		(220V~, CW or WW) I/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Phillips 36S/865 PSU W60L60 GM G2 or Equivalent)	40.00	N
	N.S	Supply & installation of LED Ceiling Light 17W (6" recessed, 220V~) i/c cutting holes to install in false (any type) i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips	45.00	
		Meson or Equivalent)	15.00	N
	N.S	Supply & installation of LED 17W Down Light (6" Surface		
		Mounted, 220V~) i/c any accessories required at site.		
		Complete in all respect as directed and approved by the Engineer Incharge (Philips Meson or Equivalent)	6.00	N
	N.S	Supply & installation of Wall Mounted LED Batten Light 20W (220V~, 6500K) i/c any accessories required at site. Complete in all respect as directed and approved by the		
		Engineer Incharge (Philips Slimline or Equivalent)	10.00	N
5	N.S	Supply & installation of Wall Bracket Fan 18" (99.99% Copper) i/c any accessories (i.e. mounting screws & etc) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (Younis, Tamoor, Pakfan		
		or Equivalent)	2.00	N
6	N.S	Supply & installation of Metal Body Wall Bracket Fan 24" (99.99% Copper) i/c any accessories (i.e. widing of mounting holes and 4.00nos of rawl bolts ¼" etc) as required at site. Complete in all respect as directed and approved by the Engineer Incharge	4.00	N
7	N.S	Supply & installation of PVC Exhaust fan 12" (99.99% Copper) i/c any accessories (i.e. screw. Rawl plug or steel nail, etc.) as required at site. Complete in all respect as directed and approved by the Engineer Incharge (GFC, Indus, Pakfan or Equivalent)	5.00	N
8	N.5	Supply and Installation of Stainless Steel/Aluminum Exhaust Hood with exhaust fan (170W) and 4 x20W halogen lamp i/c any other accessories required at site. Complete in all respects as approved by Engineer Incharge. (Canon-HD-GL9011 or Equivalent)	4.00	1
9	N.S	Supply & installation of Universal 3-Pole Socket with 13A Switch with plastic back box 3"x 3" i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips ECO Series Q2 or Equivalent)	60.00	
10) N.:	S Supply & installation of a Power plug 15A with plastic back box 3"x 3" i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (Philips ECO Series Q2 or Equivalent)	60.00	

1		Quantity	
LI	Description Descr		
The second second second	Description Descr		
RS Rel	Supply & installation of a Double of a Dou	7.00	Ma
NS	Supply 8 Incharge (Phillips ECO Series Q2 or Equivalent) Single Complete in all respect as directed and approved by single Complete in all respect as directed and approved by single Pole Switch Plate with	2.00	No
	- intelligence of the plate will I		
	of a Four Street at Site,		
NS	Supply & installation of any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required at the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by the plastic back box 3"x 3" i/c any accessories required by accessories b		
100	plastic back by plastic back as directed and are Equivalent)	4.00	No
3	plastic back box 3 x 3 Complete in all respect as directed and approved by the Complete in all respect as directed and approved by the Complete in all respect as directed and approved by the Complete in all respect to Rolle Switch Plate with		
	Engineer Incharge (1) Engineer Incharge (1) Supply & installation of a Six Single Pole Switch Plate with Supply & installation of a Six Single Pole Switch Plate with Supply & installation of a Six Single Pole Switch Plate with		
	Supply & installation of a Six Single Pole Switch Flats and Supply & installation of a Six Single Pole Switch Flats and Supply & installation of a Six Single Pole Switch Flats and Six Six Six Six Six Single Pole Switch Flats and Six		
N.S	Lack DOX of the Land approved by the		
	plastic beam all respect as directed and appropriate in all respect as directed and all respect and all respect as directed and all respect as directed and a	2.00	No
	lessinger Incharge.		
	- La Gingle Pole Switch Plate with		
N.S	Supply & installation of a Eight Single Pole Switch Plate with Supply & installation of a Eight Single Pole Switch Plate with		
N.5	plastic back box 3 x 0 " directed and approved by the		
	plastic back box 3"x 6" 1/c any accessorious plastic back box 3"x	5.00	No
	Complete in all respect as directed directed and experience Complete in all respect as directed directed and experience Complete in all respect as directed directed and experience Complete in all respect as directed directed directed and experience Complete in all respect as directed direct		,,,
	Supply & installation of a Four Single Pole Switch & Two		
N.S	Supply & installation of a Four engagement of a Four engagement as 2-Pin Socket Plate with plastic back box 3"x 6" i/c any		
	2-Pin Socket Plate with Plates and 2-Pin Socket Plate with Plates and 2-Pin Socket Plate with Plates and 2-Pin Socket Plates with Plates and 2-Pin Socket Plates and 2-Pin Soc		
	directed and approved by the Engineer Incharge. (Philips	4.00	No
100	ECO Series Q2 or Equivalent		
IS N.S	Supply & installation of PVC cable trunk (Duct) 16x25mm i/c		
16 N.S	lany accessories (i.e. screw. Rawl plug or steel nail, etc.) as		
	required at site. Complete in all respect as directed and		
	approved by the Engineer Incharge (GM, Popular or	100.00	Rft
	Equivalent)		
110	Supply & installation of 2' x 2' False Ceiling Fan 14" swipe		
17 N.S	(99.99% Copper), remote controlled i/c any accessories		
	required at site. Complete in all respect as directed and		
	approved by the Engineer Incharge (Royal, Super-asia or		
	Equivalent)	10.00	No
			110
18 N.S	(= ===)		
	i/c any accessories (i.e. screw. Rawl plug or steel nail, etc.)		
	as required at site. Complete in all respect as directed and approved by the Engineer Incharge (GM, Popular or		
	Equivalent)	100.00	Rft
		14-11-1	
		n	
19 N.	paper, metallication & commissioning of distribution		
19 N.	boards, (DBs), Open type Wall mounted design, made of M.S.		
19 N.	boards, (DBs), Open type Wall mounted design, made of M.S Sheet 18 SWG with hinged glass door, handle, and 2 coats of		
19 N.	boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main		
19 N	boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main Molded Case Circuit Breaker of 125 Amps T-p (15KA) 1.00		
19 N	boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main Molded Case Circuit Breaker of 125 Amps T-p (15KA) 1.00 No, Distribution Miniature Circuit Breaker of 10/20 Amps S-p.		
19 N	boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main Molded Case Circuit Breaker of 125 Amps T-p (15KA) 1.00 No, Distribution Miniature Circuit Breaker of 10/20 Amps S-p (6KA) 24.00 Nos, LED phase light volt meter type (RYB), Earthling bar, Neutral bar and any accessories (i.e.		
19 N	boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main Molded Case Circuit Breaker of 125 Amps T-p (15KA) 1.00 No, Distribution Miniature Circuit Breaker of 10/20 Amps S-p (6KA) 24.00 Nos, LED phase light volt meter type (RYB), Earthling bar, Neutral bar and any accessories (i.e. Earth/neutral bar, Nut/bolts, Screws/rawl plugs, Jumper		
19 N	boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main Molded Case Circuit Breaker of 125 Amps T-p (15KA) 1.00 No, Distribution Miniature Circuit Breaker of 10/20 Amps S-p (6KA) 24.00 Nos, LED phase light volt meter type (RYB), Earthling bar, Neutral bar and any accessories (i.e. Earth/neutral bar, Nut/bolts, Screws/rawl plugs, Jumper connections & etc.) required at site. Complete in all respects		
19 N	boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main Molded Case Circuit Breaker of 125 Amps T-p (15KA) 1.00 No, Distribution Miniature Circuit Breaker of 10/20 Amps S-p (6KA) 24.00 Nos, LED phase light volt meter type (RYB), Earthling bar, Neutral bar and any accessories (i.e. Earth/neutral bar, Nut/bolts, Screws/rawl plugs, Jumper connections & etc.) required at site. Complete in all respects as approved by the engineer incharge. (for MCCB & MCBs	i. f	
	boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main Molded Case Circuit Breaker of 125 Amps T-p (15KA) 1.00 No, Distribution Miniature Circuit Breaker of 10/20 Amps S-p (6KA) 24.00 Nos, LED phase light volt meter type (RYB), Earthling bar, Neutral bar and any accessories (i.e. Earth/neutral bar, Nut/bolts, Screws/rawl plugs, Jumper connections & etc.) required at site. Complete in all respects as approved by the engineer incharge. (for MCCB & MCBs Hitachi, Schneider Electric, Legrand or equivalent).		No
	boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main Molded Case Circuit Breaker of 125 Amps T-p (15KA) 1.00 No, Distribution Miniature Circuit Breaker of 10/20 Amps S-p (6KA) 24.00 Nos, LED phase light volt meter type (RYB), Earthling bar, Neutral bar and any accessories (i.e. Earth/neutral bar, Nut/bolts, Screws/rawl plugs, Jumper connections & etc.) required at site. Complete in all respects as approved by the engineer incharge. (for MCCB & MCBs Hitachi, Schneider Electric, Legrand or equivalent).	2.00	No
	boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main Molded Case Circuit Breaker of 125 Amps T-p (15KA) 1.00 No, Distribution Miniature Circuit Breaker of 10/20 Amps S-p (6KA) 24.00 Nos, LED phase light volt meter type (RYB), Earthling bar, Neutral bar and any accessories (i.e. Earth/neutral bar, Nut/bolts, Screws/rawl plugs, Jumper connections & etc.) required at site. Complete in all respects as approved by the engineer incharge. (for MCCB & MCBs Hitachi, Schneider Electric, Legrand or equivalent). N.S. Providing and Laying earthing for Electric Machines I/c boring up to moisture level (up to 60' below ground level) 4" i/d	2.00	No
	boards, (DBs), Open type Wall mounted design, made of M.S. Sheet 18 SWG with hinged glass door, handle, and 2 coats of Approved paint, (Size 24"x18") including Incoming Main Molded Case Circuit Breaker of 125 Amps T-p (15KA) 1.00 No, Distribution Miniature Circuit Breaker of 10/20 Amps S-p (6KA) 24.00 Nos, LED phase light volt meter type (RYB), Earthling bar, Neutral bar and any accessories (i.e. Earth/neutral bar, Nut/bolts, Screws/rawl plugs, Jumper connections & etc.) required at site. Complete in all respects as approved by the engineer incharge. (for MCCB & MCBs Hitachi, Schneider Electric, Legrand or equivalent).	2.00	No

	NS Ref	Description	Quantit	1
1		run in PVC pipe 20mm i/d, 1¼" i/d GI pipe 5' long, GI tee & plug for watering also includs common salt, Lime (slaked) & charcoal around copper strip I/c connecting with Electric machine. Complete in all respects as approved and as directed by the engineer incharge.	4.00	No
21	N.S	Supply and installation of 120mm², Aluminum Alloy Parallel Groove Clamp complete with nut/bolts i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge.	8.00	No
22	N.S N.S	Providing & laying of PVC/PVC 3-Core flexible 70/0.0076" copper conductor cable i/c any accessories required at site. Complete in all respect as directed and approved by the Engineer Incharge (KM, Eagle or Equivalent) Providing & laying of PVC/PVC 3-Core flexible 110/0.0076" copper conductor cable i/c any accessories required at site. Complete in all respect as directed and approved by the	50.00	М
		Engineer Incharge (KM, Eagle or Equivalent)	30.00	M
		Di il		
2	N.S	Plumbing Work (Non-Schedule) Providing, Laying, Fixing, testing uPVC (Dadex/Beta/Pakarab) plain ends socket pipe Type-B soil wste, vent & rain water as per approved make and quality i/c uPVC fitting with solvent cement jointing or rubber ring joints complete in all respects i/c clamps tees complete in all respects as approved by the engineer incharge. i) uPVC Pipe 4" dia ii) uPVC Pipe 6" dia Providing and laying, cutting, jointing, testing and disinfecting PPRC pipe line for hot and cold water supply complete in all respect socket, elbow, encaps, male/ female, threaded, fitting, like teese, adoptors to connect polydex pipes to other pipe and shower, wash basin, bibcock etc. as required at site.	20.00 200.00	Rft Rft
3	N.S	i) 25mm o/d (Dadex/Beta/BBJ) ii) 32mm o/d (Dadex/Beta/BBJ)	50.00 200.00	Rft Rft
		Providing & Fixing Stop Valve complete in all respects, as approved by the Engineer Incharge. i) 25mm ii) 32mm	2.00	No
4	N.S	ii) 32mm Providing & Fitting Steel floor jali best quality complete in all respect as per specifications and drawings and as approved by the Engineer Incharge.	2.00	No
5	N.S	Providing and fitting chromium plated Tee stop cock (817T Porta) best quality complete in all respects as approved by the engineer incharge (817T Porta or equivalent company)	10.00	No
6	N.S	Providing & Fixing uPVC "P" trap 4" dia complete in all respect as approved by the Engineer Incharge.	3.00	No
7	N.S	Providing and fitting chromium plated Bib cock (Porta) best quality complete in all respects as approved by the engineer incharge (Porta or equivalent company)	6.00	No
8	N.S	Providing and fitting glazed earthen ware Laboratory Sink 56x40 cm (22"x16") including waste pipe and waste coupling, etc. complete in all respect as approved by the engineer incharge.	1.00	No
9	N.S	Providing and fixing, chromium plated Laboratory Cock (3-way) Dilawar complete in all respect as approved by the engineer incharge.	3.00	No
			3.00	No

Renovation of Guest House (Main Entery & VVIP Block) at Abbasia Campus

Estimate Based on MRS Jan to July, 2020

ABSTRACT OF COST

A SCHEDULE WORK Civil Works	Rs.	624,156.04
II Electrical Works	Rs.	98,299.25
III Plumbing Works	Rs.	-
Total	Rs.	722,455.00
B NON SCHEDULE WORK Civil Works	Rs.	1,933,599.70
II Electrical Works	Rs.	115,347.92
III Plumbing Works	Rs.	492,481.28
Total	Rs.	2,541,429.00
Total (A+B)	Rs.	3,263,884.00
Add 16% Pst	Rs.	522,222.00
	Rs.	3,786,106.00
Grand Total		11

Executive Engineer (M)

Sub-Engineer

Technically Sanctioned for Rs.3786106/-

Project Director

Assistant Engineer

The Islamia University of Bahawa Renovation of Guest House (Main Entery & VVIP Block) at

#	_	Discription	REF	Qty	
#	CIVILV	Vork (Schedule Items)			
1	Disma	ntling glazed or encaustic tiles, etc. (4/50)	4/50	864.00	Sft
2	Disma	intling cement concrete 1:2:4 plain. (4/19c)	4/19c	314.01	Cft
3	Disma (4/19)	00 0	4/19d	863.52	Cft
4	11/2"	to 2"(40 mm to 50 mm) gauge mixed with 25%, for floor foundation, complete in all respects.	10/3	863.52	Cft
5	Ren	noving cement or lime plaster. (4/48)	4/48	1,510.00	Sft
(see brick work in ground floor ment, sand mortar:- 'Ratio 1:3 (7/4i)	7/4i	75.00	Cft
1		ement plaster 1:4 upto 20' (6.00 m) heigh " (13 mm) thick (11/9b)	11/19b	1,958.00	Sft
1	_	craping Ordinary distemper, oil bound distemper, or aint of wall. (4/49b)	4/49b	4,148.00	Sft
		Cement pointing struck joints, on walls, upto 20' (6.00 m) hiehgt:- Ratio 1:2 (11/18a)	11/18a	710.00	Sft
	10	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer	13/32b		
		complete in all respect: on old surface (13/32b)		4,960.00	Sft
	11	Painting doors and windows, any type: two coat on old surface (13/4c)	13/4c	2,768.00	Sft
	12	Petty repair to main rooms. (11/35)	11/35	3.00	Nos
	13	Petty repair to small room. (11/36)	11/36	2.00	Nos
	14	Preparing surface and painting with emulsion paint:- two coats (13/31a+b)	13/3 1a+b	6,746.50	Sft
	15	Cement concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate): (f) Ratio 1: 2: 4 (6/5f)	6/5f	200.00	Cft
	16	Painting old surfaces:- Painting sashes, fanlights, glazed or gauzed doors and windows:- two coats (13/5b)	13/5b	500.00	Sft
	17	Removing door with chowkat.	4/32a	8.00	Nos
	18	Providing and fixing 1½" (40 mm) thick deodar woo panelled or panelled and glazed, doors and windows with mild steel chowkat (frame), etc. complete in all respects (excluding sliding bolt or lock) with: M.S. angle iron 1½"x1½"x½", welded (40 mmx40	,	266.00	Sft
	1	M.S. angle iron 1½"x1½"x¼", welded (40 mmx40 mmx 6mm) with M.S. flat 2"x¼" (50 mm x 6 mm)	12/48ii	266.00	Sft

The Islamia University of Buhuwa Renovation of Guest House (Main Entery & VVIP Block) at A

#	Discription	REF	Qty
1 8 0 1 0	Providing and laying floors of a approved Dark coloured glazed Graynite tiles size 16"x16" dry Venied/ application DWV series polished dark class SB (Master Company) laid in white cement pigment on a bed of 3/4" thick cement mortar 1: Complete in all respect and as approved by the Engineer Incharge.	wet/ colour at and 2	2,616.75 Sft
-	Providing and fixing PVC imperial/Akbari co w panelling using PVC gola and joints as approve coloured & Design as approved sample comple all respects & as approved by the engineer incha	d	5,460.00 Sft
3	In-		
3	Providing and laying floors tiles 12"x18" (Mast of a approved SP series matching colour base glossy/matt light colour rectified SP laid in whicement and pigment on a bed of 3/4" thick cemmortar ratio 1:2 complete in all respect and as approved by the Engineer Incharge.	ite	192.00 Sft
4		e ite	672.00 Sft
	Providing & fixing false ceiling of Gypsuim 9n thick complete in all respects and as approval o sample by the Engineer incharge.	nm N/S	1,816.75 Sft
(Providing & Fixing door stoper for door best question complete in all respects as per approved and as directed by the Engineer incharge.	uality N/S	8.00 Nos.
	Providing and laying skirting or dado 16"x16" approved Dark coloured glazed Graynite tiles" wet/ Venied/ application DWV series polished colour class SB (Master Company) laid in whit cement and pigment on a bed of 3/4" thick cemortar 1:2 on . Complete in all respect and as approved by the Engineer Incharge.	dry dark de	310.50 Sft
	Providing & laying Boarder tiles for dado 3" w (Master Co.) of approved matching colour bas (Grossy) dark colour laid in white cement and on a bed of 3/4" thick cement sand mortar ratic Complete in all respect as apprved by the Engilncharge.	pigment on 1:2.	112.00 Rft
	Electrical Work (Schedule Items) Supply and erection of PVC pipe for wiring re in walls, including inspection boxes, pull box hooks, cutting jharries, and repairing surface, of complete with all specials.	es,	
	i 20 mm i/d ii 25 mm i/d		300.00 Rft 250.00 Rft
	2 Supply and erection of single core PVC insul copper conductor cables, in prelaid PVC pipe conduit/G.l pipe/wooden strip batten/wooder an wire/trenches (rate for cables).capping/G	e/M.S.	
	250/440 volts. PVC insulated: i) 3/0.74 mm (3/0.029") ii) 7/0.74 mm (7/0.029") iii) 7/0.044" iv) 7/0.036"		600.00 Rft 300.00 Rft 500.00 Rft 200.00 Rft

The Islamia University of Bahawa Renovation of Guest House (Main Entery & VVIP Block) at

	Discription	REF	Qty
Suppl	y and erection of ceiling rose, bakelite.	24/30	20.00 Nos.
Suppl size.	y and erection of button holder, bakelite large	24/39	25.00 Nos.
Prov	trical Work (Non Schedule Items) widing & Fixing China Sheet with switches (Futina ss or Hi-Life) and underground PVC box applete in all respects as per approved design and apple and as directed by the Engineer incharge.	, N/S	
8 8	witches + 2 socket		8.00 Nos.
100	witches + 2 socket		4.00 Nos. 8.00 Nos.
	switches + 2 socket		4.00 Nos.
	switches + 1 socket ell Push		4.00 Nos.
	V Socket		4.00 Nos. 4.00 Nos.
	elephone Socket		8.00 Nos.
-	Oouble Light Plug Light Plug single		8.00 Nos.
2	Providing & Fixing China Sheet power plug with switches (Futina, Klass or Hi-Life) and underground PVC box complete in all respects as per approved design and sample and as directed by the Engineer incharge.	N/S	4.00 Nos.
3	Providing & fixing Fan Dimmer for China Sheet (Futina, Klass or Hi-Life) complete in all respect an as approved by the Engineer Incharge		4.00 Nos.
4	Providing & Fixing Distribution board of MS Sheet SWG size 2'x1.5' complete in all respect with handle locking system with anemal paint including 5 Nos 2 Amps, 5 Nos 10 Amps, 9 Nos 6 Amps, single phase Standerd MCB china made (Lair, hi life & ABB), was 100 AM TP Tarasaki Japan made with 3 nos. volt meter, 3 nos. phase light wth wiring of penal complinal respect as approved by the engineer incharge.	oth	2.00 Nos.
1	Plumbing Work (Non-Schedule Item) Providing, laying, cutting, jointing, testing, and disinfecting PPRC pipeline for hot & cold water supply complete in all respects, i/c specials such as coupler, wash basin, bibcock etc, as required at site.connect polydex pipes to other pipe and shower,male/female, threaded, fitting, like tees, adaptors to reducing socket, elbow, endcans.	N/S	215.00 Rft
	i) 25 mm o/d (Dadex / Beta / BBJ) ii) 32 mm o/d (Dadex / Beta / BBJ)		332.00 Rft
2	Providing and fitting uPVC "P" trap 10 cm (4") di complete in all respect approved by the Engineer Incharge		10.00 No
3	Providing, laying, fixing and testing uPVC plain encocketed pipes. Soil Waste, vent & rain water as paperoved make and quality including uPVC fittings solvent cement jointing or rubber ring joints complete solvent cement jointing clamps, tees, Y-tees, Cowlall respects including clamps, tees, Y-tees, Cowlarducers, clean out WC- Elbow Adopter etc. compreducers, clean out WC- Elbow Adopter etc. compreducers, clean out WC- Elbow Adopter etc. and in all respects 4" (110mm) dia Pipe Dadex/Beeta	ete in	110.00 F

The Islamia University of Bahaws Renovation of Guest House (Main Entery & VVIP Block) at

1	Dissolution	DEE	Oty	
1	Discription	REF	Qty	
	providing, laying, fixing and testing uPVC plain ends socketed pipes. Soil Waste, vent & rain water as per approved make and quality including uPVC fittings with solvent cement jointing or rubber ring joints complete in all respects including clamps, tees, Y-tees, Cowl reducers, clean out WC- Elbow Adopter etc. complete in all respects 3" dia (82mm) Pipe Dadex/Beeta	N/S		
			110.00	Rft
5	Providing & Fixing Water Closet (WC) HDD9 Porta or equivalent company Coloured, complete in all respects & as approved by the Engineer Incharge.	N/S	4.00	Nos.
6	Providing & Fixing wash hand basin with pedestal coloured "IFO" model HD16 Porta or equivilent Quality) complete in all respects & as approved by the Engineer Incharg.	N/S	4.00	Nos.
7	Providing & Fixing Flush Tanki Slim line (HD3 Porta or equivilent Quality) complete in all respects & as approved by the Engineer Incharg	N/S	4.00	Nos.
8	Providing & Fixing Comoode Couple set IFO model (HD 201 Porta or equivilent Quality) complete in all respects & as approved by the Engineer Incharge	N/S	4.00	Nos.
9	Providing & Fixing mirror 2'x2' size best quality complete in all respects & as approved by the Engineer Incharg	N/S	4.00	Nos.
10	Providing & Fixing chromium plated (CP) Bath Set model No. 421/424 included Wall Shower, Basin Mixture, Tee cocks & Muslim shower with double Bibcock Sonex or equivilent, best quality complete in all respects & as approved by the Engineer Incharge	N/S	4.00	Nos.
11	Providing & Fixing Bath Set full steel (Shelf, Towel Rail, Tooth Bursh Holder & Soap Dish) Choice or equivilent, best quality complete in all respects & as approved by the Engineer Incharge	N/S	4.00	Nos.
12	complete in all respect & as approved by the Engineer Incharge	N/S	8.00	Nos.
13	Providing & Fixing Stainless Steel Flush Bend 1.25" dia (heavy duty), complete in all respects & as approved by the Engineer Incharge.	N/S	4.00	Nos.
		4334		